

MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

	MAINTENANCE	REPORT		REPORT #3	
Complete this report at the time of					
days). Complete this report whenever the instrument is serviced or repaired and whenever it is placed					
into service. Retain the original a	~ *	hin 15 days to the		gram, DHSS.	
INTOX EC/IR II SN	NAME OF AGENCY		DATE OF INSPECTION		
12684	SPRINGFIELD POL	TCE DEPT	01/02/2023		
	LOCATION OF INSTRUMENT (STREET AND CITY)		TIME OF INSPECTION		
2620 W BATTELFIELD SPRINGFIELD, MO			10:25 CST		
CHECKLIST: Place a mark in the box by each item if found to be satisfactory or is operating within					
established limits. (Write in observed values where determined). Unmarked items must be corrected before using instrument.					
X DIAGNOSTIC RECORD					
X BLANK CHECK		х соз снеск			
X FC 1 TEMP		X FLOW CHECK			
X SRC TEMP		X FCB CHECK			
X DET TEMP		CRC COMP CHE	CK		
X BT TEMP		X CRC CAL CHEC	K		
X STD 2 TEMP		X PRINT TEST	· · · · · · · · · · · · · · · · · · ·		
х етн снеск					
BREATH ANALYZER ACCURACY STANDA	RDS				
SIMULATOR SOLUTION		COMPRESED F	THANOL-GAS MIXTU	DR	
	IMETERS	LOT# AG215102	EXP. DATE 05/31/2024		
SIMULATOR TEMP (34°C ±0.2°C)	SIM.	SN	SIM. NIST EXP I	DATE	
X CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT)					
X CALIBRATION CHECK - (ONLY ONE	S STANDARD IS TO	BE USED PER MAIN	TENANCE REPORT)		
CALIBRATION CHECK - (ONLY ONE Run three tests using a stand				of the standard value	
Run three tests using a stand and must have a spread of .00	dard solution. A	all three tests m	ust be within +5		
Run three tests using a stand	dard solution. A	all three tests m	ust be within +5		
Run three tests using a stand and must have a spread of .00	dard solution. A 05 or less. Mark	all three tests m	ust be within ±5° onding to the sta		
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A	all three tests m the box corresp and 0.105% INCLUS and 0.084% INCLUS	ust be within ±5° onding to the sta IVE IVE		
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A	all three tests m the box corresp and 0.105% INCLUS and 0.084% INCLUS	ust be within ±5° onding to the sta IVE IVE		
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A BETWEEN 0.038% A	the box corresp and 0.105% INCLUS and 0.084% INCLUS and 0.042% INCLUS	ust be within ±5° onding to the sta IVE IVE	andard solution being	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A	the box corresp and 0.105% INCLUS and 0.084% INCLUS and 0.042% INCLUS	ust be within ±5° onding to the sta IVE IVE	andard solution being	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A BETWEEN 0.038% A	the box correspond 0.105% INCLUS INCLUS INCLUS INCLUS INCLUS INCLUS	ust be within ±5° onding to the state of the	andard solution being 0 g/210L	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A BETWEEN 0.038% A	the box correspond 0.105% INCLUS INCLUS INCLUS INCLUS INCLUS INCLUS	ust be within ±5° onding to the state of the	andard solution being 0 g/210L	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST 1 0.100 g/210L REFUSALS 0 004 12 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A BETWEEN 0.038% A TEST 2 0.100 TESTS IN THE FOLL 0509 0	the box correspond of	ust be within ±5° onding to the state of the	o g/210L TENANCE REPORT: OVER .19 1	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEFUSALS 0 004 12	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A BETWEEN 0.038% A TEST 2 0.100 TESTS IN THE FOLL 0509 0	the box correspond of	ust be within ±5° onding to the state of the	o g/210L TENANCE REPORT: OVER .19 1	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST 1 0.100 g/210L REFUSALS 0 004 12 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A BETWEEN 0.038% A TEST 2 0.100 TESTS IN THE FOLL 0509 0	the box correspond of	ust be within ±5° onding to the state of the	o g/210L TENANCE REPORT: OVER .19 1	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST 1 0.100 g/210L REFUSALS 0 004 12 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A BETWEEN 0.038% A TEST 2 0.100 TESTS IN THE FOLL 0509 0	the box correspond of	ust be within ±5° onding to the state of the	o g/210L TENANCE REPORT: OVER .19 1	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST 1 0.100 g/210L REFUSALS 0 004 12 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A BETWEEN 0.038% A TEST 2 0.100 TESTS IN THE FOLL 0509 0	the box correspond of	ust be within ±5° onding to the state of the	o g/210L TENANCE REPORT: OVER .19 1	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST 1 0.100 g/210L REFUSALS 0 004 12 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A BETWEEN 0.038% A TEST 2 0.100 TESTS IN THE FOLL 0509 0	the box correspond of	ust be within ±5° onding to the state of the	o g/210L TENANCE REPORT: OVER .19 1	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST 1 0.100 g/210L REFUSALS 0 004 12 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A BETWEEN 0.038% A TEST 2 0.100 TESTS IN THE FOLL 0509 0	the box correspond of	ust be within ±5° onding to the state of the	o g/210L TENANCE REPORT: OVER .19 1	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH THE SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST AND WITHIN ESTABLISH AND WIT	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A BETWEEN 0.038% A TEST 2 0.100 TESTS IN THE FOLL 0509 0	the box correspond of	ust be within ±5% onding to the state ive ive ive ive ive ive ive items and include items and items and include items and item	o g/210L TENANCE REPORT: OVER .19 1	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TREFUSALS 0 004 12 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND WITHIN ESTABLISH A	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A BETWEEN 0.038% A TEST 2 0.100 FESTS IN THE FOLL .0509 0 FRATION OR MODIFICATION IMITS (USE OTHER SIDE	the box correspond of	ust be within ±5% onding to the state ive ive ive ive ive ive ive items and include items and items and include items and item	o g/210L TENANCE REPORT: OVER .19 1	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TREFUSALS 0 004 12 LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALTIST AND DESCRIBE AND DESCRIBE ANY ALTIST AND DESCRIBE AND DE	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A BETWEEN 0.038% A TEST 2 0.100 TESTS IN THE FOLL .0509 0 PRATION OR MODIFICATION TESTS (USE OTHER SIDE	the box correspond of	ust be within ±5% onding to the state of the	o g/210L TENANCE REPORT: OVER .19 1	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TREFUSALS 0 004 12 LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALTIST AND DESCRIBE AND DESCRIBE ANY ALTIST AND DESCRIBE AND DE	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A BETWEEN 0.038% A TEST 2 0.100 FESTS IN THE FOLL .0509 0 FRATION OR MODIFICATION IMITS (USE OTHER SIDE	the box correspond of	ust be within ±5% onding to the state of the	o g/210L TENANCE REPORT: OVER .19 1	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TREFUSALS 0 004 12 LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALTISTACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALTIST AND DESCRIBE AND DESCRIBE ANY ALTIST AND DESCRIBE AND DE	dard solution. A 05 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A BETWEEN 0.038% A TEST 2 0.100 TESTS IN THE FOLL .0509 0 PRATION OR MODIFICATION INITS (USE OTHER SIDE	the box correspond of	ust be within ±5% onding to the state of the	o g/210L TENANCE REPORT: OVER .19 1	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST 1 0.100 g/210L REFUSALS 0 004 12 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND DESCRIBE ANY ALT SATISFACTORILY AND DESCRIBE ANY ALT SATISFACTORILY AND DESCRIBE AND DESCRIBE AND DESCRIBE ANY ALT SATISFACTORILY AND DESCRIBE A	dard solution. A 5 or less. Mark BETWEEN 0.095% A BETWEEN 0.076% A BETWEEN 0.038% A TEST 2 0.100 FESTS IN THE FOLL .0509 0 ERATION OR MODIFICATION IMITS (USE OTHER SIDE ATTOM DATE .2/2024	the box correspond of	ust be within ±5% onding to the state of the	o g/210L TENANCE REPORT: OVER .19 1 TO OPERATE	



Airgas USA LLC (LAB) 3500 Bernard Street St. Louis, Mo. 63103 Ph: (314) 533-3100

Fax: (314) 533-7328

Certificate of Analysis

Customer Name Exclusive Supplier Intoximeters, Inc. 2081 Craig Road St. Louis, Mo 63146 Test Date: 1-Jun-2022



AG215102

Lot # AG215102 Model 108

Exp Date 31-May-2024 Cyl. Type 108

Component Ethanol Nitrogen

Certified Concentration $0.100 \pm 2\%$ BrAC (272 ppm)

Certification Traceable to N.I.S.T. RGM and to CRM Ethanol Standards:

Concentration

RGM Serial No.	Concentration	RGM Serial No.	Concentration
EB0010581	391.8 ppm	EB0010603	392.5 ppm
EB0010570	259.8 ppm	EB0010559	258.9 ppm
EB0010285	209.0 ppm	EB0010562	104.2 ppm
EB0010561	103.7 ppm	EB0010579	52.94 ppm
EB0010681	52.22 ppm		i ppiii

CRM Serial No. CC727481

800.0 ppm 253.0 ppm **CRM Serial No.** CC727493

CC727498

Concentration 390.0 ppm 150.0 ppm

Analytical Method: NDIR

CC727496

Digitally signed by: Quality Control Reason: Dry gas standard certification of analysis Location. Argas USA LLC (Lab) Date 06.02.2022 17:18

Approved for Release:

Rosl Marsola

ISO 17025:2017 A2LA accredited. Certificate Number 3082.06 ISO 17034:2016 A2LA accredited. Certificate Number 3082.07



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES
BREATH ALCOHOL PROGRAM



PERMIT TYPE II

BENJAMIN R. KAUFMAN

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):


INTOX EC/IR II

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo.

	Mile Mason
DATE	DIRECTOR OF STATE PUBLIC HEALTH LABORATORY
NUMBER 220179	
EXPIRES 7/12/2024	Daves J. McBelson
	DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES

MO 580-0771 (6-10)

LAS-4 (R6-10)



The named cardholder is authorized to operate an evidential breath alcohol instrument for the determination of the alcoholic content in breath form of expired all in Missouri.

Operator KAUFMAN, BENJAMIN

Permit No 220179

Date Issued 7/12/2022 Date Expires 7/12/2024

