By Tracy Crews at 11:48 am, Nov 01, 2023



MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

	MAINTENANCE,	REPORT			REPORT #3	
Complete this report at the time of						
days). Complete this report whenever						
into service. Retain the original		hin 15 days to the				
INTOX EC/IR II SN	NAME OF AGENCY		DATE OF INSPECTION	1		
12819	WAYNESVILLE POL	ICE DEPT	10/30/2023			
	OCATION OF INSTRUMENT (STREET AND CITY)		TIME OF INSPECTION	I		
601 Historic 66 WAYNESVILLE			18:45 CDT			
CHECKLIST: Place a mark in the box						
established limits. (Write in obse	rved values where de	etermined). Unmar	ced items must be	corrected		
before using instrument. X DIAGNOSTIC RECORD						
X BLANK CHECK		X CO2 CHECK		ţ		
X FC 1 TEMP	X FLOW CHECK					
X SRC TEMP		X FCB CHECK				
X DET TEMP	X CRC COMP CHECK					
X BT TEMP	X CRC CAL CHECK		K			
X STD 2 TEMP		X PRINT TEST				
X ETH CHECK	120-100-1					
BREATH ANALYZER ACCURACY STANDA	ARDS					
	SIMULATOR SOLUTION X COMPRESSED ETHANOL-GAS MIXTURE					
<u> </u>	imeters	LOT# AG229703	EXP.	DATE 10/24/2024		
SIMULATOR TEMP (34°C ±0.2°C)	SIM.	SN	SIM. NIST EXP	DATE		
_	1					
X CALIBRATION CHECK - (ONLY ONE	E STANDARD IS TO	BE USED PER MAIN	TENANCE REPORT)	11		
Run three tests using a standard solution. All three tests must be within $\pm 5\%$ of the standard value						
Dun throo tosts using a stand				% of the standard	i velue	
Run three tests using a stand and must have a spread of .00	dard solution. A	ll three tests m	st be within ±5	% of the standard	i value	
Run three tests using a stand and must have a spread of .00 used.	dard solution. A	ll three tests m	st be within ±5	% of the standard andard solution h	i value ocing	
and must have a spread of .00 used.	dard solution. Al 05 or less. Mark	ll three tests m the box correspo	ist be within ± 5 anding to the st	% of the standard andard solution h	i value scing	
and must have a spread of .00 used. X 0.10% STANDARD - MUST READ	dard solution. Al 05 or less. Mark BETWEEN 0.095% Al	ll three tests me the box correspond o.105% INCLUS	ust be within <u>+</u> 5 ending to the st	% of the standard andard solution h	i value ocing	
and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ	dard solution. Al 25 or less. Mark BETWEEN 0.095% Al BETWEEN 0.076% Al	ll three tests m the box correspond ND 0.105% INCLUS ND 0.084% INCLUS	ust be within <u>+</u> 5 ending to the st IVE IVE	% of the standard andard solution h	i value ocing	
and must have a spread of .00 used. X 0.10% STANDARD - MUST READ	dard solution. Al 25 or less. Mark BETWEEN 0.095% Al BETWEEN 0.076% Al	ll three tests m the box correspond ND 0.105% INCLUS ND 0.084% INCLUS	ust be within <u>+</u> 5 ending to the st IVE IVE	% of the standard andard solution h	i value ocing	
and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ	dard solution. Al 25 or less. Mark BETWEEN 0.095% Al BETWEEN 0.076% Al	the box correspond o.105% INCLUS: ND 0.084% INCLUS: ND 0.042% INCLUS:	ust be within <u>+</u> 5 ending to the st IVE IVE	andard solution l	i value ocing	
and must have a spread of .00 used. X 0.10* STANDARD - MUST READ 0.08* STANDARD - MUST READ 0.04* STANDARD - MUST READ	dard solution. All of or less. Mark BETWEEN 0.095% All BETWEEN 0.038% ALL TEST 2 " 0.099	the box correspond of	ist be within ±5 onding to the st IVE IVE IVE IVE IVE IVE IVE IVE IVE IV	andard solution l	i value ocing	
and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ	dard solution. All of or less. Mark BETWEEN 0.095% All BETWEEN 0.038% ALL TEST 2 " 0.099	the box correspond of	ist be within ±5 onding to the st IVE IVE IVE IVE IVE IVE IVE IVE IVE IV	andard solution l	i value ocing	
and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATH T	dard solution. All of or less. Mark BETWEEN 0.095% All BETWEEN 0.036% ALL TEST 2 " 0.099	the box correspond of	ist be within ±5 onding to the st IVE IVE IVE IVE IVE IVE IVE IVE IVE IV	andard solution l	i value	
and must have a spread of .00 used. X 0.10* STANDARD - MUST READ 0.08* STANDARD - MUST READ 0.04* STANDARD - MUST READ TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATE T	dard solution. All of or less. Mark BETWEEN 0.095% All BETWEEN 0.038% ALL TEST 2 " 0.099 TESTS IN THE FOLLO	the box correspond of	ist be within ±5 onding to the structure IVE IVE IVE IVE IVE IVE IVE IVE IVE IV	endard solution less selection les selections selection	i value	
and must have a spread of .00 used. X 0.10* STANDARD - MUST READ 0.08* STANDARD - MUST READ 0.04* STANDARD - MUST READ TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATH T	dard solution. All of or less. Mark BETWEEN 0.095% ALL DETWEEN 0.036% ALL DETWEEN 0.036% ALL DESTS IN THE FOLLOws.	the box correspond o.105% INCLUS: ND 0.084% INCLUS: ND 0.042% INCLUS: g/210L WING RANGES SINC .1014 1 N THAT WAS MADE TO RE	ist be within ±5 onding to the structure IVE IVE IVE IVE IVE IVE IVE IVE IVE IV	endard solution less selection les selections selection	i value	
and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATH TREFUSALS 0 004 35	dard solution. All of or less. Mark BETWEEN 0.095% ALL DETWEEN 0.036% ALL DETWEEN 0.036% ALL DESTS IN THE FOLLOws.	the box correspond o.105% INCLUS: ND 0.084% INCLUS: ND 0.042% INCLUS: g/210L WING RANGES SINC .1014 1 N THAT WAS MADE TO RE	ist be within ±5 onding to the structure IVE IVE IVE IVE IVE IVE IVE IVE IVE IV	endard solution less selection les selections selection	i value	
and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATH TREFUSALS 0 004 35	dard solution. All of or less. Mark BETWEEN 0.095% ALL DETWEEN 0.036% ALL DETWEEN 0.036% ALL DESTS IN THE FOLLOws.	the box correspond o.105% INCLUS: ND 0.084% INCLUS: ND 0.042% INCLUS: g/210L WING RANGES SINC .1014 1 N THAT WAS MADE TO RE	ist be within ±5 onding to the structure IVE IVE IVE IVE IVE IVE IVE IVE IVE IV	endard solution less selection les selections selection	i value	
and must have a spread of .00 used. X 0.10* STANDARD - MUST READ 0.08* STANDARD - MUST READ 0.04* STANDARD - MUST READ TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATH TREFUSALS 0 004 35 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER	dard solution. All of or less. Mark BETWEEN 0.095% ALL DETWEEN 0.036% ALL DETWEEN 0.036% ALL DESTS IN THE FOLLOws.	the box correspond o.105% INCLUS: ND 0.084% INCLUS: ND 0.042% INCLUS: g/210L WING RANGES SINC .1014 1 N THAT WAS MADE TO RE	ist be within ±5 onding to the structure IVE IVE IVE IVE IVE IVE IVE IVE IVE IV	endard solution less selection les selections selection	i value	
and must have a spread of .00 used. X 0.10* STANDARD - MUST READ 0.08* STANDARD - MUST READ 0.04* STANDARD - MUST READ TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATH T REFUSALS 0 004 35 LIST ANY NEW PARTS AND DESCRIBE ANY ALTE	dard solution. All of or less. Mark BETWEEN 0.095% ALL DETWEEN 0.036% ALL DETWEEN 0.036% ALL DESTS IN THE FOLLOws.	the box correspond o.105% INCLUS: ND 0.084% INCLUS: ND 0.042% INCLUS: g/210L WING RANGES SINC .1014 1 N THAT WAS MADE TO RE	ist be within ±5 onding to the structure IVE IVE IVE IVE IVE IVE IVE IVE IVE IV	endard solution less selection les selections selection	i value	
and must have a spread of .00 used. X 0.10* STANDARD - MUST READ 0.08* STANDARD - MUST READ 0.04* STANDARD - MUST READ TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATE T REFUSALS 0 004 35 LIST ANY NEW PARTS AND DESCRIBE ANY ALTE SATISFACTORILY AND WITHIN ESTABLISHED LI	dard solution. All of or less. Mark BETWEEN 0.095% ALL DETWEEN 0.036% ALL DETWEEN 0.036% ALL DESTS IN THE FOLLOws.	the box correspond o.105% INCLUS: ND 0.084% INCLUS: ND 0.042% INCLUS: g/210L WING RANGES SINC .1014 1 N THAT WAS MADE TO RE	ist be within ±5 onding to the structure IVE IVE IVE IVE IVE IVE IVE IVE IVE IV	endard solution less selection les selections selection selection selection les selections selection sele	i value	
and must have a spread of .00 used. X 0.10* STANDARD - MUST READ 0.08* STANDARD - MUST READ 0.04* STANDARD - MUST READ TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATH T REFUSALS 0 004 35 LIST ANY NEW PARTS AND DESCRIBE ANY ALTES SATISFACTORILY AND WITHIN ESTABLISHED LI	dard solution. All of or less. Mark BETWEEN 0.095% ALL DETWEEN 0.036% ALL DETWEEN 0.036% ALL DESTS IN THE FOLLOws.	the box correspond 0.105% INCLUS: ND 0.084% INCLUS: ND 0.042% INCLUS: G/210L DWING RANGES SING 1.1014 1 N THAT WAS MADE TO REIF NECESSARY).	ist be within ±5 onding to the structure IVE IVE IVE IVE IVE IVE IVE IVE IVE IV	endard solution less selection les selections selection selection selection les selections selection sele	i value	
and must have a spread of .00 used. X 0.10* STANDARD - MUST READ 0.08* STANDARD - MUST READ 0.04* STANDARD - MUST READ TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATE T REFUSALS 0 004 35 LIST ANY NEW PARTS AND DESCRIBE ANY ALTE SATISFACTORILY AND WITHIN ESTABLISHED LI	dard solution. All of or less. Mark BETWEEN 0.095% ALL DETWEEN 0.036% ALL DETWEEN 0.036% ALL DESTS IN THE FOLLOws.	the box correspond of 105% INCLUS: ND 0.105% INCLUS: ND 0.042% INCLUS: G/210L DWING RANGES SINCE 1.1014 1 N THAT WAS MADE TO RESIF NECESSARY).	ist be within ±5 onding to the structure IVE IVE IVE IVE IVE IVE IVE IVE IVE IV	endard solution less selection les selections selection selection selection les selections selection sele	i value	
and must have a spread of .00 used. X 0.10* STANDARD - MUST READ 0.08* STANDARD - MUST READ 0.04* STANDARD - MUST READ 1.00.04* STANDARD STANDA	dard solution. All of or less. Mark BETWEEN 0.095% ALL DETWEEN 0.036% ALL DETWEEN 0.036% ALL DESTS IN THE FOLLOws.	the box correspond 0.105% INCLUS: ND 0.084% INCLUS: ND 0.042% INCLUS: G/210L DWING RANGES SING 1.1014 1 N THAT WAS MADE TO REIF NECESSARY).	ist be within ±5 onding to the structure IVE IVE IVE IVE IVE IVE IVE IVE IVE IV	endard solution less selection les selections selection selection selection les selections selection sele	i value	
and must have a spread of .00 used. X 0.10* STANDARD - MUST READ 0.08* STANDARD - MUST READ 0.04* STANDARD - MUST READ TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATH T REFUSALS 0 004 35 LIST ANY NEW PARTS AND DESCRIBE ANY ALTE SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND WITHIN ESTABLISHED LIST AND WITHIN ESTABLISH AND WITHIN	dard solution. All of or less. Mark BETWEEN 0.095% All BETWEEN 0.038% ALL TEST 2 *** 0.099 FESTS IN THE FOLLO OS09 0 FRATION OR MODIFICATION OR MODIFICATION OR MODIFICATION OR SIDE 1	the box correspond o.105% INCLUS: ND 0.084% INCLUS: ND 0.042% INCLUS: OWING RANGES SINCE .1014 1 N THAT WAS MADE TO RESIF NECESSARY).	est be within ±5 ending to the structure to the structure treatment of the structure treatment of the structure treatment of the instructure treatment of the structure treatment of the	endard solution less selection les selections selection selection selection les selections selection sele	i value	
and must have a spread of .00 used. X 0.10* STANDARD - MUST READ 0.08* STANDARD - MUST READ 0.04* STANDARD - MUST READ 1.0.099 g/210L INDICATE THE NUMBER OF BREATH TO 1.0.099 g/210L REFUSALS 0 004 35 LIST ANY NEW PARTS AND DESCRIBE ANY ALTE SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTE SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTE SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTE SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTE SATISFACTORILY AND WITHIN ESTABLISHED LIST AND WITHIN ESTABLISH AND WITHIN W	dard solution. All of or less. Mark BETWEEN 0.095% All BETWEEN 0.036% ALL TEST 2 110 0.099 FESTS IN THE FOLLOW OF AN ALL OF THE STOLE OF THE SIDE OF	the box correspond of	est be within ±5 ending to the structure to the structure treatment of the structure treatment of the structure treatment of the instructure treatment of the structure treatment of the	endard solution less selection les selections selection selection selection les selections selection sele	i value	
and must have a spread of .00 used. X 0.10* STANDARD - MUST READ 0.08* STANDARD - MUST READ 0.04* STANDARD - MUST READ 1.00.04* STANDARD - MUST READ 1.00.099 g/210L INDICATE THE NUMBER OF BREATH TO 1.00.099 g/210L REFUSALS 0 004 35 LIST ANY NEW PARTS AND DESCRIBE ANY ALTES SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND WITHIN ESTABLISHED LIST TYPE II FERMIT NUMBER 230218 EXPIRA 230218 EXPIRA 10/0	dard solution. All of or less. Mark BETWEEN 0.095% All BETWEEN 0.036% ALL TEST 2 " 0.099 FESTS IN THE FOLLOW OF THE STORY OF THE STOR	the box correspond o.105% INCLUS: ND 0.084% INCLUS: ND 0.042% INCLUS: MD 0.042% INCL	est be within ±5 anding to the structure	9 g/210L TENANCE REPORT: OVER .19 2	i value	
and must have a spread of .00 used. X 0.10* STANDARD - MUST READ 0.08* STANDARD - MUST READ 0.04* STANDARD - MUST READ 0.04* STANDARD - MUST READ TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATH TREFUSALS 0 004 35 LIST ANY NEW PARTS AND DESCRIBE ANY ALTES SATISFACTORILY AND WITHIN ESTABLISHED LIST AND WITHIN ESTABLISH AND WITHIN E	dard solution. All of or less. Mark BETWEEN 0.095% All BETWEEN 0.036% ALL TEST 2 " 0.099 FESTS IN THE FOLLOW OF THE STORY OF THE STOR	the box correspond o.105% INCLUS: ND 0.084% INCLUS: ND 0.042% INCLUS: MD 0.042% INCL	est be within ±5 anding to the structure	9 g/210L TENANCE REPORT: OVER .19 2	i value	



Airgas USA LLC (LAB) 3500 Bernard Street St. Louis, Mo. 63103 Ph: (314) 533-3100 Fax: (314) 533-7328

Certificate of Analysis

Customer Name

Exclusive Supplier Intoximeters, Inc. 2081 Craig Road St. Louis, Mo 63146 Test Date: 26-Oct-2022

Lot # AG229703 Model 108

Exp Date 24-Oct-2024 Cyl. Type 108 Component

Certified Concentration

Ethanol

Nitrogen

0.100 ± 2% BrAC (272 ppm)

Certification Traceable to N.I.S.T. RGM and to CRM Ethanol Standards:

RGM Serial No.	Concentration	RGM Serial No.	Concentration
EB0010581	392.1 ppm	EB0010603	393.0 ppm
EB0010570	259.8 ppm	EB0010559	258.2 ppm
EB0010285	208.0 ppm	EB0010595	208.3 ppm
EB0010561	103.6 ppm	EB0010562	104.2 ppm
EB0010681	52.12 ppm	EB0010579	52.81 ppm

CRM Serial No.

Concentration 800.0 ppm

253.0 ppm

ppm 0056649

CRM Serial No.

0056649 0056662 Concentration

390.1 ppm 150.2 ppm

Analytical Method: NDIR

CC434668

CC234503

Digitally signed by:Quality Control Reason:Dry gas standard certification of analysis Location:Airgas USA LLC (Lab) Date:10.31.2022 12:31

Approved for Release:

Rod Marsala

ISO 17025:2017 A2LA accredited. Certificate Number 3082.06
ISO 17034:2016 A2LA accredited. Certificate Number 3082.07



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES
BREATH ALCOHOL PROGRAM



PERMIT TYPE || KYLE R. PROCK

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):

INTOX EC/IR II

MO 580-0771 (8-10)

P DEFACTION OF TRACTITATE GENION GENTAGES

LAB-4 (R6-10)

