RECEIVED

By Tracy Crews at 1:39 pm, Jul 21, 2023



MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

INTOX DMT MAINTENANCE REPORT

REPORT #1

Retain the original and send a copy within 15 days to the Breath Alcohol Program, INTOX DMT SN St. James Police Dept			07/18/2023		
LOCATION OF INSTRUMENT (STREET AND CITY) 200 N. Bourbeuse Street, St. James, MO 65559			TIME OF INSPECTION 13:56:05		
CHECKLIST: Place a mark in the box by values where determined). Unmarked ite	each item if found to be ms must be corrected be	e satisfactory or is ope	rating within established limit.	ts. (Write in observed	
☑ DIAGNOSTIC RECORD					
DATE AND TIME <u>07/18/2023 13</u>	56:08	☑ DETECT	OR .		
☑ PROGRAM		☑ FILTER 1			
☑ SAMPLE CHAMBER 48.7°C		☑ FILTER 2			
☑ BREATH TUBE_46.8°C		☑ FILTER 3			
□ PUMP		☑ INTERNAL STANDARD			
BREATH ANALYZER ACCURACY ST	ANDARDS				
☑ SIMULATOR STANDARD		☐ COMPRE	SSED ETHANOL-GAS MIX	THANOL-GAS MIXTURE	
M CTANDADD CLIDDLIED CLITTLE		LOT# 22310	EXP. DATE	08/11/2024	
M STANDARD SUPPLIER GUTH					
SIMULATOR TEMP (34°C ± 0.2°C)_ CALIBRATION CHECK - (ONLY O Run three tests using a standard. All of .005 or less. Mark the box corresponded on the control of .005 or less. Mark the box corresponded on the control of .005 or less. Mark the box corresponded on the control of .005 or less. Mark the box corresponded on the control of .005 or less. Mark the box corresponded on the control of .005 or less. Mark the box corresponded on the control of .005 or less.	34.0 S NE STANDARD IS TO three tests must be with conding to the standard READ BETWEEN 0.09	nn ±5% of the standar being used. 95% AND 0.105% INC	INTENANCE REPORT) d value and must have a spr	ATE <u>09/30/2023</u> read	
SIMULATOR TEMP (34°C ± 0.2°C) CALIBRATION CHECK - (ONLY O Run three tests using a standard. All of .005 or less. Mark the box corresponds 0.10% STANDARD - MUST 0.08% STANDARD - MUST 0.04% STANDARD - MUST	34.0 S NE STANDARD IS TO three tests must be with conding to the standard READ BETWEEN 0.07	BE USED PER MA Jin ±5% of the standar being used. JEW AND 0.105% INC JEW AND 0.084% INC JEW AND 0.042% INC	INTENANCE REPORT) d value and must have a spr CLUSIVE CLUSIVE		
SIMULATOR TEMP (34°C ± 0.2°C)_ CALIBRATION CHECK - (ONLY O Run three tests using a standard. All of .005 or less. Mark the box correspond 0.10% STANDARD - MUST 0.08% STANDARD - MUST 0.04% STANDARD - MUST TEST 1: 0.099	34.0 S NE STANDARD IS TO three tests must be with conding to the standard READ BETWEEN 0.07 READ BETWEEN 0.03	BE USED PER MA Jin ±5% of the standar being used. JEW AND 0.105% INC JEW AND 0.084% INC JEW AND 0.042% INC	NTENANCE REPORT) d value and must have a spr CLUSIVE CLUSIVE CLUSIVE		
SIMULATOR TEMP (34°C ± 0.2°C) CALIBRATION CHECK - (ONLY O Run three tests using a standard. All of .005 or less. Mark the box corresp 0.10% STANDARD - MUST 0.08% STANDARD - MUST 0.04% STANDARD - MUST TEST 1: 0.099	34.0 S NE STANDARD IS TO three tests must be with conding to the standard READ BETWEEN 0.07 READ BETWEEN 0.07 READ BETWEEN 0.03 TEST 2: 0.098	BE USED PER MA hin ±5% of the standar being used. 95% AND 0.105% INC 76% AND 0.084% INC 88% AND 0.042% INC	NTENANCE REPORT) d value and must have a spr CLUSIVE CLUSIVE CLUSIVE TEST 3: 0.098	read	
SIMULATOR TEMP (34°C ± 0.2°C) CALIBRATION CHECK - (ONLY O Run three tests using a standard. All of .005 or less. Mark the box corresponds 0.10% STANDARD - MUST 0.08% STANDARD - MUST 0.04% STANDARD - MUST TEST 1: 0.099 PERFORM R.F.I. TEST INDICATE THE NUMBER OF BREATI	34.0 S NE STANDARD IS TO three tests must be with conding to the standard READ BETWEEN 0.07 READ BETWEEN 0.07 READ BETWEEN 0.03 TEST 2: 0.098	BE USED PER MA hin ±5% of the standar being used. 95% AND 0.105% INC 76% AND 0.084% INC 88% AND 0.042% INC	NTENANCE REPORT) d value and must have a spr CLUSIVE CLUSIVE CLUSIVE TEST 3: 0.098	read	
Run three tests using a standard. All of .005 or less. Mark the box corresp © 0.10% STANDARD - MUST 0.08% STANDARD - MUST 0.04% STANDARD - MUST TEST 1: 0.099 PERFORM R.F.I. TEST INDICATE THE NUMBER OF BREATI	34.0 S NE STANDARD IS TO three tests must be with conding to the standard READ BETWEEN 0.07 READ BETWEEN 0.07 READ BETWEEN 0.03 TEST 2: 0.098 H TESTS IN THE FOLION OF MODIFICATION THAT WAS	D BE USED PER MA Juin ±5% of the standar being used. 105% AND 0.105% INC 105% AND 0.084% INC 105% AND 0.042% INC 105% AND 0.042% INC 105% AND 0.042% INC 105% AND 0.042% INC	INTENANCE REPORT) d value and must have a spi CLUSIVE CLUSIVE TEST 3: 0.098 SINCE THE LAST MAINTE	ENANCE REPORT: OVER .19: 0	
SIMULATOR TEMP (34°C ± 0.2°C) CALIBRATION CHECK - (ONLY O Run three tests using a standard. All of .005 or less. Mark the box corresponds of .005 or less. Mark the box corresponds of .008% STANDARD - MUST 0.08% STANDARD - MUST 0.04% STANDARD - MUST TEST 1: 0.099 PERFORM R.F.I. TEST INDICATE THE NUMBER OF BREATI REFUSALS: 0 004: 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION ESTABLISHED LIMITS (USE OTHER SIDE IF NECESSAR)	34.0 S NE STANDARD IS TO three tests must be with conding to the standard READ BETWEEN 0.07 READ BETWEEN 0.07 READ BETWEEN 0.03 TEST 2: 0.098 H TESTS IN THE FOLION OF THE TOWN OF TH	D BE USED PER MA Juin ±5% of the standar being used. 105% AND 0.105% INC 105% AND 0.084% INC 105% AND 0.042% INC 105% AND 0.042% INC 105% AND 0.042% INC 105% AND 0.042% INC	INTENANCE REPORT) d value and must have a spi CLUSIVE CLUSIVE TEST 3: 0.098 SINCE THE LAST MAINTE	ENANCE REPORT: OVER .19: 0	
SIMULATOR TEMP (34°C ± 0.2°C) CALIBRATION CHECK - (ONLY O Run three tests using a standard. All of .005 or less. Mark the box correspond of .005 or less. Mark	34.0 S NE STANDARD IS TO three tests must be with conding to the standard READ BETWEEN 0.07 READ BETWEEN 0.07 READ BETWEEN 0.03 TEST 2: 0.098 H TESTS IN THE FOLION OF THE TOWN OF TH	D BE USED PER MA Juin ±5% of the standar being used. 105% AND 0.105% INC 105% AND 0.084% INC 105% AND 0.042% INC 105% AND 0.042% INC 105% AND 0.042% INC 105% AND 0.042% INC	INTENANCE REPORT) d value and must have a spi CLUSIVE CLUSIVE TEST 3: 0.098 SINCE THE LAST MAINTE	ENANCE REPORT: OVER .19: 0	
SIMULATOR TEMP (34°C ± 0.2°C) CALIBRATION CHECK - (ONLY O Run three tests using a standard. All of .005 or less. Mark the box corresponding of .005 or less. Mark the box corresponding of .008% STANDARD - MUST 0.08% STANDARD - MUST 0.04% STANDARD - MUST 0.04% STANDARD - MUST TEST 1: 0.099 PERFORM R.F.I. TEST INDICATE THE NUMBER OF BREATI REFUSALS: 0 004: 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION	34.0 S NE STANDARD IS TO three tests must be with conding to the standard READ BETWEEN 0.07 READ BETWEEN 0.07 READ BETWEEN 0.03 TEST 2: 0.098 H TESTS IN THE FOLION OF THE TOWN OF TH	D BE USED PER MA Juin ±5% of the standar being used. 105% AND 0.105% INC 105% AND 0.084% INC 105% AND 0.042% INC 105% AND 0.042% INC 105% AND 0.042% INC 105% AND 0.042% INC	INTENANCE REPORT) d value and must have a spr CLUSIVE CLUSIVE TEST 3: 0.098 SINCE THE LAST MAINTE .1519: 0 TRUMENT TO OPERATE SATISFACTOR	ENANCE REPORT: OVER .19: 0	



CERTIFICATE OF ANALYSIS

Certified Alcohol Reference Solution for Simulator

Random Samples of Lot Number 22310 of Alcohol Reference Solution for Simulator were analyzed by gas chromatography on August 16, 2022, using a Perkin Elmer Gas Chromatograph Autosystem XL S/N: 610N9030209, and found to contain 0.1205% (w/vol) ethyl alcohol. The expiration date for this lot number is August 11, 2024 at 11:59 PM.

When used in a calibrated Simulator, operating at 34°C +/- .2°C, this solution will give a breath alcohol analysis instrument reading of 0.100 g/210L +/- 3%.

The alcohol and water used in this solution were free of test interfering substances.

Ted L. Pauley, President GUTH LABORATORIES, INC.

NIST Traceability:

Testing was conducted using Cerilliant Reference Standard lot number FN03052002 whose values are traceable to NIST.

All balances are calibrated annually by an outside agency using NIST traceable weights. Calibration verification is done prior to each use utilizing NIST traceable weights.



Missouri Department of Health and Senior Services

P.O. Box 570, Jefferson City, MO 65102-0570 Phone: 573-751-6400 FAX: 573-751-6010 RELAY MISSOURI for Hearing and Speech Impaired 1-800-735-2966 VOICE 1-800-735-2466



Paula Nickelson **Acting Director**

Michael L. Parson Governor

SIMULATOR CERTIFICATION REPORT

SIMULATOR INFORMATION

Simulator Serial Number: MP2927

Manufacturer: Guth

Model Number:

12V500

Agency:

ST JAMES PD

Agency Address: 200 N BOURBEUSE ST, ST JAMES, MO 65559

NIST THERMOMETER INFORMATION

Serial Number:

17KMM00690

Bias:

0.01

Uncertainty:

0.02

Date of Certification:

11/10/2021

Date of Expiration: 11/10/2022

ENVIRONMENTAL CONDITIONS

The environmental conditions during testing are within the tolerances of DHSS BAP method 3.

VERIFICATION RESULTS

Simulator Average

NIST Average

Combined Uncertainty

34.02

34.03

.03

The combined uncertainty is calculated with a k=2 value.

ADJUSTMENT RESULTS

No adjustment was needed.

Date of testing:

9/30/2022

Certification Expiration:

9/30/2023

Simulator testing technician: M. BOND

Notes on Condition: none

Deviation(s) from method: none

DHSS BAP Scientist Approving:

B. LUTMER

Certification No:

MP2927 9302022

DHSS BAP Scientist Approving

Simulator Calibration Certification

Issued by Lab Manager, DHSS BAP Revision Date: 06/25/2022

Breath Alcohol Program 1903 Northwood Drive, Suite 4 Poplar Bluff, MO 63901

DHSS BAP Document 3.6A Revision 2

Page 1 of 1



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES
BREATH ALCOHOL PROGRAM



PERMIT TYPE II CHRISTOPHER PIGG

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s).

INTOX DMT

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo.

DATE 3/16/2022	tillian 1 1 mg
	DIRECTOR OF STATE PUBLIC HEALTH LABORATORY
NUMBER 220090	
	Davla I neckelson
EXPIRES 3/16/2024	the second second
	DIRECTOR OF DEPARTMENT OF HEALTH AND SERVICE OF

MO 580-0771 (6-10)

I AB 4 (B6 10)