RECEIVED

By Tracy Crews at 8:22 am, Dec 08, 2020



MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

INTOX DMT MAINTENANCE REPORT

REPORT #1

Walles where determined). Unmarked terms must be corrected before using instrument. ☑ DIAGNOSTIC RECORD □ DATE AND TIME 12/07/2020 10:57:34 □ □ DETECTOR ☑ PROGRAM □ □ FILTER 1 □ SAMPLE CHAMBER 48.7°C □ □ FILTER 2 □ BREATH TUBE 44.8°C □ □ FILTER 3 □ PUMP □ □ INTERNAL STANDARD □ SIMULATOR STANDARD □ □ COMPRESSED ETHANOL-GAS MIXTURE □ SIMULATOR STANDARD □ □ COMPRESSED ETHANOL-GAS MIXTURE □ SIMULATOR STANDARD □ □ SIM SN □ SIM NIST EXP DATE □ SIMULATOR TEMP (34°C ± 0.2°C) □ SIM SN □ SIM NIST EXP DATE □ CALIBRATION CHECK - ((ONLY ONE STANDARD IS 10 BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests must be we test and and must have a spread of .005 or less. Mark the box corresponding to the standard debing used. □ 0.10% STANDARD - MUST READ BETWEEN 0 .05% AND 0.105% INCLUSIVE □ 0.08% STANDARD - MUST READ BETWEEN 0 .05% AND 0.084% INCLUSIVE □ 0.08% STANDARD - MUST READ BETWEEN 0 .05% AND 0.044% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0 .05% AND 0.044% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0 .05% AND 0.044% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0 .05% AND 0.044% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0 .05% AND 0.044% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0 .05% AND 0.044% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0 .05% AND 0.044% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0 .05% AND 0.044% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0 .05% AND 0.044% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0 .05% AND 0.044% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0 .05% AND 0.044% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0 .05% AND 0.05% AND 0.05% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0 .05% AND 0.05% AND 0.05% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0 .05% AND 0.064% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0 .05% AND 0.064% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0 .05% AND 0.064% INCLUSIVE □ 0.05% STANDARD - MUST READ BETWEEN 0 .05% AND 0.064% INCLUSIVE □ 0.05% STANDARD - MUST READ BETWEEN 0 .0	IIII OX BIVIT	IVI (III LIV) (IIO	L INEI OIL	·			1121 0111 #	
CALIBRATION CHECK- CONTY ONLY ONLY ONLY ONLY ONLY ONLY ONLY ONL	Complete this report wheneve	r the instrument is se	erviced or re	aired and w	henever it is placed	exceed 35 days). d into service.		
14 South Water, Liberty, Missouri CHECKLIST: Place a mark in the box by each item if found to be satisfactory or is operating within established limits. (Write in observed values where determined). Unmarked items must be corrected before using instrument. DIAGNOSTIC RECORD DATE AND TIME 12/07/2020 10:57:34 DETECTOR DITTER 1 SAMPLE CHAMBER 48.7°C DETILTER 2 DETECTOR DETILTER 3 DETILTER 111/12/2021 SIMULATOR STANDARD DETILTER 111/12/2021 SIMULATOR STANDARD STANDARD AND STREAD BETWEEN 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0			Highway P	patrol DATE OF INSPECTION 12/07/2020				
DATE AND TIME 12/07/2020 10:57:34 DETECTOR D								
DATE AND TIME 12/07/2020 10:57:34 DETECTOR D	CHECKLIST: Place a mark in values where determined). Un	the box by each item marked items must be	m if found to be corrected	be satisfact before using	ory or is operating v	within established limits. (W	/rite in observed	
© PROGRAM © SAMPLE CHAMBER 48.7°C © BREATH TUBE 44.8°C © PUMP © INTERNAL STANDARD BREATH ANALYZER ACCURACY STANDARDS □ SIMULATOR STANDARD © STANDARD SUPPLIER INTOXIMETERS LOT # AG931605 EXP. DATE 11/12/2021 □ SIMULATOR TEMP (34°C ± 0.2°C) □ SIMULATOR STANDARD STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests usung a standard All three tests must be within 15% of the standard value and must have a spread of 0.005 or less. Mark the box corresponding to the standard delicity be within 15% of the standard value and must have a spread of 0.005 or less. Mark the box corresponding to the standard delicity be within 15% of the standard value and must have a spread of 0.005 or less. Mark the box corresponding to the standard delicity be within 15% of the standard value and must have a spread of 0.005 or less. Mark the box corresponding to the standard delicity be within 15% of the standard value and must have a spread of 0.005 or less. Mark the box corresponding to the standard delicity be within 15% of the standard value and must have a spread of 0.005 or less. Mark the box corresponding to the standard delicity be within 15% of the standard value and must have a spread of 0.005 or less. Mark the box corresponding to the standard value and must have a spread of 0.005 or less. Mark the box corresponding to the standard value and must have a spread of 0.005 or less. Mark the box corresponding to the standard value and must have a spread of 0.005 or less. Mark the box corresponding to the standard value and must have a spread of 0.005 or less. Mark the box corresponding to the standard value and must have a spread of 0.005 or less. Mark the box corresponding to the standard value and must have a spread of 0.005 or less. Mark the box corresponding to the standard value and must have a spread of 0.005 or	☑ DIAGNOSTIC RECORD							
SAMPLE CHAMBER 48.7°C	DATE AND TIME 12/07	/2020 10:57:34		X	DETECTOR			
BREATH TUBE_44.8°C ☐ PUMP ☐ INTERNAL STANDARD ☐ COMPRESSED ETHANOL-GAS MIXTURE ☐ SIMULATOR STANDARD ☐ COMPRESSED ETHANOL-GAS MIXTURE ☐ SIMULATOR STANDARD ☐ SIMULATOR TEMP (34°C ± 0.2°C) ☐	☑ PROGRAM			×	FILTER 1			
BREATH ANALYZER ACCURACY STANDARDS □ SIMULATOR STANDARD □ SIMULATOR STANDARD □ SIMULATOR STANDARD □ SIMULATOR TEMP (34"C ± 0.2"C) □ SIM SN □ SIM. NIST EXP DATE □ SIMULATOR TEMP (34"C ± 0.2"C) □ SIM. SN □ SIM. NIST EXP DATE □ SIMULATOR TEMP (34"C ± 0.2"C) □ SIM. SN □ SIM. NIST EXP DATE □ SIM. SIM. SIM. NIST EXP DATE □ CALIBRATION CHECK - (ONLY ONE STANDARD IS 105% of the standard value and must have a spread of 0.05 or less. Mark the box corresponding to the standard being used. □ 0.10% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.105% INCLUSIVE □ 0.08% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.084% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 0.95% AND 0.042% INCLUSIVE □ 0.04% STANDARD		48.7°C		×	☑ FILTER 2			
BREATH ANALYZER ACCURACY STANDARDS SIMULATOR STANDARD SIMULATOR STANDARD STANDARD SUPPLIER INTOXIMETERS LOT # AG931605 EXP. DATE 11/12/2021 SIM. NIST EXP DATE CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Mark the box corresponding to the standard being used. O 1.0% STANDARD - MUST READ BETWEEN 0. 95% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0. 95% AND 0.04% INCLUSIVE 1.0.099 TEST 2: 0.099 TEST 2: 0.099 TEST 3: 0.100 PERFORM R.F.I. TEST INDICATE THE NUMBER OF BREATH TESTS IN THE FC LLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: REFUSALS: 0 0.04, 0 0.04, 0 0.05.09: 0 1014: 1 1519: 0 OVER .19: 3 USTAN NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN STANDARD LIMITS QUAR OTHER SCE P RECESSARY) INSPECTING OFFICER SIGNATURE DAY OFFICER SIGNATURE DAY OF THE LEPPIONE NUMBER SIGNATURE DAY OF THE LEPPIONE NUMBER SIGNATURE DAY OF THE LEPPIONE NUMBER DAY OF THE LEPPIONE NUMBER SIGNATURE DAY OF THE LEPPIONE NUMBER BY DAY OF THE LEPPIONE NUMBER DAY OF THE LIFET N	☐ BREATH TUBE 44.8	°C		X	FILTER 3			
□ SIMULATOR STANDARD □ STANDARD SUPPLIER_INTOXIMETERS □ LOT #_AG931605	☑ PUMP				☑ INTERNAL STANDARD			
STANDARD SUPPLIER_INTOXIMETERS LOT #_AG931605 EXP. DATE11/12/2021 SIM. SIM. SIM. NIST EXP DATE SIM. NIST EXP DATE SIM. NIST EXP DATE SIM. SIM. SIM. NIST EXP DATE SIM. SIM. SIM. SIM. SIM. SIM. NIST EXP DATE SIM. SIM. SIM. SIM. SIM. SIM. SIM. SIM.	BREATH ANALYZER ACCU	RACY STANDARD	os					
□ SIMULATOR TEMP (34"C ± 0.2"C) SIM SN SIM NIST EXP DATE □ CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Mark the box corresponding to the standard being used. □ 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE □ 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 1.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 1.05 O.099 □ TEST 2: 0.099 □ TEST 3: 0.100 □ PERFORM R.F.I. TEST INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: REFUSALS: 0 0.04: 0 0.509: 0 1.014: 1 1.519: 0 0VER .19: 3 UST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN STANDARD INCRESSARY) INSPECTING OFFICER SIGNATURE PRINT FULL NAME	☐ SIMULATOR STANDARD			☑ COMPRESSED ETHANOL-GAS MIXTURE				
© CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Mark the box corresponding to the standard being used. © 0.10% STANDARD - MUST READ BETWEEN 0. 05% AND 0.105% INCLUSIVE □ 0.08% STANDARD - MUST READ BETWEEN 0. 05% AND 0.084% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0. 038% AND 0.042% INCLUSIVE TEST 1: 0.099 □ TEST 2: 0.099 □ TEST 3: 0.100 □ PERFORM R.F.I. TEST INDICATE THE NUMBER OF BREATH TESTS IN THE FC LLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: REFUSALS. 0 □ 0.04; 0 □ 0.04; 0 □ 0.0509: 0 □ 1014: 1 □ 1519: 0 □ OVER .19: 3 UST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN STABLISHED LIMITS USE OTHER SIDE IF NECESSARY) INSPECTING OFFICER SIGNATURE □ PRINT FULL NAME J A GREEN TYPE II DEFEMIT NUMBER 290.296 EXPRATION DATE 12/20/2021 □ FILEPHONE NUMBER 290.296 RETURN COMPLETED REPORT TO THE Breath Alcohol Program, Missouri Department of Health and Senior Services	☑ STANDARD SUPPLIER	NTOXIMETERS		LOT#_A	G931605	EXP. DATE 11	/12/2021	
of .005 or less. Mark the box corresponding to the standard being used. © 0.10% STANDARD - MUST READ BETWEEN 0. 95% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0. 38% AND 0.084% INCLUSIVE TEST 1: 0.099 TEST 2: 0.099 TEST 2: 0.099 TEST 3: 0.100 PERFORM R.F.I. TEST INDICATE THE NUMBER OF BREATH TESTS IN THE FC LLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: REFUSALS: 0	☐ SIMULATOR TEMP (34°C	SIMULATOR TEMP (34°C ± 0.2°C)		SIM. SN		SIM. NIST EXP DATE		
INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: REFUSALS: 0	of .005 or less. Mark the I ☑ 0.10% STANDAR ☐ 0.08% STANDAR	oox corresponding to D - MUST READ BI D - MUST READ BI	o the standar ETWEEN 0. ETWEEN 0.	d being use 095% AND 076% AND	d. 0.105% INCLUSIV 0.084% INCLUSIV	E		
INDICATE THE NUMBER OF BREATH TESTS IN THE FOULDWING RANGES SINCE THE LAST MAINTENANCE REPORT: REFUSALS: 0 004: 0 .0509: 0 .1014: 1 .1519: 0 OVER .19: 3 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN STRUMENT TO OPERATE SATISFACTORILY AND STRUMENT	TEST 1: 0.099	T 1: 0.099 TEST 2: 0.09		9		TEST 3: 0.100	TEST 3: 0.100	
REFUSALS: 0 004: 0 .0509: 0 .1014: 1 .1519: 0 OVER .19: 3 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN ESTABLISHED LIMITS (USE OTHER SIDE IF NECESSARY) INSPECTING OFFICER SIGNATURE PRINT FULL NAME J A GREEN TYPE II PERMIT NUMBER 290296 RETURN COMPLETED REPORT TO THE Breath Alcohol Program, Missouri Department of Health and Senior Services	☑ PERFORM R.F.I. TEST	.				1		
LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN ESTABLISHED LIMITS (USE OTHER SIDE IF NECESSARY) INSPECTING OFFICER SIGNATURE J A GREEN TYPE II PERMIT NUMBER 290296 RETURN COMPLETED REPORT TO THE Breath Alcohol Program, Missouri Department of Health and Senior Services	INDICATE THE NUMBER O	F BREATH TESTS	IN THE FO	LLOWING	RANGES SINCE	THE LAST MAINTENAN	CE REPORT:	
INSPECTING OFFICER SIGNATURE TYPE II PERMIT NUMBER 290296 RETURN COMPLETED REPORT TO THE Breath Alcohol Program, Missouri Department of Health and Senior Services	REFUSALS: 0 004:	0 .0	0509: 0		1014: 1	.1519: 0	OVER .19: 3	
PRINT FULL NAME J A GREEN TYPE II PERMIT NUMBER 290296 RETURN COMPLETED REPORT TO THE Breath Alcohol Program, Missouri Department of Health and Senior Services	LIST ANY NEW PARTS AND DESCRIBE AI ESTABLISHED LIMITS (USE OTHER SIDE	Y ALTERATION OR MODIFI F NECESSARY)	CATION THAT W	AS MADE TO RE	STORE THE INSTRUMENT	TO OPERATE SATISFACTORILY AND	NIHTIW C	
RETURN COMPLETED REPORT TO THE Breath Alcohol Program, Missouri Department of Health and Senior Services	SIGNATURE			IN DATE	J A GREEN			
MO 580-2898 (5.19)	RETURN COMPLETED REF	DIE	eath Alcohol mail, fax, or	Program, M email	issouri Department		ices	