## **RECEIVED**

By Tracy Crews at 9:50 am, Jan 18, 2021



MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

## INTOX DMT MAINTENANCE REPORT

REPORT #1

| □ SIMULATOR STANDARD □ STANDARD SUPPLIER INTOXIMETERS □ LOT # AG012501 □ EXP. DATE □ 05/04/2022 □ SIMULATOR TEMP (34°C ± 0.2°C) □ SIM. SN □ SIM. NIST EXP DATE □ SIMULATOR TEMP (34°C ± 0.2°C) □ SIM. SN □ SIM. NIST EXP DATE □ CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests must be within ±5% of the standard being used. □ 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE □ 0.08% STANDARD - MUST READ BETWEEN 0.095% AND 0.084% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.05% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST  | THO A BITT WATER LIVE OF T   |   |  |                           |                    |  |
|--|--|---|--|---------------------------|--------------------|--|
| SOUTH ASH ST, NEVADA, NO 64772   Checked before using instrument.   14:13:12   | Complete this report whenever the instrument is service  | ed or repaired and  | whenever it is placed                            |                           |                    |  |
| 120 SOUTH ASH ST, NEVADA, MO 64772  CHECKLIST, Place a mark in the box by each item if found to be satisfactory or is operating within established limits. (Write in observed volutions where determined). Unmarked items must be corrected before using instrument.  DATE AND TIME  |  |   |  |                           |                    |  |
| Walles where determined.) Unmarked items must be corrected before using instrument.  ② DIAGNOSTIC RECORD  DATE AND TIME_01/17/2021 14:13:14. ② DETECTOR  ② PROGRAM ② FILTER 1  ③ SAMPLE CHAMBER_48,7°C. ③ FILTER 2  ② BREATH TUBE_45.0°C. ② FILTER 3  ② PUMP ③ INTERNAL STANDARD  BREATH ANALYZER ACCURACY STANDARDS  ③ SIMULATOR STANDARD ② COMPRESSED ETHANOL-GAS MIXTURE  ② STANDARD SUPPLIER_INTOXIMETERS LOT #_AG012501 EXP. DATE_05/04/2022  ③ SIMULATOR TEMP (34°C ± 0.2°C) SIM. SN. SIM. NIST EXP DATE  ② CALIBRATINO LECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three feets using a standard. All three tests must be within ±5% of the standard value and must have a spread of. 005 or less. Mark the box corresponding to the standard being used.  ③ 0.08% STANDARD - MUST READ BETWEEN 0.078% AND 0.084% INCLUSIVE  ② 0.08% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.086 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.087 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.088 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.088 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.089 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.089 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.081 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.081 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.081 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.081 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.081 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.081 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.081 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.081 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  □ 0.081 STANDARD - MUST READ B  |  |   |  |                           |                    |  |
| DATE AND TIME 01/17/2021 14:13:14  | CHECKLIST: Place a mark in the box by each item if values where determined). Unmarked items must be c                    | found to be satisfactorrected before usi                  | ctory or is operating w                          | ithin established limits. | (Write in observed |  |
| © PROGRAM © FILTER 1  © SAMPLE CHAMBER 48.7°C © FILTER 2  © BREATH TUBE 45.0°C © FILTER 3  © PUMP © INTERNAL STANDARD  BREATH ANALYZER ACCURACY STANDARDS  □ SIMULATOR STANDARD © COMPRESSED ETHANOL-GAS MIXTURE  © STANDARD SUPPLIER INTOXIMETERS LOT # AG012501 EXP. DATE 05/04/2022  □ SIMULATOR TEMP (34°C ± 0.2°C) SIM. SN SIM. NIST EXP DATE  © SIMULATOR TEMP (34°C ± 0.2°C) SIM. SN SIM. NIST EXP DATE  © CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT)  Run three tests using a standard All times tests must be within £5% of the standard value and must have a spread of .005 or less. Mark the box corresponding to the standard being used.  □ 0.00% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE  □ 0.00% STANDARD - MUST READ BETWEEN 0.035% AND 0.084% INCLUSIVE  □ 0.00% STANDARD - MUST READ BETWEEN 0.035% AND 0.042% INCLUSIVE  TEST 1: 0.081 TEST 3: 0.079  © PERFORM R.F.I. TEST  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  REFUSALS: 0 0.04: 0 .05: 09: 0 .10: 14: 0 .15: 19: 0 .0 VER .19: 0  INSPECTING OFFICER  BIOLANCE OF THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE INSTRUMENT TO OPERATE SATISFACTORLY AND WITHIN SET ANY NEW PARTS AND RESCRIPE ANY ALTERATION OF RECESSARY)  INSPECTING OFFICER  BIOLANCE OF THE NUMBER OF SIDE IN NECESSARY)  INSPECTING OFFICER  BIOLANCE OF THE SIDE IN NECESSARY)  EXPERIENCE NUMBER  DOWN THE ANALY NUMBER OF BREATH TO THE BREATH AND PROGRAM THAT WAS MASE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORLY AND WITHIN SET ANY NUMBER OF SIDE IN NECESSARY)  INSPECTING OFFICER  BIOLANCE OF THE SIDE IN NECESSARY)  BIOLANCE OF THE SIDE IN NECESSARY)  BIOLANCE OF THE SIDE IN NECESSARY)  BIOLANCE OF THE SIDE IN  | ☑ DIAGNOSTIC RECORD  |   |  |                           |                    |  |
| © SAMPLE CHAMBER 48,7°C  | DATE AND TIME <u>01/17/2021 14:13:14</u>   | Ţ.  | ☑ DETECTOR                                       |                           |                    |  |
| BREATH TUBE 45.0°C   | ☑ PROGRAM  | Į.  | XI FILTER 1                                      |                           |                    |  |
| BREATH ANALYZER ACCURACY STANDARDS  □ SIMULATOR STANDARD  □ SIMULATOR TEMP (34°C ± 0.2°C)  □ SIMULATOR STANDARD (34°C)    | ☑ SAMPLE CHAMBER 48.7°C ☑ FILTER 2   |   |  |                           |                    |  |
| BREATH ANALYZER ACCURACY STANDARD  SIMULATOR STANDARD  STANDARD SUPPLIER INTOXIMETERS  LOT # AG012501  EXP. DATE 05/04/2022  SIM. SIM. SIM. SIM. NIST EXP DATE  SIMULATOR TEMP (34°C ± 0.2°C)  SIM. SIM. SIM. SIM. SIM. NIST EXP DATE  CALIBRATION CHECK. (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests using a standard and must have a spread of 005 or less. Mark the box corresponding to the standard being used.  0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE  0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.044% INCLUSIVE  1.0.084 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  1.0.085 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  1.0.086 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  1.0.087 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  1.0.087 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  1.0.088 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  1.0.089 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  1.0.089 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  1.0.089 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  1.0.089 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  1.0.089 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  1.0.089 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  1.0.089 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  1.0.089 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  1.0.089 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  1.0.089 STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  1.0.089 STANDARD - MUST READ BETWEEN 0.058% AND 0.042% INCLUSIVE  1.0.089 STANDARD - MUST READ BETWEEN 0.058% AND 0.042% INCLUSIVE  1.0.089 STANDARD - MUST READ BETWEEN 0.058% AND 0.042% INCLUSIVE  1.0.089 STANDARD - MUST READ BETWEEN 0.058% AND 0.042% INCLUSIVE  1.0.089 STANDARD - MUST READ BETWEEN 0.058% AND 0.042% INCLUSIVE  1.0.089 STANDARD - MUST READ BETWEEN 0.058% AND 0.042% INCLUSIV | ☑ BREATH TUBE_45.0°C   | ſ   | XI FILTER 3                                      | - 111 - 111 - 111         |                    |  |
| SIMULATOR STANDARD  STANDARD SUPPLIER INTOXIMETERS  LOT # AG012501 EXP. DATE 05/04/2022  SIMULATOR TEMP (34°C ± 0.2°C) SIM. SIM. SIM. SIM. SIM. NIST EXP DATE  SIMULATOR TEMP (34°C ± 0.2°C) SIM. SIM. SIM. SIM. NIST EXP DATE  CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests using a standard. All three tests using a standard. All three tests using a standard seing used.  □ 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE  □ 0.04% STANDARD - MUST READ BETWEEN 0.036% AND 0.042% INCLUSIVE  TEST 1: 0.081 TEST 2: 0.079 TEST 3: 0.079  EX PERFORM R.F.I. TEST  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  REFUSALS: 0 0-04: 0 .05-09: 0 .10-14: 0 .15-19: 0 OVER :19: 0  LIBIT MY NEW PARTS AND DESCRIBE MY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTONE THE INSTITUMENT TO OPERATE SATISFACTORLY AND WITHIN SIGNAL OTHER SIDE IF NECESSARY)  JAN MAINT  INSPECTING OFFICER  PIRMIT PRIME PARTS AND DESCRIBE MY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTONE THE INSTITUMENT TO OPERATE SATISFACTORLY AND WITHIN SIGNAL OTHER SIDE IF NECESSARY)  JAN MAINT  INSPECTING OFFICER  PIRMIT PRIME PARTS AND DESCRIBE MY ALTERATION OF MODIFICATION THAT WAS MADE TO RESTONE THE INSTITUMENT TO OPERATE SATISFACTORLY AND WITHIN SIGNAL OTHER SIDE IF NECESSARY)  JAN MAINT  INSPECTING OFFICER  PIRMIT PRIME PARTS AND DESCRIBE MY ALTERATION OF MODIFICATION THAT WAS MADE TO RESTONE THE INSTITUMENT TO OPERATE SATISFACTORLY AND WITHIN SIDE IF NECESSARY)  JAN MAINT  INSPECTING OFFICER  PIRMIT PRIME PARTS AND DESCRIBE MY ALTERATION OF MODIFICATION THAT WAS MADE TO RESTONE THE INSTITUMENT TO OPERATE SATISFACTORLY AND WITHIN SIDE IF NECESSARY)  JAN MAINT  INSPECTING OFFICER  PIRMIT PRIME PARTS AND DESCRIBE MY ALTERATION OF MODIFICATION THAT WAS MADE TO RESTONE THE INSTITUMENT TO OPERATE SATISFACTORLY AND WITHIN SIDE AND ALTER AND A  | ☑ PUMP ☑ INTERNAL STANDARD   |   |  |                           |                    |  |
| STANDARD SUPPLIER INTOXIMETERS  LOT # AG012501  EXP. DATE 05/04/2022  SIM. SN SIM. NIST EXP DATE  CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Mark the box corresponding to the standard being used.  □ 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE  □ 0.04% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE  □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  TEST 1: 0.081  TEST 2: 0.079  TEST 3: 0.079  ■ PERFORM R.F.I. TEST  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  REFUSALS: 0  Q04: 0  Q04: 0  Q0509: 0  1014: 0  1519: 0  Q0VER.19: 0  USTANDARD AND CONTRIBE AND ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN STANDARD WITHIN STANDARD S                | BREATH ANALYZER ACCURACY STANDARDS   |   |  |                           |                    |  |
| □ SIMULATOR TEMP (34"C ± 0.2"C) SIM. SN SIM. NIST EXP DATE  □ CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Mark the box corresponding to the standard being used. □ 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.036% AND 0.084% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ B  | ☐ SIMULATOR STANDARD   |   | XI COMPRESSED E                                  | THANOL-GAS MIXTU          | RE                 |  |
| © CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Mark the box corresponding to the standard being used.  □ 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.036% AND 0.084% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  TEST 1: 0.081   | ☑ STANDARD SUPPLIER INTOXIMETERS   | LOT#  | AG012501   | EXP. DATE_0               | 05/04/2022         |  |
| of .005 or less. Mark the box corresponding to the standard being used.  0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE  0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE  1.0.081  TEST 2: 0.079  TEST 3: 0.079  PERFORM R.F.I. TEST  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  REFUSALS: 0  0.04: 0  0.0509: 0  1014: 0  1519: 0  OVER .19: 0  USET AND RESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORLY AND WITHIN STABLISHED LIMITS (USE OTHER SIDE IF NECESSARY)  INSPECTING OFFICER  SIGNATURE  JOSH R MULLIN  TYPE II PERMIT FULL NAME  JOSH R MULLIN  TYPE II PERMIT PART AND P       | ☐ SIMULATOR TEMP (34°C ± 0.2°C)  | SIM. SN_  |  | SIM. NIST EXP DATE        | Ξ                  |  |
| EXPIRATION DATE  SIGNATURE  SIGNATURE  PRINT FULL NAME 290055  PETURN COMPLETED REPORT TO THE  Breath Alcohol Program, Missouri Department of Health and Senior Services by mail, fax, or email  | of .005 or less. Mark the box corresponding to the ☐ 0.10% STANDARD - MUST READ BETW ☐ 0.08% STANDARD - MUST READ BETW — | e standard being us<br>VEEN 0.095% ANE<br>VEEN 0.076% ANE | sed.<br>D 0.105% INCLUSIVE<br>D 0.084% INCLUSIVE | ·<br><u>:</u>             | 1                  |  |
| INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  REFUSALS: 0 004: 0 .0509: 0 .1014: 0 .1519: 0 .OVER .19: 0  LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN  JAN MAINT  INSPECTING OFFICER  SIGNATURE  PRINT FULL NAME JOSH R MULLIN  TYPE II PERMIT NAMBER 290055  EXPIRATION DATE 03/01/2021  TELEPHONE NUMBER 290055  Breath Alcohol Program, Missouri Department of Health and Senior Services by mail, fax, or email  | TEST 1: 0.081 TES  | ST 2: 0.079   |  | TEST 3: 0.079             |                    |  |
| REFUSALS: 0 004: 0 .0509: 0 .1014: 0 .1519: 0 OVER .19: 0  LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN  JAN MAINT  INSPECTING OFFICER  SIGNATURE   | ☑ PERFORM R.F.I. TEST  |   |  |                           |                    |  |
| INSPECTING OFFICER  SIGNATURE  SI | INDICATE THE NUMBER OF BREATH TESTS IN   | THE FOLLOWING   | RANGES SINCE T                                   | HE LAST MAINTENA          | ANCE REPORT:       |  |
| JAN MAINT  INSPECTING OFFICER  SIGNATURE  SI | REFUSALS: 0 004: 0 .050  | 09: 0   | .1014: 0   | .1519: 0                  | OVER .19: 0        |  |
| INSPECTING OFFICER  SIGNATURE  SIGNATURE  JOSH R MULLIN  TYPE II PERMIT MAMBER  290055  EXPIRATION DATE  O3/01/2021  Breath Alcohol Program, Missouri Department of Health and Senior Services by mail, fax, or email  | LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION ESTABLISHED LIMITS (USE OTHER SIDE IF NECESSARY)          | IN THAT WAS MADE TO R                                     | I<br>ESTORE THE INSTRUMENT T                     | O OPERATE SATISFACTORILY  | AND WITHIN         |  |
| PRINT FULL NAME JOSH R MULLIN  TYPE II PERMIT ANDMBER 290055  EXPIRATION DATE 03/01/2021  FELEPHONE NUMBER 417-448-2710  Breath Alcohol Program, Missouri Department of Health and Senior Services by mail, fax, or email  | JAN MAINT  |   |  |                           |                    |  |
| JOSH R MULLIN  TYPE II PERMIT MOMBER 290055  EXPIRATION DATE 03/01/2021  FELEPHONE NUMBER 417-448-2710  Breath Alcohol Program, Missouri Department of Health and Senior Services by mail, fax, or email   | INSPECTING OFFICER   |   | •  |                           |                    |  |
| EXPIRATION DATE O3/01/2021 TELEPHONE NUMBER 417-448-2710  RETURN COMPLETED REPORT TO THE Breath Alcohol Program, Missouri Department of Health and Senior Services by mail, fax, or email  | SIGNATURE / (Gy)   |   |  |                           |                    |  |
| by mail, fax, or email   | TYPE II PERMIT MUMBER  |   |  |                           |                    |  |
|  | by mail  | Alcohol Program, N<br>, fax, or email                     | Missouri Department o                            | of Health and Senior Se   | ervices            |  |



## Airgas USA LLC (LAB)

3500 Bernard Street St. Louis, Mo. 63103 Ph: (314) 533-3100

Fax: (314) 533-7328

## **Certificate of Analysis**

**Customer Name** 

Exclusive Supplier Intoximeters, Inc. 2081 Craig Road St. Louis, Mo 63146 Test Date: 6-May-2020

Lot # AG012501 Model 108cacd

Exp. Date 4-May-2022 Cyl. Type

Component

**Certified Concentration** 

108

Ethanol Nitrogen 0.080 ± 0.002 BrAC (208 ppm)

Balance

Certification Traceable to N.I.S.T. RGM and to CRM Ethanol Standards:

| RGM Serial No. | <u>Concentration</u> | RGM Serial No. | <b>Concentration</b> |
|----------------|----------------------|----------------|----------------------|
| EB0010581      | 392.1 ppm            | EB0010603      | 393.0 ppm            |
| EB0010570      | 259.8 ppm            | EB0010559      | 258.2 ppm            |
| EB0010285      | 208.0 ppm            | EB0010595      | 208.3 ppm            |
| EB0010561      | 103,6 ppm            | EB0010562      | 104.2 ppm            |
| EB0010681      | 52.12 ppm            | EB0010579      | 52.81 ppm            |
|                |                      |                |                      |
| CRM Serial No. | <u>Concentration</u> | CRM Serial No. | <b>Concentration</b> |
| CC434668       | 800.0 ppm            | 0056649        | 390.1 ppm            |
| CC234503       | 253.0 ppm            | 0056662        | 150.2 ppm            |

Analytical Method:

**NDIR** 

Digitally signed by Quality Control Date: 2020,05,06 20:17:55 -05:00 Reason: Dry gas standard certification of analysis Location: Airgas USA LLC (Lab)

Approved for Release:

Rod Marsala

ISO 17025:2005 A2LA accredited. Certificate Number 3082.06 ISO 17034:2016 A2LA accredited. Certificate Number 3082.07

)