RECEIVED

By Tracy Crews at 6:46 am, Mar 15, 2021



MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

INTOX DMT MAINTENANCE REPORT

REPORT #1

Retain the original and send a copy within 15 day INTOX DMT SN 500286 NAME OF AGENCY Desloge P.D		DATE OF INSPECTION 03/10/2021	
LOCATION OF INSTRUMENT (STREET AND CITY)		TIME OF INSPECTION	
1000 N. Desloge Dr., Desloge, MO	town if forward to be potinfectory as in once	01:35:50	in changed
CHECKLIST: Place a mark in the box by each it values where determined). Unmarked items mus	tem if found to be satisfactory or is oper to the corrected before using instrument.	ating within established limits. (Write	e in observed
☑ DIAGNOSTIC RECORD			
DATE AND TIME <u>03/10/2021 01:35:52</u>	_ DETECTO	☑ DETECTOR	
☑ PROGRAM	☑ FILTER 1	☑ FILTER 1	
SAMPLE CHAMBER 48.8°C ■ 48.8°C	☑ FILTER 2		
☑ BREATH TUBE 46.3°C	☑ FILTER 3		
☑ PUMP		STANDARD	
BREATH ANALYZER ACCURACY STANDAI	RDS		
☐ SIMULATOR STANDARD		SED ETHANOL-GAS MIXTURE	
			7/2022
STANDARD SUPPLIER INTOXIMETER	S LOT# AG005803	EXP. DATE <u>02/27</u>	12022
☐ SIMULATOR TEMP (34°C ± 0.2°C) ☐ CALIBRATION CHECK - (ONLY ONE ST Run three tests using a standard. All three to of .005 or less. Mark the box corresponding ☐ 0.10% STANDARD - MUST READ	SIM. SN ANDARD IS TO BE USED PER MAIN ests must be within ±5% of the standard g to the standard being used. BETWEEN 0.095% AND 0.105% INC	SIM. NIST EXP DATE ITENANCE REPORT) value and must have a spread USIVE	172022
□ SIMULATOR TEMP (34°C ± 0.2°C) □ CALIBRATION CHECK - (ONLY ONE ST Run three tests using a standard. All three to of .005 or less. Mark the box corresponding □ 0.10% STANDARD - MUST READ □ 0.08% STANDARD - MUST READ □ 0.04% STANDARD - MUST READ	SIM. SN ANDARD IS TO BE USED PER MAIN ests must be within ±5% of the standard g to the standard being used. BETWEEN 0.095% AND 0.105% INC. BETWEEN 0.076% AND 0.084% INC. BETWEEN 0.038% AND 0.042% INC.	SIM. NIST EXP DATE ITENANCE REPORT) value and must have a spread USIVE USIVE	12022
□ SIMULATOR TEMP (34°C ± 0.2°C) □ CALIBRATION CHECK - (ONLY ONE ST Run three tests using a standard. All three to of .005 or less. Mark the box corresponding □ 0.10% STANDARD - MUST READ □ 0.08% STANDARD - MUST READ □ 0.04% STANDARD - MUST READ □ 1.04% STANDARD - MUST READ TEST 1: 0.100	SIM. SN ANDARD IS TO BE USED PER MAIN ests must be within ±5% of the standard g to the standard being used. BETWEEN 0.095% AND 0.105% INCI BETWEEN 0.076% AND 0.084% INCI	SIM. NIST EXP DATE ITENANCE REPORT) value and must have a spread LUSIVE LUSIVE	72022
□ SIMULATOR TEMP (34°C ± 0.2°C) □ CALIBRATION CHECK - (ONLY ONE ST Run three tests using a standard. All three to of .005 or less. Mark the box corresponding □ 0.10% STANDARD - MUST READ □ 0.08% STANDARD - MUST READ □ 0.04% STANDARD - MUST READ □ 0.04% STANDARD - MUST READ □ 0.04% STANDARD - MUST READ	SIM. SN ANDARD IS TO BE USED PER MAIN ests must be within ±5% of the standard growth to the standard being used. BETWEEN 0.095% AND 0.105% INCIDENTAL BETWEEN 0.076% AND 0.084% INCIDENTAL BETWEEN 0.038% AND 0.042% INCIDENTAL SET 2: 0.100	SIM. NIST EXP DATE ITENANCE REPORT) value and must have a spread LUSIVE LUSIVE LUSIVE TEST 3: 0.100	
□ SIMULATOR TEMP (34°C ± 0.2°C) □ CALIBRATION CHECK - (ONLY ONE ST Run three tests using a standard. All three to of .005 or less. Mark the box corresponding □ 0.10% STANDARD - MUST READ □ 0.08% STANDARD - MUST READ □ 0.04% STANDARD - MUST READ TEST 1: 0.100 □ PERFORM R.F.I. TEST INDICATE THE NUMBER OF BREATH TES	SIM. SN ANDARD IS TO BE USED PER MAIN ests must be within ±5% of the standard g to the standard being used. BETWEEN 0.095% AND 0.105% INC. BETWEEN 0.076% AND 0.084% INC. BETWEEN 0.038% AND 0.042% INC. TEST 2: 0.100 TS IN THE FOLLOWING RANGES S	SIM. NIST EXP DATE ITENANCE REPORT) value and must have a spread LUSIVE LUSIVE TEST 3: 0.100	
SIMULATOR TEMP (34°C ± 0.2°C) CALIBRATION CHECK - (ONLY ONE ST Run three tests using a standard, All three to of .005 or less. Mark the box corresponding □ 0.10% STANDARD - MUST READ □ 0.08% STANDARD - MUST READ □ 0.04% STANDARD - MUST READ □ 0.0	SIM. SN ANDARD IS TO BE USED PER MAIN ests must be within ±5% of the standard growth to the standard being used. BETWEEN 0.095% AND 0.105% INCOME BETWEEN 0.076% AND 0.084% INCOME BETWEEN 0.038% AND 0.042% INCOME BETWEEN 0.038% AND 0.042% INCOME TEST 2: 0.100 TS IN THE FOLLOWING RANGES STANDS 1.0509: 0 .1014: 0	SIM. NIST EXP DATE ITENANCE REPORT) value and must have a spread LUSIVE LUSIVE TEST 3: 0.100 INCE THE LAST MAINTENANCE .1519: 0	REPORT:
□ 0.08% STANDARD - MUST READ □ 0.08% STANDARD - MUST READ □ 0.04% STANDARD - MUST READ TEST 1: 0.100 □ PERFORM R.F.I. TEST INDICATE THE NUMBER OF BREATH TES REFUSALS: 0	SIM. SN ANDARD IS TO BE USED PER MAIN ests must be within ±5% of the standard growth to the standard being used. BETWEEN 0.095% AND 0.105% INCOME BETWEEN 0.076% AND 0.084% INCOME BETWEEN 0.038% AND 0.042% INCOME BETWEEN 0.038% AND 0.042% INCOME TEST 2: 0.100 TS IN THE FOLLOWING RANGES STANDS 1.0509: 0 .1014: 0	SIM. NIST EXP DATE ITENANCE REPORT) value and must have a spread LUSIVE LUSIVE TEST 3: 0.100 INCE THE LAST MAINTENANCE .1519: 0	E REPORT: OVER .19: 0
□ SIMULATOR TEMP (34°C ± 0.2°C) □ CALIBRATION CHECK - (ONLY ONE ST Run three tests using a standard. All three to of .005 or less. Mark the box corresponding □ 0.10% STANDARD - MUST READ □ 0.08% STANDARD - MUST READ □ 0.04% STANDARD - MUST READ □ 0.04% STANDARD - MUST READ TEST 1: 0.100 □ PERFORM R.F.I. TEST INDICATE THE NUMBER OF BREATH TES REFUSALS: 0 004: 6 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MO	SIM. SN ANDARD IS TO BE USED PER MAIN ests must be within ±5% of the standard growth to the standard growth the standard grow	SIM. NIST EXP DATE ITENANCE REPORT) value and must have a spread LUSIVE LUSIVE TEST 3: 0.100 INCE THE LAST MAINTENANCE .1519: 0 RUMENT TO OPERATE SATISFACTORILY AND W	E REPORT: OVER .19: 0



Airgas USA LLC (LAB)

3500 Bernard Street St. Louis, Mo. 63103

Ph: (314) 533-3100 Fax: (314) 533-7328

Certificate of Analysis

Customer Name

Exclusive Supplier Intoximeters, Inc. 2081 Craig Road St. Louis, Mo 63146

2-Mar-2020 Test Date:

Lot # AG005803 Model 108cacd

Exp. Date 27-Feb-2022 Cyl. Type 108

Component Ethanol Nitrogen

Certified Concentration 0.100 ± 2% BrAC (260 ppm)

Balance

Certification Traceable to N.I.S.T. RGM and to CRM Ethanol Standards:

RGM Serial No. EB0010581

EB0010570 EB0010285 EB0010561

EB0010681 CRM Serial No.

CC434668 CC234503

Concentration 392.1 ppm

259.8 ppm 208.0 ppm 103.6 ppm 52.12 ppm

Concentration 800.0 ppm

253.0 ppm

RGM Serial No. EB0010603 EB0010559 EB0010595

EB0010562 EB0010579

CRM Serial No. 0056649 0056662

Concentration 393.0 ppm 258.2 ppm 208.3 ppm

104.2 ppm 52.81 ppm

Concentration 390.1 ppm 150.2 ppm

Analytical Method:

NDIR

Digitally signed by Quality Control Date: 2020.03.02 10:29:26-06:00 Reason: Dry gas standard certification of analysis Location: Airgas USA LLC (Lab)

Approved for Release:

ISO 17025:2005 A2LA accredited. Certificate Number 3082.06 ISO 17034:2016 A2LA accredited. Certificate Number 3082.07



DEPARTMENT OF HEALTH AND SENIOR SERVICES

BREATH ALCOHOL PROGRAM

PERMIT TYPE II

LORALEE BADER

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs and operate the following breath analyzer(s):


INTOX DMT

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of section 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo.

DATE3/3/2020	win
	DIRECTOR OF STATE PUBLIC HEALTH LABORATORY
NUMBER 200110	
EXPIRES 3/3/2022	fly ville
	DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES

LAB-4 (R6-

MD 580-0771 (6-10)



The named cardholder is authorized to operate an evidential breath alcohol instrument for the determination of the alcoholic content in breath form of expired ali in Missouri.

Operator BADER, LORALEE Permit No 200110

Date Issued 3/3/2020 Date Expires 3/3/2022

