By Tracy Crews at 8:52 am, Sep 19, 2022



MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

	MAINTENANCE RE			REPORT #3	
Complete this report at the time of					
days). Complete this report whenev		_			
into service. Retain the original	NAME OF AGENCY	15 days to the D	Breath Alcohol Pro	ogram, DHSS.	
INTOX BC/IR II SN 12819	WAYNESVILLE POLICE	חדסיד	09/06/2022		
LOCATION OF INSTRUMENT (STREET AND CIT		DELL	TIME OF INSPECTION		
601 Historic 66 WAYNESVILLE			17:54 CDT		
CHECKLIST: Place a mark in the box	s by each item if found	to be satisfacto		na within	
established limits. (Write in obse	=				
before using instrument.					
X DIAGNOSTIC RECORD					
X BLANK CHECK	X	CO2 CHECK			
X FC 1 TEMP X FLOW CHECK					
X SRC TEMP		FCB CHECK			
X DET TEMP		CRC COMP CHEC	TV		
X BT TEMP		CRC CAL CHECK			
X STD 3 TEMP		PRINT TEST			
	X	PRINT TEST			
X ETH CHECK					
BREATH ANALYZER ACCURACY STAND					
SIMULATOR SOLUTION	X	COMPRESSED ET	HANOL-GAS MIXTU		
X STANDARD SUPPLIER Into	cimeters LOT	* AG028101	EXP.	DATE 10/07/2022	
SIMULATOR TEMP (34°C +0.2°C)) SIM. SN		SIM. NIST EXP I	ATE	
X CALIBRATION CHECK - (ONLY ON	E STANDARD IS TO BE U	SED PER MAINT	ENANCE REPORT)		
X CALIBRATION CHECK - (ONLY ON				of the standard value	
Run three tests using a stan	dard solution. All t	hree tests mus	st be within <u>+</u> 5%	of the standard value	
	dard solution. All t	hree tests mus	st be within <u>+</u> 5%	s of the standard value andard solution being	
Run three tests using a stan and must have a spread of .0 used.	dard solution. All t 05 or less. Mark the	hree tests mus box correspon	st be within ±5% nding to the sta	s of the standard value undard solution being	
Run three tests using a stan and must have a spread of .0	dard solution. All t 05 or less. Mark the BETWEEN 0.095% AND 0	hree tests must box correspondent.	st be within <u>+</u> 5% nding to the sta VE	of the standard value indard solution being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ	dard solution. All t 05 or less. Mark the BETWEEN 0.095% AND 0 BETWEEN 0.076% AND 0	hree tests must box corresponding the corresponding to the corresponding	st be within <u>+</u> 5% nding to the sta VE VE	of the standard value andard solution being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ	dard solution. All to 05 or less. Mark the DETWEEN 0.095% AND 0 DETWEEN 0.076% AND 0 DETWEEN 0.038% AND 0	hree tests must box corresponding to the correspond	st be within <u>+</u> 5% nding to the sta VE VE	indard solution being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ	dard solution. All t 05 or less. Mark the BETWEEN 0.095% AND 0 BETWEEN 0.076% AND 0	hree tests must box corresponding to the correspond	st be within <u>+</u> 5% nding to the sta VE VE	indard solution being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ	dard solution. All to 05 or less. Mark the BETWEEN 0.095% AND 0 BETWEEN 0.076% AND 0 BETWEEN 0.038% AND 0 TEST 2 3 0.099 g/2	hree tests must box correspond .105% INCLUSIV .084% INCLUSIV .042% INCLUSIV	st be within ±5% nding to the stave VE VE TEST 3 % 0.099	ndard solution being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.099 g/210L	dard solution. All to 05 or less. Mark the BETWEEN 0.095% AND 0 BETWEEN 0.076% AND 0 BETWEEN 0.038% AND 0 TEST 2 3 0.099 g/2	hree tests must box correspond .105% INCLUSIV .084% INCLUSIV .042% INCLUSIV	st be within ±5% nding to the stave ve ve ve ve TEST 3 % 0.099	ndard solution being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.099 g/210L	dard solution. All to 05 or less. Mark the BETWEEN 0.095% AND 0 BETWEEN 0.076% AND 0 BETWEEN 0.038% AND 0 TEST 2 0.099 g/2	hree tests must box correspond .105% INCLUSIV .084% INCLUSIV .042% INCLUSIV	st be within ±5% nding to the stave ve ve ve ve TEST 3 % 0.099	ndard solution being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.0099 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM	dard solution. All to 05 or less. Mark the BETWEEN 0.095% AND 0 BETWEEN 0.076% AND 0 BETWEEN 0.038% AND 0 TEST 2 0.099 g/2 TEST 2 0.099 g/2 TESTS IN THE FOLLOWIN	hree tests must box corresponding to the correspond	st be within ±5% nding to the state very sta	og/210L CENANCE REPORT: OVER .19 3	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0	dard solution. All to 05 or less. Mark the BETWEEN 0.095% AND 0 BETWEEN 0.076% AND 0 BETWEEN 0.038% AND 0 TEST 2 0.099 g/2 TEST 2 0.099 g/2 TESTS IN THE FOLLOWIN	hree tests must box corresponding to the correspond	st be within ±5% nding to the state very sta	og/210L CENANCE REPORT: OVER .19 3	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.0099 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM	dard solution. All to 05 or less. Mark the BETWEEN 0.095% AND 0 BETWEEN 0.076% AND 0 BETWEEN 0.038% AND 0 TEST 2 0.099 g/2 TEST 2 0.099 g/2 TESTS IN THE FOLLOWIN	hree tests must box corresponding to the correspond	st be within ±5% nding to the state very sta	og/210L CENANCE REPORT: OVER .19 3	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.0099 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM	dard solution. All to 05 or less. Mark the BETWEEN 0.095% AND 0 BETWEEN 0.076% AND 0 BETWEEN 0.038% AND 0 TEST 2 0.099 g/2 TEST 2 0.099 g/2 TESTS IN THE FOLLOWIN	hree tests must box corresponding to the correspond	st be within ±5% nding to the state very series of the state very serie	og/210L CENANCE REPORT: OVER .19 3	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.0099 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM	dard solution. All to 05 or less. Mark the BETWEEN 0.095% AND 0 BETWEEN 0.076% AND 0 BETWEEN 0.038% AND 0 TEST 2 0.099 g/2 TEST 2 0.099 g/2 TESTS IN THE FOLLOWIN	hree tests must box correspond to the correspond	st be within ±5% nding to the state very series of the state very serie	og/210L CENANCE REPORT: OVER .19 3	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.0099 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM	dard solution. All to 05 or less. Mark the BETWEEN 0.095% AND 0 BETWEEN 0.076% AND 0 BETWEEN 0.038% AND 0 TEST 2 0.099 g/2 TEST 2 0.099 g/2 TESTS IN THE FOLLOWIN	hree tests must box correspond to the correspond	st be within ±5% nding to the state very series of the state very serie	og/210L CENANCE REPORT: OVER .19 3	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.0099 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM	dard solution. All to 05 or less. Mark the BETWEEN 0.095% AND 0 BETWEEN 0.076% AND 0 BETWEEN 0.038% AND 0 TEST 2 0.099 g/2 TESTS IN THE FOLLOWIN	hree tests must box correspond to the correspond	st be within ±5% nding to the state very series of the state very serie	og/210L CENANCE REPORT: OVER .19 3	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALX SATISFACTORILY AND WITHIN ESTABLISHED I	dard solution. All to 05 or less. Mark the 05 determined by 0.095% AND 05 determined by 0.038% AND 05 determined by 0.099 g/2 TEST 2 0.099 g/2 TESTS IN THE FOLLOWING 1.0509 1 .1 PRINTING OF MODIFICATION THE IMPORTANCE OF MEDIFICATION THE IMPORTANCE OF	hree tests must box corresponds to the correspond to the correspon	st be within ±5% nding to the state very series of the state very serie	og/210L CENANCE REPORT: OVER .19 3	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 g/210L TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED IN SATISFACTORILY AND WITHIN SATISFACTORILY AND WITHIN ESTABLISHED IN SATISFACTORILY AND WITHI	dard solution. All to 05 or less. Mark the 05 determined of 0.095% AND 05 determined of 0.038% AND 05 determined of 0.099 g/2 TEST 2 0.099 g/2 TESTS IN THE FOLLOWING 1.0509 1 .1 PERATION OR MODIFICATION THE IMMITS (USE OTHER SIDE IF ME	hree tests must box corresponds to the correspond to the correspon	st be within ±5% nding to the state very series of the state very serie	og/210L CENANCE REPORT: OVER .19 3	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.0009 g/210L TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM SATISFACTORILY AND WITHIN ESTABLISHED IN SATISFAC	dard solution. All to 05 or less. Mark the 05 detection 0.038% AND 06 detection 0.038% AND 07 detection of Modification The IMITS (USE OTHER SIDE IF NE 17 ME) ATION DATE TEIL TEIL TEIL TEIL TEIL TEIL TEIL TE	hree tests must box correspond to the correspond	st be within ±5% nding to the state very series of the state very serie	og/210L CENANCE REPORT: OVER .19 3	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM SATISFACTORILY AND WITHIN ESTABLISHED IN SIGNATURE TYPE II PERMIT NUMBER EXPIR 10/0	dard solution. All to 05 or less. Mark the 05 between 0.095% AND 05 between 0.038% AND 05 between 0.038% AND 05 between 0.038% AND 07 between 0.099 g/2 TEST 2 0.099 g/2 TESTS IN THE FOLLOWING 1.0509 1 .1 PERATION OR MODIFICATION THE INITS (USE OTHER SIDE IF NE 1.06/2023 C. 1.06/20	hree tests must box corresponds to the correspond to the correspon	st be within ±5% nding to the state very series of the state very serie	og/210L CENANCE REPORT: OVER .19 3	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.0009 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM SATISFACTORILY AND WITHIN ESTABLISHED INTERPRETATION OF THE SIGNATURE TYPE II PERMIT NUMBER EXPIRE 210229 EXPIRE 210229	dard solution. All to 05 or less. Mark the 05 determined the 05 determined the 15 determin	hree tests must box corresponds to the correspond to the correspon	st be within ±5% nding to the state very series of the state very serie	og/210L ENANCE REPORT: OVER .19 3 TO OPERATE	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.099 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM SATISFACTORILY AND WITHIN ESTABLISHED IN SIGNATURE TYPE II PERMIT NUMBER EXPIR 10/0	dard solution. All to 05 or less. Mark the 05 determined the 05 determined the 15 determin	hree tests must box corresponds to the correspond to the correspon	st be within ±5% nding to the state very series of the state very serie	og/210L ENANCE REPORT: OVER .19 3 TO OPERATE	

09/19/2022 08:07 (FAX) P.002/003



Airgas USA LLC (LAB)

3500 Bernard Street

St. Louis, Mo. 63103

Ph: (314) 533-3100

Fax: (314) 533-7328

Certificate of Analysis

Customer Name

Exclusive Supplier Intoximeters, Inc. 2081 Craig Road St. Louis, Mo 63146 Test Date: 7-Oct-2020

Lot # AG028101 Model 108cacd

Exp. Date

Cyl. Type

Component

Certifled Concentration

7-Oct-2022

108

Ethanol Nitrogen $0.100 \pm 2\%$ BrAC (272 ppm)

Balance

Certification Traceable to N.I.S.T. RGM and to CRM Ethanol Standards:

RGM Serial No.	<u>Concentration</u>	RGM Serial No.	<u>Concentration</u>
EB0010581	392.1 ppm	EB0010603	393.0 ppm
EB0010570	259.8 ppm	EB0010559	258.2 ppm
EB0010285	208.0 ppm	EB0010595	208.3 ppm
EB0010561	103.6 ppm	EB0010562	104.2 ppm
EB0010681	52.12 ppm	EB0010579	52.81 ppm
CRM Serial No.	Concentration	CRM Serial No.	Concentration

 CRM Serial No.
 Concentration
 CRM Serial No.
 Concentration

 CC434668
 800.0 ppm
 0056649
 390.1 ppm

 CC234503
 253.0 ppm
 0056662
 150.2 ppm

Analytical Method: NDIR

Approved for Release:

Rod Marsala

ISO 17025:2005 A2LA accredited. Certificate Number 3082.06 ISO 17034:2016 A2LA accredited. Certificate Number 3082.07



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES
BREATH ALCOHOL PROGRAM



PERMIT TYPE II

KYLE R. PROCK

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):

INTOX EC/IR II

for the determination of the alcoholic content of blood from a sample of ex	xpired air. Pe	ermit issued i	under the provisions	of sections
577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo.				
, ,	<i>2</i> }	25%	21 C	

DATE10/6/2021	Lama & Day
	DIRECTOR OF STATE PUBLIC HEALTH LABORATORY
NUMBER 210229	Thound S. Kann
EXPIRES 10/6/2023	DIRECTOR OF DEPARTMENT OF HEALTH AND SERVICES
MQ 580-0771 (6-10)	LAG4 (R6-10)

. ______

> STATE OF MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES BREATH ALCOHOL PROGRAM

The named cardhoider is authorized to operate an evidential breath alcohol

instrument for the determination of the alcoholic content in breath form of expired as in Missouri

Operator PROCK, KYLE Permit No 210229

Date Issued 10/6/2021

Date Expires 10/6/2023

