

MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY

ALCO-SENSOR IV WITH PRINTER MAINTENANCE REPORT

Complete this report in duplicate at the time of the regular monthly proventative maintenance check, and whenever instrument is repairly send only to Department of Health and Senior Services, retain original in department file. ACO SENSOR IV SN AME OF AGENCY LOCATION OF INSTRUMENT (STREET AND CITY) LOCATION OF INSTRUMENT (STREET AND CITY (STREET AND CITY) LOCATION OF INSTRUMENT (STREET AND CITY) LOC	ABICE XX					•		REPOR	
ALCO SENSORING IN SN CHECKLIST: Place as mark in the box by each them if found to be satisfactory or if operating within established limits. (Write in observed value where determined.) Unmarked items must be corrected before using instrument. DIGITAL READOUT (ALL ELEMENTS OPERATIONAL) TEMPERATURE OF ALCO SENSOR (10°C - 40°C) PRINTER WORKING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS SIMULATOR SOLUTION CALIBRATION CHECK — (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 o less. Check the box corresponding to the standard solution being used. (PRINTOTT ATTACHED) OLOMOW, STANDARD - MUST READ BETWEEN 0.035% and 0.045% INCLUSIVE OLOMOW, STANDARD - MUST READ BETWEEN 0.075% and 0.045% INCLUSIVE TEST 1 ** TEST 2 ** JED TEST 3 ** PRINT NAME PRINT NAME	Complete this report in d Send copy to Departmen	uplicate at the time t of Health and Se	e of the regular mont	hly preventative original in depart	mainten tment file	ance check, and	d whenever	instrument is repair	
LOCATION OF INSTRUMENT (STREET AND CITY) TIME OF ALCO SENSOR (10°C - 40°C) PRINTER WORKING PROPERLY TIME AND DATE DISPLAYING PROPERLY TIME AND DATE DISPLAYING PROPERLY SIMULATOR SOLUTION CALIBRATION CHECK — (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three lests using a standard solution had three tests must be within ±5% of the standard value and must have a spread of .005 o less .Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.080% STANDARD . MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD . MUST READ BETWEEN 0.095% and 0.045% INCLUSIVE TEST 1 — TEST 2 — TEST 3 — TEST 1 — TEST 2 — TEST 3 — TEST 4 — TEST 4 — TEST 4 — TEST 5 — T	ALCO SENSOR IV SN						DATE OF INC	DECTION	
CHECKLIST: Place a mark in the box by each item if found to be satisfactory or if operating within established limits. (Write in observed valuative determined.) Unmarked items must be corrected before using instrument. DIGITAL READOUT (ALL ELEMENTS OPERATIONAL) TEMPERATURE OF ALCO SENSOR (10°C - 40°C) PRINTER WORKING PROPERLY TIME AND DATE DISPLAYING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS SIMULATOR SOLUTION COMPRESSED ETHANOL-GAS MIXTURE STANDARD SUPPLIER SIMULATOR TEMPERATURE (34°C ± 0.2°C) Lyss C SIM. SN Ja January SIM. NIST EXP DATE 0170-02. CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within 45% of the standard value and must have a spread of .005 or 10.10% STANDARD. MUST READ BETWEEN 0.055% and 0.105% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.055% and 0.045% INCLUSIVE TEST 1	0924,8	>	PERGU	Coal Pa				.3 _	
CHECKLIST: Place a mark in the box by each item if found to be salisfactory or if operating within established limits. (Write in observed valuative detections of the property of the property detections of the property of t									
DIGITAL READOUT (ALL ELEMENTS OPERATIONAL) TEMPERATURE OF ALCO SENSOR (10°C - 40°C) PRINTER WORKING PROPERLY BERATH ALCOHOL ACCURACY STANDARDS SIMULATOR SOLUTION STANDARD SUPPLIER CALIBRATION CHECK — (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. Being used. (PRINTOUT ATTACHED) 0.080% STANDARD - MUST READ BETWEEN 0.095% and 0.085% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.095% and 0.085% INCLUSIVE 1.0 D TEST 2	CHECKLIST: Place a mar	k in the box by and	Paller Soal N	10 6435			12	500	
TEMPERATURE OF ALCO SENSOR (10°C - 40°C) PRINTER WORKING PROPERLY SIMULATOR SOLUTION SIMULATOR SOLUTION SIMULATOR SUPPLIER SIMULATOR SUPPLIER SIMULATOR TEMPERATURE (34°C ± 0.2°C) Ly. 0°C SIM. SN Jophy SIM. NIST EXP DATE 2000-2000 CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.0809% STANDARD - MUST READ BETYMEEN 0.095% and 0.105% INCLUSIVE 0.0409% STANDARD - MUST READ BETYMEEN 0.095% and 0.042% INCLUSIVE 1.0 D TEST 2 TEST 2 TEST 3 PRINTER NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: DO NOT INCLUDE SELF-ADMINISTERED TESTS) SEFUALS (0.0-04) (0.5-09) (0.5-09) (10-14) (15-19) (OVER .19) SEFUSION ONT INCLUDE SELF-ADMINISTERED TESTS) SEFUSIALS (0.0-04) (0.5-09) (0.5-09) (10-14) (15-19) (OVER .19) SEFUSION ONT INCLUDE SELF-ADMINISTERED TESTS) SEFUSIALS (1.0-04) (1.5-19) (0.5-09) (1.0-14) (1.5-19) (0.5-19) SEFUSION ONT INCLUDE SELF-ADMINISTERED TESTS) SEFUSIALS (1.0-04) (1.0-14) (1.5-19) (0.5-19) SEFUSION ONT INCLUDE SELF-ADMINISTERED TESTS) SEFUSIALS (1.0-04) (1.0-14) (1.5-19) (0.5-19) SEFUSION ONT INCLUDE SELF-ADMINISTERED TESTS) SEFUSIALS (1.0-04) (1.0-14) (1.5-19) (0.0-14) (1.5-19) SEFUSION ONT INCLUDE SELF-ADMINISTERED TESTS) SEFUSIALS (1.0-04) (1.0-14) (1.5-19) (0.0-14) (1.5-19) SEFUSION ONT INCLUDE SELF-ADMINISTERED TESTS) SEFUSIALS (1.0-04) (1.0-14) (1.0-14) (1.5-19) (0.0-14) (1.5-19) SEFUSION ONT INCLUDE SELF-ADMINISTERED TESTS) SEFUSIALS (1.0-04) (1.0-14) (1.0-14) (1.5-19) (0.0-14) (1.5-19) SEFUSION ONT INCLUDE SELF-ADMINISTERED TESTS) SEFUSIALS (1.0-04) (1.0-14) (1.0-14) (1.5-19) (0.0-14) (1.5-19) (0.0-14) (1.5-19) SEFUSION ONT INCLUDE SELF-ADMINISTERED TESTS) SEFUSIALS (1.0-04) (1.0-14) (1.0-14) (1.0-14) (1.0-14) (1.5-19) (1.0-14) (1.5-19) (1.0-14) (1.0-14) (1.0-14) (1.0-14) (1.0-14) (1.0-14) (1.	where determined.) Unma	arked items must b	e corrected before us	satisfactory or if c sing instrument.	perating	within establish	ed limits. (W	rite in observed valu	
PRINTER WORKING PROPERLY TIME AND DATE DISPLAYING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS SIMULATOR SOLUTION COMPRESSED ETHANOL-GAS MIXTURE STANDARD SUPPLIER SIMULATOR TEMPERATURE (34°C ± 0.2°C) 3/y 5°C SIM. SIM. SIM. SIM. NIST EXP DATE 6000-2000 CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.100% STANDARD - MUST READ BETYMEEN 0.095% and 0.105% INCLUSIVE 0.040% STANDARD - MUST READ BETYMEEN 0.095% and 0.042%. INCLUSIVE ITEST 1	DIGITAL READOUT	(ALL ELEMENTS (OPERATIONAL)						
TIME AND DATE DISPLAYING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS SIMULATOR SOLUTION COMPRESSED ETHANOL-GAS MIXTURE STANDARD SUPPLIER SIMULATOR TEMPERATURE (34°C ± 0.2°C) 240°C SIM. SN 50 PM SIM. NIST EXP DATE 20-10-10 CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.095% and 0.042% INCLUSIVE 1.0 D TEST 2 TEST 3 TEST 3 TEST 3 TEST 3 TEST 3 TEST 3 (0-04) 6 (05-09) 0 (10-14) 6 (15-19) 6 (OVER .19) 6 (OVER .19	TEMPERATURE OF	ALCO SENSOR (1	10°C - 40°C)				26 8		
SIMULATOR SOLUTION COMPRESSED ETHANOL-GAS MIXTURE SIMULATOR SUPPLIER LOT # 27 90 EXP. DATE [01] SIM. NIST EXP DATE [01] SIM. NIST EXP. DATE [01] SIM. NIST E	PRINTER WORKING	PROPERLY							
SIMULATOR SOLUTION COMPRESSED ETHANOL-GAS MIXTURE LOT # 23 9 EXP. DATE [01] 20 SIM. NIST EXP DATE [0	TIME AND DATE DIS	PLAYING PROPE	RLY						
STANDARD SUPPLIER LOT # 23 90 EXP. DATE [01320] SIMULATOR TEMPERATURE (34°C ± 0.2°C)	BREATH ALCOHOL ACC	URACY STANDA	RDS						
SIMULATOR TEMPERATURE (34°C ± 0.2°C) SIM. SN SIM. SIM. SIM. SIM. NIST EXP DATE SIM. SIM. SIM. SIM. SIM. NIST EXP DATE SIM. SIM. SIM. SIM. SIM. SIM. SIM. SIM	SIMULATOR SOLUTION	RESSED	ETHANOL-GA	S MIXTURE					
SIMULATOR TEMPERATURE (34°C ± 0.2°C) 34.5°C SIM. SIM. SIM. SIM. SIM. NIST EXP DATE SIM. SIM. SIM. SIM. SIM. SIM. SIM. SIM.	STANDARD SUPPLIE	R GUTH		LOT# 23	390	EXP. DATE	10-1)-2	b) T	
CALIBRATION CHECK — (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 o less Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.095% and 0.084% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.093% and 0.042% INCLUSIVE TEST 1 TEST 2 TEST 3 TEST	SIMULATOR TEMPER	RATURE (34°C ± 0	1.2°C) 140°C						
Interests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less, check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE 1			•		7				
0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE TEST 1 TEST 2 TEST 3 TEST	Run three tests using a	a standard solution	ANDARD IS TO BE	USED PER MA	INTENA	NCE REPORT)			
U.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE TEST 1 TEST 2 TEST 3 TEST	less Check the box cor	rresponding to the	standard solution be	ing used (PDINI	Of the Sta	andard value an	d must have	e a spread of .005 o	
0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE TEST 1 TEST 2 TEST 3 TEST	0.100% STANDAR	RD - MUST READ	BETWEEN 0.095% a	and 0 105% INC	LUSIVE	TACHED)			
TEST 1 TEST 2 TEST 3 TE	U 0.080% STANDAR	RD - MUST READ	BETWEEN 0.076% a	and 0.084% INC	LUSIVE				
RFI DETECTOR OPERATING NDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: DO NOT INCLUDE SELF-ADMINISTERED TESTS) REFUSALS (004) (0509) (1014) (1519) (OVER .19) (OVER .19) (OVER .19) (Include Self-Administration or modification that was made to restore the instrument to operate satisfactorily and within stabilished limits (use other side if necessary). REFUSALS (Include Self-Administration or modification that was made to restore the instrument to operate satisfactorily and within stabilished limits (use other side if necessary). REFUSALS (Include Self-Administration or modification that was made to restore the instrument to operate satisfactorily and within stabilished limits (use other side if necessary). REFUSALS (Include Self-Administration or modification that was made to restore the instrument to operate satisfactorily and within stabilished limits (use other side if necessary). REFUSALS (Include Self-Administration or modification that was made to restore the instrument to operate satisfactorily and within stabilished limits (use other side if necessary).	LJ 0.040% STANDAF	RD - MUST READ	BETWEEN 0.038% a	and 0.042% INC	LUSIVE				
PRINT NAME SPECTING OFFICER SMATURE PRINT NAME PRI	TEST 1 F	-	TEST 2 - 4/0	D	Т	EST 3 🖝	. 1 0	D	
NDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: DO NOT INCLUDE SELF-ADMINISTERED TESTS) REFUSALS (004) (.0509) (.1014) (.1519) (OVER .19) (OVER .19) (OVER .19) (OVER .19) (Include Self-ADMINISTERED TESTS) Is any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and within stablished limits (use other side if necessary). ISPECTING OFFICER GNATURE PRINT NAME PE II PERMIT NUMBERVEXPIRATION DATE TELEPHONE NUMBER 3. 4 - 3 9 3 - 4 8 9 Peturn completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office.	RFI DETECTOR OPER	ATING			,		10	0	
REFUSALS (004) (0509) (1014) (1014) (1019) (OVER .19) (OVER .19) (IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII									
ISPECTING OFFICER GNATURE PEINT NAME PE II PERMIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 3, 4-393-499, eturn completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services, Southeast District Office	DO NOT INCLUDE SELF-	OF BREATH TEST ADMINISTERED 1	S IN THE FOLLOW! (ESTS)	NG RANGES S	INCE TH	E LAST MAINT	ENANCE F	REPORT:	
ISPECTING OFFICER GNATURE PEINT NAME PE II PERMIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 3, 4-393-499, eturn completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services, Southeast District Office	REFUSALS A (C)04)	(05-09)	(10-14)		/15 10)	1,000		
ISPECTING OFFICER GNATURE PRINT NAME PRINT NAME PRINT NAME TELEPHONE NUMBER 3, 4-393-499, eturn completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office				(.1014)	6	(.1519)	(OVE	ER .19)	
PRINT NAME PE II PERMIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 3, 4-393-499 Peturn completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office.	stablished limits (use other	side if necessary)		was made to re	estore the	e instrument to	operate sati	sfactorily and within	
PE II PERMIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 3, 4-393-899 eturn completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office		,,							
PE II PERMIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 3, 4-393-899 eturn completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office									
PE II PERMIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 3, 4-393-899 eturn completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office									
PE II PERMIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 3, 4-393-899 eturn completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office									
PE II PERMIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 3, 4-393-899 eturn completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office									
PE II PERMIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 3, 4-393-895 Peturn completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office									
PE II PERMIT NUMBER/EXPIRATION DATE TELEPHONE NUMBER 3, 4-393-895 Peturn completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office	SPECTING OFFICER					STANTON DE LOS CALLANS DE LOS CALLAN			
eturn completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office	GNATURE				PRI	NT NAME			
23 = 2 Sq / / / / 2 = 2 T	PE II DEDMIT NI ACCOUNT					021/11.	2, </td <td>-</td>	-	
eturn completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office	2300 0 11/					1			
eturn completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services, Southeast District Office by mail, fax, or email.	31	11//				7		9	
	eturn completed report to	the: Breath Alco	phol Program, MO De	partment of Hea	alth and S	Senior Services,	Southeast I	District Office	

TEST RECORD 00194

TEST RECORD 00194

9/
Temp Date Time 210L

Air Blank:
10/24/24 15:17 .000

Calibration Check:
24 10/24/24 15:17 .100

Subject Name

Subject I.D.

Operator Name, I.D.

Location

AS IV Serial no: 097418

AS IV Serial no: 897418 Version no: 532B

TEST RECORD 00195
s/
Temp Date Time 2:08L
Air Blank:
10/24/24 15:18 .000
Calibration Check:
25 10/24/24 15:18 .100
Subject Name

Location WEST

Operator Name: I.D.

AS IV Serial no: 097418
Version no: 532B

TEST RECORD 00196

Sy

Temp Date Time 210L

Air Blank:
10/24/24 15:20 .000

Calibration Check:
25 10/24/24 15:20 .100

Subject Name

Subject I.D.

Operator Name: I.D.

Location

AS IV Serial no: 097418 Version no: 5327

TEST RECORD 00197

Temp Date Time 210L

VOID: RFI 12 10/24/24 15:23

Subject Name

Subject I.D.

Operator Name, I.D.

Location UES



CERTIFICATE OF ANALYSIS

Certified Alcohol Reference Solution for Simulator

Random Samples of Lot Number 23390 of Alcohol Reference Solution for Simulator were analyzed by gas chromatography on October 18, 2023, using a Perkin Elmer Gas Chromatograph Autosystem XL S/N: 610N9030209, and found to contain 0.1207% (w/vol) ethyl alcohol. The expiration date for this lot number is October 17, 2025 at 11:59 PM.

When used in a calibrated Simulator, operating at 34°C +/- 2°C, this solution will give a breath alcohol analysis instrument reading of 0.100 g/210L +/- 3%.

The alcohol and water used in this solution were free of test interfering substances.

Ted L. Pauley, President GUTH LABORATORIES, INC.

NIST Traceability:

Testing was conducted using Cerilliant Reference Standard lot number FN03072301 whose values are traceable to NIST.

All balances are calibrated annually by an outside agency using NIST traceable weights. Calibration verification is done prior to each use utilizing NIST traceable weights.



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES BREATH ALCOHOL PROGRAM



PERMIT TYPE

DANNY E. WEST

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s): ALCO-SENSOR IV WITH PRINTER for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo. Mile Mason DIRECTOR OF STATE PUBLIC HEALTH LABORATORY 11/14/2023 NUMBER 230254 Davla J. Michelso DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES EXPIRES 11/14/2025 LAB-4 (R6-10)

MO 580-0777 (6-10)



The named cardholder is authorized to operate an evidential breath alcohol instrument for the determination of the alcoholic content in breath form of expired ai in Missouri.

Operator

WEST, DANNY

Permit No 230254 Date Issued 11/14/2023

Date Expires 11/14/2025

