

By Tracy Crews at 8:04 am, Dec 04, 2024



MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY

ALCO-SENSOR IV WITH PRINTER MAINTENANCE REPORT

REPORT #7

Send copy to Departmen			E OF AGENCY						
1002	86		Cuba				DAT	E OF INSPECTIO	N
LOCATION OF INSTRUMENT (STREET AND CITY		cusa	10			711.00	12-3-24	
602 S. Fran	aklin St	Cuba						E OF INSPECTION	
CHECKLIST: Place a ma where determined.) Unma	k in the box by e	ach item if fo	und to be sa	atisfactory	or if operat	ing within est	ahlished lii	mito Ottain in	
where determined.) Unma			a pelote dal	ing instru	ment.				
TEMPERATURE OF	ALCO SENSOR	(10°C - 40°C	C)						
PRINTER WORKING	PROPERLY								
TIME AND DATE DIS									
REATH ALCOHOL ACC		ARDS							
SIMULATOR SOLUTION					OMPRESS	ED ETHANC	DL-GAS M	IXTURE	
STANDARD SUPPLIE	R_Guda			LOT#_	23390	EXP. D	ATE 10	17-25	
SIMULATOR TEMPER	ATURE (34°C ±	0.2°C) _ 3	<u>4°</u> s	IM. SN _	MP 38	72 s	IM. NIST E	EXP DATE 5.	7-25
CALIBRATION CHECK Run three tests using a less. Check the box cor 0.100% STANDAR 0.080% STANDAR	- (ONLY ONE S standard solution responding to the D - MUST REAL D - MUST REAL	STANDARD I on. All three to e standard so D BETWEEN D BETWEEN	lests must b olution being 0.095% an	De within : g used. (I ad 0.105% ad 0.084%	R MAINTEN ±5% of the PRINTOUT INCLUSIV	standard val ATTACHED) E		ust have a spre	
CALIBRATION CHECK Run three tests using a less. Check the box cor 0.100% STANDAR 0.080% STANDAR 0.040% STANDAR	- (ONLY ONE S standard solution responding to the RD - MUST REAL RD - MUST REAL RD - MUST REAL	STANDARD I on. All three to e standard so D BETWEEN D BETWEEN D BETWEEN	lests must be plution being 0.095% and 0.076% and 0.038% and	De within : g used. (I ad 0.105% ad 0.084%	R MAINTEN ±5% of the PRINTOUT INCLUSIV	standard val ATTACHED) (E (E (E	ue and mu		
CALIBRATION CHECK Run three tests using a less. Check the box cor 0.100% STANDAR 0.080% STANDAR 0.040% STANDAR	- (ONLY ONE S standard solution responding to the RD - MUST REAL RD - MUST REAL RD - MUST REAL	STANDARD I on. All three to e standard so D BETWEEN D BETWEEN	lests must be plution being 0.095% and 0.076% and 0.038% and	De within : g used. (I ad 0.105% ad 0.084%	R MAINTEN ±5% of the PRINTOUT INCLUSIV	standard val ATTACHED) E			
CALIBRATION CHECK Run three tests using a less. Check the box cor 0.100% STANDAR 0.080% STANDAR 0.040% STANDAR ST 1 - /0/ RFI DETECTOR OPERA	- (ONLY ONE S standard solution responding to the RD - MUST READ RD - MUST READ RD - MUST READ RD - MUST READ	STANDARD I on. All three 1 e standard so D BETWEEN D BETWEEN D BETWEEN	lests must be obtained being 10.095% and 10.038% and 1	pe within a gused. (I guse	R MAINTEN 15% of the PRINTOUT INCLUSIV INCLUSIV	standard val ATTACHED) /E /E /E TEST 3 •	ue and mu)/	ead of .00
CALIBRATION CHECK Run three tests using a less. Check the box cor 0.100% STANDAR 0.080% STANDAR 0.040% STANDAR	- (ONLY ONE S standard solution responding to the RD - MUST READ RD - MUST READ ATING	TEST 2	lests must be obtained being 10.095% and 10.038% and 1	pe within a gused. (I guse	R MAINTEN 15% of the PRINTOUT INCLUSIV INCLUSIV	standard val ATTACHED) /E /E /E TEST 3 •	ue and mu)/	ead of .00
CALIBRATION CHECK Run three tests using a less. Check the box cor 0.100% STANDAR 0.080% STANDAR 0.040% STANDAR ST 1 - /0/ RFI DETECTOR OPER/ CONTINCLUDE SELF-A	- (ONLY ONE S standard solution responding to the RD - MUST READ RD - MUST READ ATING PF BREATH TES ADMINISTERED	STANDARD I on. All three 1 e standard so D BETWEEN D BETWEEN TEST 2 TEST 2 TEST SIN THE I TESTS)	iests must bolution being 0.095% and 0.076% and 0.038%	pe within a gused. (I od 0.105% ad 0.084% ad 0.042%	R MAINTEN 15% of the PRINTOUT INCLUSIV INCLUSIV INCLUSIV	standard val ATTACHED) /E /E /E TEST 3 -	,/O	NCE REPORT	ead of .00
CALIBRATION CHECK Run three tests using a less. Check the box cor O.100% STANDAR O.080% STANDAR O.040% STANDAR ST 1/O/ RFI DETECTOR OPER/ DICATE THE NUMBER OF NOT INCLUDE SELF-A FUSALS (0.	(ONLY ONE S standard solution responding to the RD - MUST READ RD - MUST READ RTING PF BREATH TES ADMINISTERED	STANDARD I on. All three i e standard so D BETWEEN D BETWEEN TEST 2 TEST 2 TESTS IN THE i TESTS)	iests must be plution being 10.095% and 10.076% and 10.038% and 10	g used. (I nd 0.105% nd 0.084% nd 0.042%	R MAINTEN 15% of the PRINTOUT INCLUSIV INCLUSIV INCLUSIV	standard val ATTACHED) /E /E /E TEST 3 **	,/O	NCE REPORT	ead of .00
CALIBRATION CHECK Run three tests using a less. Check the box cor 0.100% STANDAR 0.080% STANDAR 0.040% STANDAR The control of the control	- (ONLY ONE S standard solution responding to the RD - MUST READ RD - MUST READ ATING PF BREATH TES ADMINISTERED04) ribe any alteration	STANDARD I on. All three 1 e standard so D BETWEEN D BETWEEN TEST 2 TEST 2 TEST 5 (.0509)	iests must be plution being 10.095% and 10.076% and 10.038% and 10	g used. (I nd 0.105% nd 0.084% nd 0.042%	R MAINTEN 15% of the PRINTOUT INCLUSIV INCLUSIV INCLUSIV	standard val ATTACHED) /E /E /E TEST 3 **	,/O	NCE REPORT	ead of .00
CALIBRATION CHECK Run three tests using a less. Check the box cor 0.100% STANDAR 0.080% STANDAR 0.040% STANDAR ST 1 - /0/ RFI DETECTOR OPERA CONOT INCLUDE SELF-A any new parts and descent	- (ONLY ONE S standard solution responding to the RD - MUST READ RD - MUST READ ATING PF BREATH TES ADMINISTERED04) ribe any alteration	STANDARD I on. All three 1 e standard so D BETWEEN D BETWEEN TEST 2 TEST 2 TEST 5 (.0509)	iests must be plution being 10.095% and 10.076% and 10.038% and 10	g used. (I nd 0.105% nd 0.084% nd 0.042%	R MAINTEN 15% of the PRINTOUT INCLUSIV INCLUSIV INCLUSIV	standard val ATTACHED) /E /E /E TEST 3 **	,/O	NCE REPORT	ead of .00
CALIBRATION CHECK Run three tests using a less. Check the box cor 0.100% STANDAR 0.080% STANDAR 0.040% STANDAR The standar The standar Control of the standar Control o	- (ONLY ONE S standard solution responding to the RD - MUST READ RD - MUST READ ATING PF BREATH TES ADMINISTERED04) ribe any alteration	STANDARD I on. All three 1 e standard so D BETWEEN D BETWEEN TEST 2 TEST 2 TEST 5 (.0509)	iests must be plution being 10.095% and 10.076% and 10.038% and 10	g used. (I nd 0.105% nd 0.084% nd 0.042%	R MAINTEN 15% of the PRINTOUT INCLUSIV INCLUSIV INCLUSIV	standard val ATTACHED) /E /E /E TEST 3 **	,/O	NCE REPORT	ead of .00
CALIBRATION CHECK Run three tests using a less. Check the box cor 0.100% STANDAR 0.080% STANDAR 0.040% STANDAR ST 1/0/ RFI DETECTOR OPER/ CONOT INCLUDE SELF-A FUSALS (0.040% STANDAR CONOT INCLUDE SELF-A EUSALS (0.040% STANDAR EUSALS (0.040% ST	- (ONLY ONE S standard solution responding to the RD - MUST READ RD - MUST READ ATING PF BREATH TES ADMINISTERED04) ribe any alteration	STANDARD I on. All three 1 e standard so D BETWEEN D BETWEEN TEST 2 TEST 2 TEST 5 (.0509)	iests must be plution being 10.095% and 10.076% and 10.038% and 10	g used. (I nd 0.105% nd 0.084% nd 0.042%	R MAINTEN 15% of the PRINTOUT INCLUSIV INCLUSIV INCLUSIV	standard val ATTACHED) /E /E /E TEST 3 **	,/O	NCE REPORT	ead of .00
CALIBRATION CHECK Run three tests using a less. Check the box cor 0.100% STANDAR 0.080% STANDAR 0.040% STANDAR ST 1 / / / / RFI DETECTOR OPER/ CONOT INCLUDE SELF-A FUSALS (0.40% any new parts and describilished limits (use other	- (ONLY ONE S standard solution responding to the RD - MUST READ RD - MUST READ ATING PF BREATH TES ADMINISTERED04) ribe any alteration	STANDARD I on. All three 1 e standard so D BETWEEN D BETWEEN TEST 2 TEST 2 TEST 5 (.0509)	iests must be plution being 10.095% and 10.076% and 10.038% and 10	g used. (I nd 0.105% nd 0.084% nd 0.042%	R MAINTEN 15% of the PRINTOUT INCLUSIV INCLUSIV ES SINCE	Standard val ATTACHED) /E /E /E TEST 3	,/O	(OVER .19)	ead of .00
CALIBRATION CHECK Run three tests using a less. Check the box cor 0.100% STANDAR 0.080% STANDAR 0.040% STANDAR ST 1/0/ RFI DETECTOR OPERA CONOT INCLUDE SELF-A FUSALS (0- any new parts and describilished limits (use other DECTING OFFICER FURE	a standard solution responding to the RD - MUST REAL RD - MUST REAL RD - MUST REAL RATING PERFECT REAL RATING PERFECT RESERVATION REPORT REAL RATING PERFECT REAL RATING PERFECT RESERVATION REPORT REAL RATING PERFECT REAL RATING REAL RATING REPORT REAL RATING PERFECT REAL RATING REPORT REAL RATING RE	STANDARD I on. All three 1 e standard so D BETWEEN D BETWEEN TEST 2 TEST 2 TEST 5 (.0509)	iests must be plution being 10.095% and 10.076% and 10.038% and 10	g used. (I nd 0.105% nd 0.084% nd 0.042%	R MAINTEN ES Of the PRINTOUT INCLUSIV INCLUSIV TO restore	Standard val ATTACHED) TE TE TEST 3 TEST 3 T	AINTENA	(OVER .19)	ead of .00
CALIBRATION CHECK Run three tests using a less. Check the box cor 0.100% STANDAR 0.080% STANDAR 0.040% STANDAR ST 1/0/ RFI DETECTOR OPER/ CONOT INCLUDE SELF-A FUSALS (0.040% STANDAR CONOT INCLUDE SELF-A EUSALS (0.040% STANDAR EUSALS (0.040% ST	a standard solution responding to the RD - MUST READ -	STANDARD I on. All three 1 e standard so D BETWEEN D BETWEEN TEST 2 TEST 2 TEST 5 (.0509)	iests must be plution being 10.095% and 10.076% and 10.038% and 10	g used. (I nd 0.105% nd 0.084% nd 0.042%	R MAINTEN ES Of the PRINTOUT INCLUSIV INCLUSIV TO restore	Standard val ATTACHED) TE TE TEST 3 TEST 3 T	AINTENA	(OVER .19) Ite satisfactorii	ead of .00

AS IV Serial no: 180286 Version no: 532B Subject I.D. Calibration Check: 22 12/03/24 16:10 .101 Temp Omerator Name, I.D. Subject Name Air Blank: endune, 602 S. Franklin St 163t Blan 16 12/83/24 16:18 .080 Date Time 2101 6300hB

TEST RECORD 01377 AS IV Serial no: 100286 Version no: 5328 12/03/24 16:12 .000 Calibration Check: 23 12/03/24 16:12 .101 Air Blank Subject Name Operator Name: I.D.
Censunci / 240089 Subject I.D. Location 602 S. Franklin St Blank 7551 Q

> Temp Date Time 2100 AS IV Serial no: 180286 Version no: 532B TEST RECORD 01378

Air Blank: 12/03/24 16:13 .000 Calibration Check: 23 12/03/24 16:13 .101

Subject Name Blank

Subject I.D.

Test 3

Operator Name, I.D.

Century / 240089

Location 602 S. Franklin &

AS IV Serial no: 188286 Version no: 5328

VOID: RFI TEST RECORD 01379 12 12/03/24 16:14

Subject Name

Blank

Subject I.D.

Cenduny / 240089

602 S. Franklin St Location



CERTIFICATE OF ANALYSIS

Certified Alcohol Reference Solution for Simulator

Random Samples of Lot Number 23390 of Alcohol Reference Solution for Simulator were analyzed by gas chromatography on October 18, 2023, using a Perkin Elmer Gas Chromatograph Autosystem XL S/N: 610N9030209, and found to contain 0.1207% (w/vol) ethyl alcohol. The expiration date for this lot number is October 17, 2025 at 11:59 PM.

When used in a calibrated Simulator, operating at 34°C +/- .2°C, this solution will give a breath alcohol analysis instrument reading of 0.100 g/210L +/- 3%.

The alcohol and water used in this solution were free of test interfering substances.

Ted L. Pauley, President GUTH LABORATORIES, INC.

NIST Traceability.

Testing was conducted using Cerilliant Reference Standard lot number FN03072301 whose values are traceable to NIST.

All balances are calibrated annually by an outside agency using NIST traceable weights. Calibration verification is done prior to each use utilizing NIST traceable weights.



Missouri Department of Health and Senior Services

P.O. Box 570, Jefferson City, MO 65102-0570 Phone: 573-751-6400 FAX: 573-751-6010 RELAY MISSOURI for Hearing and Speech Impaired 1-800-735-2966 VOICE 1-800-735-2466

Paula Nickelson Acting Director

SIMULATOR CERTIFICATION REPORT

SIMULATOR INFORMATION

Simulator Serial Number: MP3872

Manufacturer: Guth

Model Number:

12V500

Agency:

CUBA PD

Agency Address: 602 S FRANKLIN, CUBA, MO 65453

NIST THERMOMETER INFORMATION

Serial Number:

17KMM00690

Bias:

0.00

Uncertainty:

0.02

Date of Certification:

10/27/2023

Date of Expiration: 10/27/2024

ENVIRONMENTAL CONDITIONS

The environmental conditions during testing are within the tolerances of DHSS BAP method 3.

VERIFICATION RESULTS

Simulator Average 34.01

NIST Average

Combined Uncertainty

34.01 The combined uncertainty is calculated with a k=2 value.

ADJUSTMENT RESULTS

No adjustment was needed.

Date of testing:

5/7/2024

Certification Expiration:

5/7/2025

Simulator testing technician: M. BOND

Notes on Condition: none

Deviation(s) from method: none

DHSS BAP Scientist Approving:

BRIANNA MEDRANO

Certification No:

MP3872_572024

DHSS BAP Scientist Approving

Simulator Calibration Certification

Issued by Lab Manager, DHSS BAP Revision Date: 06/25/2022

Breath Alcohol Program 1903 Northwood Drive, Suite 4 Poplar Bluff, MO 63901

DHSS BAP Document 3.6A Revision 2


Page 1 of 1



MO 580-0771 (8-10)

STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES BREATH ALCOHOL PROGRAM



MICHAEL S. CENTUNZI

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and re

ALCO-SENSOR IV WITH PRINTER

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sect 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo.

NUMBER 240089 EXPIRES 4/8/2026

DIRECTOR OF STATE PUBLIC HEALTH LABORATORY

DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES



CENTUNZI, MICHAEL

