

### MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY

## RECEIVED By Tracy Crews at 6:56 am, Dec 13, 2024

#### ALCO-SENSOR IV WITH PRINTER MAINTENANCE REPORT

REPORT #7

less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED)  ✓ 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE  □ 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE  □ 0.040% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE  TEST 1  0.099  TEST 2  0.099  TEST 2  0.099  TEST 3  0.099  ✓ RFI DETECTOR OPERATING  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  (DO NOT INCLUDE SELF-ADMINISTERED TESTS)  REFUSALS  (0.04)  (.0509)  (.1014)  (.1519)  (OVER .19)  List any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and within established limits (use other side if necessary).  INSPECTING OFFICER  SIGNATURE  CPL R. D. Johnson  THE PERMIT NAME  CPL R. D. JOHNSON	1411						
Missouri State Highway Patrol 1/20/1204 1/20/1	Complete this report in du Send copy to Department	plicate at the time o of Health and Senio	of the regular month or Services; retain o	nly preventative maintena original in department file	ance check, and wh	enever instrument is repaired.	
TIME OF INSPECTION TOOR B. KORREUMENT ISTREET AND CITY TOOR B. ZODE 6 Office Kahoka, MO  CHECKLIST: Place a mark in the box by each item if found to be satisfactory or if operating within established limits. (Write in observed values where determined.) Unmarked items must be corrected before using instrument.  ☑ DIGITAL READOUT (ALL ELEMENTS OPERATIONAL)  ☑ TEMPERATURE OF ALCO SENSOR (10°C - 40°C)  ☑ PRINTER WORKING PROPERLY  ☑ TIME AND DATE DISPLAYING PROPERLY  ☑ SIMULATOR SOLUTION  ☑ COMPRESSED ETHANOL-GAS MIXTURE  ☑ SIMULATOR SOLUTION  ☑ STANDARD SUPPLIER Guth Labs  ☑ COMPRESSED ETHANOL-GAS MIXTURE  ☑ SIMULATOR TEMPERATURE (34°C ± 0.2°C) 34.02 SIM. SN MP2120 SIM. NIST EXP DATE 04/25/2025  ☑ CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or loss. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED)  ☑ 0.080%: STANDARD - MUST READ BETWEEN 0.055% and 0.036%: INCLUSIVE  ☐ 0.080%: STANDARD - MUST READ BETWEEN 0.055% and 0.036%: INCLUSIVE  ☐ 0.060%: STANDARD - MUST READ BETWEEN 0.055% and 0.048%: INCLUSIVE  ☐ 0.060%: STANDARD - MUST READ BETWEEN 0.055% and 0.048%: INCLUSIVE  ☐ 0.070%: STANDARD - MUST READ BETWEEN 0.055% and 0.048%: INCLUSIVE  ☐ 0.060%: STANDARD - MUST READ BETWEEN 0.055% and 0.048%: INCLUSIVE  ☐ 0.060%: STANDARD - MUST READ BETWEEN 0.055% and 0.048%: INCLUSIVE  ☐ 0.060%: STANDARD - MUST READ BETWEEN 0.055% and 0.048%: INCLUSIVE  ☐ 0.060%: STANDARD - MUST READ BETWEEN 0.055% and 0.048%: INCLUSIVE  ☐ 0.060%: STANDARD - MUST READ BETWEEN 0.055% and 0.048%: INCLUSIVE  ☐ 0.060%: STANDARD - MUST READ BETWEEN 0.055% and 0.048%: INCLUSIVE  ☐ 0.060%: STANDARD - MUST READ BETWEEN 0.055% and 0.048%: INCLUSIVE  ☐ 0.060%: STANDARD - MUST READ BETWEEN 0.055% and 0.048%: INCLUSIVE  ☐ 0.060%: STANDARD - MUST READ BETWEEN 0.055% and 0.048%: INCLUSIVE  ☐ 0.060%: STANDARD - MUST READ BETWEEN 0.055% and 0.048%: INCLUSIVE  ☐ 0.							
CHECKLIST: Place a mark in the box by each liem if found to be satisfactory or if operating within established limits. (Write in observed values where determined.) Limitaries and the corrected before using instrument.  DIGITAL READOUT (ALL ELEMENTS OPERATIONAL)  TEMPERATURE OF ALCO SENSOR (10°C - 40°C)  PRINTER WORKING PROPERLY  TIME AND DATE DISPLAYING PROPERLY  BREATH ALCOHOL ACCURACY STANDARDS  SIMULATOR SOLUTION  COMPRESSED ETHANOL-GAS MIXTURE  STANDARD SUPPLIER Guth Labs  LOT # 23390  EXP. DATE 10/17/2025  SIMULATOR TEMPERATURE (34°C ± 0.2°C)  34.02  SIM. SIM. MP2120  SIM. NIST EXP DATE 04/25/2025  CALIBRATION CHECK — (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED)  0.0109% STANDARD · MUST READ BETWEEN 0.036% and 0.068% INCLUSIVE  0.040% STANDARD · MUST READ BETWEEN 0.036% and 0.042% INCLUSIVE  0.040% STANDARD · MUST READ BETWEEN 0.036% and 0.042% INCLUSIVE  TEST 1 = 0.099  TEST 2 = 0.099  TEST 2 = 0.099  TEST 3 =	LOCATION OF INSTRUMENT (STREET AND CITY)						
## DIGITAL READOUT (ALL ELEMENTS OPERATIONAL)  ## DIGITAL READOUT (ALL ELEMENTS OPERATIONAL)  ## TEMPERATURE OF ALCO SENSOR (10°C - 40°C)  ## PRINTER WORKING PROPERLY  ## TIME AND DATE DISPLAYING PROPERLY  ## BREATH ALCOHOL ACCURACY STANDARDS  ## SIMULATOR SOLUTION  ## SANDARD SUPPLIER Guth Labs  ## SIMULATOR TEMPERATURE (34°C ≥ 0.2°C)  ## SIMULATOR TEMPERATURE			item if found to be s	atisfactory or if operating	within established li	mits. (Write in observed values	
DIGITAL READOUT (ALL ELEMENTS OPERATIONAL)   TEMPERATURE OF ALCO SENSOR (10°C - 40°C)   PRINTER WORKING PROPERLY   TIME AND DATE DISPLAYING PROPERLY   BREATH ALCOHOL ACCURACY STANDARDS   SIMULATOR SOLUTION	where determined.) Unma	rked items must be	corrected before us	sing instrument.			
TIME AND DATE DISPLAYING PROPERLY  BREATH ALCOHOL ACCURACY STANDARDS  SIMULATOR SOLUTION  COMPRESSED ETHANOL-GAS MIXTURE  STANDARD SUPPLIER Guth Labs  LOT # 23390  EXP. DATE 10/17/2025  SIM. NIST EXP DATE 04/25/2025  SIM. SIMILATOR TEMPERATURE (34°C ± 0.2°C)  SIM. SIM. SN. MP2120  SIM. NIST EXP DATE 04/25/2025  CALIBRATION CHECK − (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT.  Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED)  10.100% STANDARD - MUST READ BETWEEN 0.095% and 0.084% INCLUSIVE  10.040% STANDARD - MUST READ BETWEEN 0.038% and 0.105% INCLUSIVE  10.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE  10.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE  10.07 TEST 1 ▼ 0.099  TEST 2 ▼ 0.099  TEST 2 ▼ 0.099  TEST 3 ▼ 0.099  INSIDEATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: (DO NOT INCLUDE SELF-ADMINISTERED TESTS)  REFUSALS  10.05 0.09  10.1014)  11.5119)  11.52 0.0000 (OVER .19)  11.51 any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and within established limits (use other side if necessary).  11.52 0.0000 (PICE)  11.52 0.0000 (PICE)  12.54 0.0000 (PICE)  13.54 0.0000 (PICE)  14.55 0.0000 (PICE)  15.55 0.0000 (PICE)  15.55 0.0000 (PICE)  16.600 385-2132  Return completed report to the: Breath Alcohol Program. MO Department of Health and Senior Services, Southeast District Office							
## TIME AND DATE DISPLAYING PROPERLY    BREATH ALCOHOL ACCURACY STANDARDS	✓ TEMPERATURE OF ALCO SENSOR (10°C - 40°C)						
### STANDARD SUPPLIER Guth Labs  LOT # 23390  EXP. DATE 10/17/2025  SIMULATOR TEMPERATURE (34°C ± 0.2°C) 34.02  SIM. SN MP2120  SIM. NIST EXP DATE 04/25/2025  CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED)  0.009% STANDARD - MUST READ BETWEEN 0.095% and 0.165% INCLUSIVE  0.009% STANDARD - MUST READ BETWEEN 0.075% and 0.084% INCLUSIVE  0.009% STANDARD - MUST READ BETWEEN 0.075% and 0.042% INCLUSIVE  1.0099  TEST 1 ● 0.099  TEST 2 ● 0.099  TEST 3 ● 0.099  REI DETECTOR OPERATING  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: (DO NOT INCLUDE SELF-ADMINISTERED TESTS)  REFUSALS  (0.04)  (0.50-09)  (10-14)  (15-19)  (OVER .19)  List any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and within established limits (use other side if necessary).    INSPECTING OFFICER   PRINT NAME   CPL R. D. Johnson	✓ PRINTER WORKING PROPERLY						
SIMULATOR SOLUTION  COMPRESSED ETHANOL-GAS MIXTURE  INTERIOR SUPPLIER Guth Labs  LOT # 23390  EXP. DATE 10/17/2025  EXP. DATE 10/17/2025  SIM. NIST EXP DATE 04/25/2025  CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUTA TATACHED)  0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE  0.080% STANDARD - MUST READ BETWEEN 0.095% and 0.084% INCLUSIVE  0.080% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE  TEST 1 ● 0.099  TEST 2 ● 0.099  TEST 2 ● 0.099  TEST 3 ● 0.099  TEST 3 ● 0.099  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: (OD NOT INCLUDE SELF-ADMINISTERED TESTS)  REFUSALS  (0-04)  (05-09)  (1014)  (1519)  (OVER .19)  List any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and within established limits (use other side if necessary).  INSPECTING OFFICIAL  PRINT NAME (PRINT NAME (P	✓ TIME AND DATE DISPLAYING PROPERLY						
STANDARD SUPPLIER Guth Labs  LOT # 23390  EXP. DATE 10/17/2025  SIMULATOR TEMPERATURE (34°C ± 0.2°C) 34.02  SIM. SN MP2120  SIM. NIST EXP DATE 04/25/2025  CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT)  Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED)  O .100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE  0 .080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE  0 .080% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE  TEST 1 ▼ 0.099  TEST 2 ▼ 0.099  TEST 2 ▼ 0.099  TEST 3 ▼ 0.099  PRIOTECTOR OPERATING  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: (DO NOT INCLUDE SELF-ADMINISTERED TESTS)  REFUSALS  (0 - 0.4)  (05-09)  (.1014)  (.1519)  (OVER .19)  List any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and within established limits (use other side if necessary).  INSPECTING OFFICER  SIQUENTIAL THE PRIOR TARME  CPL R. D. Johnson  TELEPHONE NUMBER  (660) 385-2132  Return completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services, Southeast District Office	BREATH ALCOHOL ACC	URACY STANDAR	DS				
SIMULATOR TEMPERATURE (34°C ± 0.2°C) 34.02 SIM. SN MP2120 SIM. NIST EXP DATE 04/25/2025  CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED)  ○ 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE ○ 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE ○ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE ○ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE □ 0	✓ SIMULATOR SOLUTION ☐ COMPRESSE				D ETHANOL-GAS MIXTURE		
CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED)  O.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE TEST 1	STANDARD SUPPLIER Guth Labs			LOT # 23390	EXP. DATE 10/17/2025		
Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED)  0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE  0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE  0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE  TEST 1  0.099  TEST 2  0.099  TEST 3  0.099  TEST 3  0.099  TEST 3  0.099  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  (DO NOT INCLUDE SELF-ADMINISTERED TESTS)  REFUSALS  (0.04)  (.0509)  (.1014)  (.1519)  (OVER .19)  List any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and within established limits (use other side if necessary).  INSPECTING OFFICER  SEQUENCE OFFICER  SEQU	SIMULATOR TEMPERATURE (34°C ± 0.2°C) 34.02 SIM. SN MP2120 SIM. NIST EXP DATE 04/25/2025						
INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  (DO NOT INCLUDE SELF-ADMINISTERED TESTS)  REFUSALS  (004)  (.0509)  (.1014)  (.1519)  (OVER .19)  List any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and within established limits (use other side if necessary).  INSPECTING OFFICER  SIGNATURE  CPL R. D. Johnson  TYPE II PERMIT NUMBER CRITATION LATE  240036/1-02/05/2026  Return completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services, Southeast District Office	less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED)  ✓ 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE  □ 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE						
INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: (DO NOT INCLUDE SELF-ADMINISTERED TESTS)  REFUSALS  (004)  (.0509)  (.1014)  (.1519)  (OVER .19)  List any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and within established limits (use other side if necessary).    NSPECTING OFFICER   PRINT NAME   CPL R. D. Johnson	TEST 1 • 0.099		TEST 2 • 0.099		TEST 3 • 0.099		
REFUSALS (004) (.0509) (.1014) (.1519) (OVER .19)  List any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and within established limits (use other side if necessary).  INSPECTING OFFICER  SIGNATURE  PRINT NAME  CPL R. D. Johnson  Type II PERMIT NUMBER XPRATION OATE  240036/J.02/05/2026  Return completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services, Southeast District Office	✓ RFI DETECTOR OPE	RATING					
List any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and within established limits (use other side if necessary).    INSPECTING OFFICE:   PRINT NAME   CPL R. D. Johnson	INDICATE THE NUMBER	R OF BREATH TEST F-ADMINISTERED	TS IN THE FOLLO TESTS)	WING RANGES SINCE	THE LAST MAINTE	ENANCE REPORT:	
INSPECTING OFFICER  SIGNATURE  CPL R. D. Johnson  TELEPHONE NUMBER  (660) 385-2132  Return completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services, Southeast District Office	REFUSALS						
TYPE II PERMIT NUMBER EXPIRATION DATE  240036/L02/05/2026  Return completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services, Southeast District Office	List any new parts and de established limits (use oth	escribe any alteration ner side if necessary	on or modification the state of	hat was made to restore	the instrument to o	perate satisfactorily and within	
CPL R. D. Johnson  TYPE II PERMIT NUMBER EXPIRATION DATE  240036/J 02/05/2026  Return completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services, Southeast District Office	INSPECTING OFFICER				PRINT NAME	A CAN HAND THE REAL PROPERTY OF THE PARTY OF	
240036/J.02/05/2026 (660) 385-2132  Return completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services, Southeast District Office	SIGNATURE	1	<del>77</del> 7.62			son	
Return completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services, Southeast District Office		ION DATE					
by mail fax, or email.		rt to the: Breath A	Icohol Program, MC	Department of Health a	and Senior Services	, Southeast District Office	

#### DEC 0 1 2024

AS IV Serial no: 107990 Version no: 532B

TEST RECORD 01008

Time 210L Temp Date

Air Blank: 12/01/24 10:04 .000 Calibration Check:

23 12/01/24 10:04 .099

Subject Name

lest 1

Subject I.D.

TEST

Operator Name: I.D.

B.

AS IV Serial no: 107990 Version no: 532B

TEST RECORD 01010

Temp Date Time 210L

Air Blank:

12/01/24 10:08 .000

Calibration Check: 24 12/01/24 10:08 .099

Subject Name

Test

Subject I.D.

Test

Operator Name, I.D.

Location

(00P B. Kanoka AS IV Serial no: 107990 Version no: 532B

TEST RECORD 01009

Temp Date Time 210L

Air Blank:

12/01/24 10:06 .000

Calibration Check:

23 12/01/24 10:06 .099

Subject Name

Subject I.D.

Test

Operator Name, I.D.

K. Johnson

Location

rap B

AS IV Serial no: 107990 Version no: 532B

TEST RECORD 01011

Temp Date Time 210L

VOID: RFI

12 12/01/24 10:08

Subject Name

ubject I.I.

Operator Name, I.D.

K. Johnsa



#### STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES
BREATH ALCOHOL PROGRAM



# PERMIT

#### RILEY D. JOHNSON

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):

#### ALCO-SENSOR IV WITH PRINTER, INTOX DMT

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections

EXPIRES 2/5/2026

DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES

MO 580-0771 (6-10)

LAB-4 (R6-10)



The named cardholder is authorized to operate an evidential breath alcohol instrument for the determination of the alcoholic content in breath form of expired a in Missouri.

Operator JOHNSON, RILEY

