MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY

ALCO-SENSOR IV WITH PRINTER MAINTENANCE REPORT

REPORT #7

Complete this report in duplicate at the time of the regular monthly preventative maintenance check, and whenever instrument is report in duplicate at the time of the regular monthly preventative maintenance check, and whenever instrument is report of Department of Health and Senior Services; retain original in department file. ALCO SENSOR IV SN 111777 NAME OF AGENCY Missouri State Highway Patrol DATE OF INSPECTION 07/08/2024					
Missouri State Highway Patrol O7/08/2024 DOCATION OF INSTRUMENT (STREET AND CITY) 3131 E Kearney, Springfield, Missouri 65803 CHECKLIST: Place a mark in the box by each item if found to be satisfactory or if operating within established limits. (Write in observed where determined.) Unmarked items must be corrected before using instrument. DIGITAL READOUT (ALL ELEMENTS OPERATIONAL) TEMPERATURE OF ALCO SENSOR (10°C - 40°C) PRINTER WORKING PROPERLY TIME AND DATE DISPLAYING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS SIMULATOR SOLUTION □ COMPRESSED ETHANOL-GAS MIXTURE STANDARD SUPPLIER Guth Laboratories, INC LOT # 23390 EXP. DATE 10/17/2025 SIMULATOR TEMPERATURE (34°C ± 0.2°C) 33.99 SIM. SIM. NIST EXP DATE 12/05/203 CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .0 less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) O.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.095% and 0.084% INCLUSIVE TEST 1 ▼ .100 TEST 2 ▼ .099 TEST 3 ▼ .099					
TIME OF INSPECTION 3131 E Kearney, Springfield, Missouri 65803 CHECKLIST: Place a mark in the box by each item if found to be satisfactory or if operating within established limits. (Write in observed where determined.) Unmarked items must be corrected before using instrument. ✓ DIGITAL READOUT (ALL ELEMENTS OPERATIONAL) ✓ TEMPERATURE OF ALCO SENSOR (10°C - 40°C) ✓ PRINTER WORKING PROPERLY ✓ TIME AND DATE DISPLAYING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS ✓ SIMULATOR SOLUTION ☐ COMPRESSED ETHANOL-GAS MIXTURE ✓ STANDARD SUPPLIER Guth Laboratories, INC LOT # 23390 EXP. DATE 10/17/2025 ✓ SIMULATOR TEMPERATURE (34°C ± 0.2°C) 33.99 SIM. SN MP2418 SIM. NIST EXP DATE 12/05/200 ✓ CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .0 tess. Check the box corresponding to the standard solution being used. (PPINTOUT ATTACHED) ✓ 0.080% STANDARD - MUST READ BETWEEN 0.095% and 0.084% INCLUSIVE ☐ 0.080% STANDARD - MUST READ BETWEEN 0.095% and 0.084% INCLUSIVE ☐ 0.080% STANDARD - MUST READ BETWEEN 0.095% and 0.084% INCLUSIVE ☐ 0.080% STANDARD - MUST READ BETWEEN 0.095% and 0.084% INCLUSIVE ☐ 0.080% STANDARD - MUST READ BETWEEN 0.095% and 0.084% INCLUSIVE ☐ 0.040% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE ☐ 0.040% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE ☐ 0.040% STANDARD - MUST READ BETWEEN 0.076% and 0.042% INCLUSIVE ☐ 0.040% STANDARD - MUST READ BETWEEN 0.076% and 0.042% INCLUSIVE ☐ 0.040% STANDARD - MUST READ BETWEEN 0.076% and 0.042% INCLUSIVE ☐ 0.040% STANDARD - MUST READ BETWEEN 0.076% and 0.042% INCLUSIVE					
where determined.) Unmarked items must be corrected before using instrument. ✓ DIGITAL READOUT (ALL ELEMENTS OPERATIONAL) ✓ TEMPERATURE OF ALCO SENSOR (10°C - 40°C) ✓ PRINTER WORKING PROPERLY ✓ TIME AND DATE DISPLAYING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS ✓ SIMULATOR SOLUTION ☐ COMPRESSED ETHANOL-GAS MIXTURE ✓ STANDARD SUPPLIER Guth Laboratories, INC LOT # 23390 EXP. DATE 10/17/2025 ✓ SIMULATOR TEMPERATURE (34°C ± 0.2°C) 33.99 SIM. SN MP2418 SIM. NIST EXP DATE 12/05/203 ✓ CALIBRATION CHECK – (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .0 less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) ✓ 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE ☐ 0.080% STANDARD - MUST READ BETWEEN 0.095% and 0.042% INCLUSIVE ☐ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE ☐ 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE TEST 1 ▼ .100 TEST 2 ▼ .099 TEST 3 ▼ .099					
DIGITAL READOUT (ALL ELEMENTS OPERATIONAL) TEMPERATURE OF ALCO SENSOR (10°C - 40°C) PRINTER WORKING PROPERLY TIME AND DATE DISPLAYING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS SIMULATOR SOLUTION					
PRINTER WORKING PROPERLY TIME AND DATE DISPLAYING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS SIMULATOR SOLUTION					
TIME AND DATE DISPLAYING PROPERLY BREATH ALCOHOL ACCURACY STANDARDS SIMULATOR SOLUTION COMPRESSED ETHANOL-GAS MIXTURE COMPRESSED ETHANOL-GAS MIXTURE COMPRESSED ETHANOL-GAS MIXTURE STANDARD SUPPLIER Guth Laboratories, INC LOT # 23390 EXP. DATE 10/17/2025 SIMULATOR TEMPERATURE (34°C ± 0.2°C) 33.99 SIM. SN MP2418 SIM. NIST EXP DATE 12/05/2009 CALIBRATION CHECK – (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .00 less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) O.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE TEST 1 ▼ .100 TEST 2 ▼ .099 TEST 3 ▼ .099					
SIMULATOR SOLUTION COMPRESSED ETHANOL-GAS MIXTURE STANDARD SUPPLIER Guth Laboratories, INC LOT # 23390 EXP. DATE 10/17/2025 SIMULATOR TEMPERATURE (34°C ± 0.2°C) 33.99 SIM. SN MP2418 SIM. NIST EXP DATE 12/05/200 CALIBRATION CHECK − (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .0 less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) O.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE TEST 1 ★ .100 TEST 2 ★ .099					
SIMULATOR SOLUTION ☐ COMPRESSED ETHANOL-GAS MIXTURE ☐ STANDARD SUPPLIER Guth Laboratories, INC ☐ LOT # 23390 ☐ EXP. DATE 10/17/2025 ☐ SIMULATOR TEMPERATURE (34°C ± 0.2°C) 33.99 ☐ SIM. SN MP2418 ☐ SIM. NIST EXP DATE 12/05/203 ☐ CALIBRATION CHECK — (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) ☐ Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .0 less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) ☐ 0.100% STANDARD — MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE ☐ 0.080% STANDARD — MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE ☐ 0.040% STANDARD — MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE ☐ 0.040% STANDARD — MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE ☐ TEST 1 ■ .100 ☐ TEST 2 ■ .099 ☐ TEST 3 ■ .099					
STANDARD SUPPLIER Guth Laboratories, INC LOT # 23390 EXP. DATE 10/17/2025 SIMULATOR TEMPERATURE (34°C ± 0.2°C) 33.99 SIM. SN MP2418 SIM. NIST EXP DATE 12/05/2020 CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .0 less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE TEST 1 ▼ .100 TEST 2 ▼ .099 TEST 3 ▼ .099					
SIMULATOR TEMPERATURE (34°C ± 0.2°C) 33.99 SIM. SN MP2418 SIM. NIST EXP DATE 12/05/2020 CALIBRATION CHECK – (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .0 less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE TEST 1 ▼ .100 TEST 2 ▼ .099					
CALIBRATION CHECK – (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .0 less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE TEST 1 • .100 TEST 2 • .099					
Run three tests using a standard solution. All three tests must be within ±5% of the standard value and must have a spread of .0 less. Check the box corresponding to the standard solution being used. (PRINTOUT ATTACHED) 0.100% STANDARD - MUST READ BETWEEN 0.095% and 0.105% INCLUSIVE 0.080% STANDARD - MUST READ BETWEEN 0.076% and 0.084% INCLUSIVE 0.040% STANDARD - MUST READ BETWEEN 0.038% and 0.042% INCLUSIVE TEST 1 • .100 TEST 2 • .099 TEST 3 • .099					
FFI DETECTOR OPERATING					
INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: (DO NOT INCLUDE SELF-ADMINISTERED TESTS)					
REFUSALS 0 (004) 0 (.0509) 0 (.1014) 1 (.1519) 0 (OVER .19) -0					
List any new parts and describe any alteration or modification that was made to restore the instrument to operate satisfactorily and established limits (use other side if necessary).					
CHANGED TIME+2 MINUTES					
CHANGED TIME+2 MINUTES INSPECTING OFFICER SIGNATURE # 727 PRINT NAME D W Henley #727					

Return completed report to the: Breath Alcohol Program, MO Department of Health and Senior Services, Southeast District Office

by mail, fax, or email.

Serial n no: 5 r RECORD	Air Blank: 67/08/24 20:33 .000 Calibration Check: 72 87/08/24 20:33 .099	Subject Name TEST 3 Subject I.D.	Operator Name, I.D. L. HENLEY #227 Location 3331 F KEAD of y	Speed Free O, MO
AS IV Serial no: 111777 Version no: 532B TEST RECORD 00196 9/ Temp Date Time 210L	Air Blank: 07/08/24 20:32 .000 Calibration Check: 21 07/08/24 20:32 .099	Subject Name ### #################################	Operator Name, 1.D. () L) HENLEY #737 Location SIS) E KEARNEY	SPOETIKETELD, MO
AS IV Serial no: 111777 Usersion no: 532B TEST RECORD 00195 9/	C 60 - 10		Uperator Name, 1.1. OLU HENLEY#72> Location SISI E KEARNEY	SperwGFIE (D, 2012)

TEST RECORD 00198

Temp Date Time 210L

VOID: RFI
12 07/08/24 20:34 AS IV Serial no: 111777 Version no: 532B

Subject Name

Subject I.D.

OW HENLEY #737 Location OPERATOR NAME, I.D.

SORTNEFIELD MO



CERTIFICATE OF ANALYSIS

Certified Alcohol Reference Solution for Simulator

Random Samples of Lot Number 23390 of
Alcohol Reference Solution for Simulator were analyzed by
gas chromatography on October 18, 2023, using a Perkin Elmer Gas
Chromatograph Autosystem XL S/N: 610N9030209, and found to contain
0.1207% (w/vol) ethyl alcohol. The expiration date for this lot
number is October 17, 2025 at 11:59 PM.

When used in a calibrated Simulator, operating at 34°C +/- .2°C, this solution will give a breath alcohol analysis instrument reading of 0.100 g/210L +/- 3%.

The alcohol and water used in this solution were free of test interfering substances.

Ted L. Pauley, President GUTH LABORATORIES, INC.

NIST Traceability:

Testing was conducted using Cerilliant Reference Standard lot number FN03072301 whose values are traceable to NIST.

All balances are calibrated annually by an outside agency using NIST traceable weights. Calibration verification is done prior to each use utilizing NIST traceable weights.



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES BREATH ALCOHOL PROGRAM



PERMIT TYPE II

DAVID W. HENLEY, JR.

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):

ALCO-SENSOR IV WITH PRINTER, INTOX DMT

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo. DATE ___6/28/2024 DIRECTOR OF STATE PUBLIC HEALTH LABORATORY NUMBER 240144 Daves J. nichelson EXPIRES 6/28/2026 DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES LAB-4 (R6-10)

MO 580-0771 (6-10)





The named cardholder is authorized to operate an evidential breath alcohol instrument for the determination of the alcoholic content in breath form of expired ail in Missouri.

Operator HENLEY, JR., DAVID

Permit No 240144 Date Issued 6/28/2024

Date Expires 6/28/2026

