

MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY

RECEIVED By Tracy Crews at 2:00 pm, Oct 30, 2024

ALCO-SENSOR IV WITH PRINTER MAINTENANCE REPORT

REPORT #7

	-itii the time o	f the regular monthly preventative mainter	nance check, and whenever instrument is repai
omplete this report in du end copy to Department	of Health and Senio	r Services; retain original in department file	3.
LCO SENSOR IV SN 19732		NAME OF AGENCY North County Co-Op (MSC)	DATE OF INSPECTION 10/29/2024
OCATION OF INSTRUMENT (S 200 S. Holden St. War	TREET AND CITY)	93	TIME OF INSPECTION 1:45 pm
PHECKI IST: Place a mar	in the box by each	item if found to be satisfactory or if operatin	g within established limits. (Write in observed va
vhere determined.) Unma	rked items must be	corrected before using instrument.	
DIGITAL READOUT (ALL ELEMENTS OF	PERATIONAL)	
TEMPERATURE OF	ALCO SENSOR (10	°C - 40°C)	
PRINTER WORKING	PROPERLY		
TIME AND DATE DIS			
BREATH ALCOHOL ACC	URACY STANDAR		
☐ SIMULATOR SOLUT	ION	☑ COMPRESS	ED ETHANOL-GAS MIXTURE
STANDARD SUPPLI	ER Intoximeter's	LOT # AG311004	EXP. DATE <u>04/20/2025</u>
SIMULATOR TEMPE	RATURE (34°C ± 0	.2°C) SIM. SN	SIM. NIST EXP DATE
CALIBRATION CHECK Run three tests using less. Check the box of the control of the	CK – (ONLY ONE S) a standard solution or responding to the ARD - MUST READ	FANDARD IS TO BE USED PER MAINTED. All three tests must be within ±5% of the standard solution being used. (PRINTOU' BETWEEN 0.095% and 0.105% INCLUS	NANCE REPORT) e standard value and must have a spread of .0 Γ ATTACHED) VE
CALIBRATION CHECK Run three tests using less. Check the box of the control of the	CK – (ONLY ONE ST a standard solution corresponding to the ARD - MUST READ	FANDARD IS TO BE USED PER MAINTE	NANCE REPORT) e standard value and must have a spread of .0 Γ ATTACHED) VE VE
CALIBRATION CHECK Run three tests using less. Check the box of the control of the	K – (ONLY ONE ST a standard solution corresponding to the ARD - MUST READ ARD - MUST READ ARD - MUST READ	FANDARD IS TO BE USED PER MAINTED. All three tests must be within ±5% of the standard solution being used. (PRINTOUBETWEEN 0.095% and 0.105% INCLUS BETWEEN 0.076% and 0.084% INCLUS	NANCE REPORT) e standard value and must have a spread of .0 Γ ATTACHED) VE VE
CALIBRATION CHECK Run three tests using less. Check the box of the control of the	EK – (ONLY ONE ST a standard solution corresponding to the ARD - MUST READ ARD - MUST READ ARD - MUST READ	TANDARD IS TO BE USED PER MAINTEN. All three tests must be within ±5% of the standard solution being used. (PRINTOU' BETWEEN 0.095% and 0.105% INCLUS BETWEEN 0.076% and 0.084% INCLUS BETWEEN 0.038% and 0.042% INCLUS	NANCE REPORT) e standard value and must have a spread of .0 f ATTACHED) VE IVE IVE
CALIBRATION CHECK Run three tests using less. Check the box of the control of the	EK – (ONLY ONE ST a standard solution corresponding to the ARD - MUST READ ARD - MUST READ ARD - MUST READ ERATING	TANDARD IS TO BE USED PER MAINTED. All three tests must be within ±5% of the standard solution being used. (PRINTOU' BETWEEN 0.095% and 0.105% INCLUS BETWEEN 0.076% and 0.084% INCLUS BETWEEN 0.038% and 0.042% INCLUS TEST 2 .099	NANCE REPORT) e standard value and must have a spread of .0 f ATTACHED) IVE IVE IVE TEST 3 • .099
CALIBRATION CHECK Run three tests using less. Check the box of the control of the	EK – (ONLY ONE ST a standard solution corresponding to the ARD - MUST READ ARD - MUST READ ARD - MUST READ ERATING	TANDARD IS TO BE USED PER MAINTED. All three tests must be within ±5% of the standard solution being used. (PRINTOU' BETWEEN 0.095% and 0.105% INCLUS BETWEEN 0.076% and 0.084% INCLUS BETWEEN 0.038% and 0.042% INCLUS TEST 2 .099	NANCE REPORT) e standard value and must have a spread of .0 f ATTACHED) IVE IVE IVE TEST 3 • .099
CALIBRATION CHECK Run three tests using less. Check the box of the control of the	EK - (ONLY ONE ST a standard solution corresponding to the ARD - MUST READ ARD - MUST READ ARD - MUST READ ERATING ERATING R OF BREATH TES LF-ADMINISTERED	TANDARD IS TO BE USED PER MAINTE 1. All three tests must be within ±5% of the standard solution being used. (PRINTOU' BETWEEN 0.095% and 0.105% INCLUS BETWEEN 0.076% and 0.084% INCLUS BETWEEN 0.038% and 0.042% INCLUS TEST 2 .099 STS IN THE FOLLOWING RANGES SINCE TESTS) (.0509)	NANCE REPORT) e standard value and must have a spread of .0 f ATTACHED) VE IVE IVE TEST 3 • .099 E THE LAST MAINTENANCE REPORT: (.1519) (OVER .19)
CALIBRATION CHECK Run three tests using less. Check the box of the control of the	EK - (ONLY ONE ST a standard solution corresponding to the ARD - MUST READ ARD - MUST READ ARD - MUST READ ERATING ERATING R OF BREATH TES LF-ADMINISTERED (004)	TANDARD IS TO BE USED PER MAINTER. All three tests must be within ±5% of the standard solution being used. (PRINTOU' BETWEEN 0.095% and 0.105% INCLUS BETWEEN 0.076% and 0.084% INCLUS BETWEEN 0.038% and 0.042% INCLUS TEST 2 .099	NANCE REPORT) e standard value and must have a spread of .0 f ATTACHED) IVE IVE IVE TEST 3 • .099 E THE LAST MAINTENANCE REPORT:
CALIBRATION CHECK Run three tests using less. Check the box of the control of the	EK - (ONLY ONE ST a standard solution corresponding to the ARD - MUST READ ARD - MUST READ ARD - MUST READ ERATING B OF BREATH TES F-ADMINISTERED (004) describe any alteration	TANDARD IS TO BE USED PER MAINTER. All three tests must be within ±5% of the standard solution being used. (PRINTOU' BETWEEN 0.095% and 0.105% INCLUS BETWEEN 0.076% and 0.084% INCLUS BETWEEN 0.038% and 0.042% INCLUS TEST 2 .099	NANCE REPORT) e standard value and must have a spread of .0 TATTACHED) IVE IVE IVE IVE IVE I TEST 3 • .099 E THE LAST MAINTENANCE REPORT: (.1519) (OVER .19) ore the instrument to operate satisfactorily and
CALIBRATION CHECK Run three tests using less. Check the box of the control of the	EK – (ONLY ONE ST a standard solution forresponding to the ARD - MUST READ ARD - MUST READ ARD - MUST READ ERATING B OF BREATH TES LF-ADMINISTERED (004) describe any alteration of the side if necessary	TANDARD IS TO BE USED PER MAINTER. All three tests must be within ±5% of the standard solution being used. (PRINTOU' BETWEEN 0.095% and 0.105% INCLUS BETWEEN 0.076% and 0.084% INCLUS BETWEEN 0.038% and 0.042% INCLUS TEST 2 .099	NANCE REPORT) e standard value and must have a spread of .0 TATTACHED) IVE

AS IV Serial no: 119732 , Version no: 532C TEST RECORD 00188 Date Time 210L Air Blank: 10/29/24 13:45 .000 Calibration Check: 23 10/29/24 13:45 .100 Subject Name Operator Name, I.D. MSC

NS IV Serial no: 119732 Jersion no: 5320	•
TEST RECORD 00189	
Temp Date Time 210L	
Air Blank: 10/29/24 13:47 .000 Calibration Check: 24 10/29/24 13:47 .099	
Subject Name Jest 2	*
Subject I.D.	
Operator Name, I.D.	5
Zoćation MSC	

AS IV Serial no: 119732 Version no: 5320 TEST RECORD 00190 Temp Date Time 210L Air Blank: 10/29/24 13:48 .000 Calibration Check: 24 10/29/24 13:48 .099 Subject Name Subject I.D. Operator Name, I.D. Location MSC

AS IV Serial no: 119732 Version no: 5320

TEST RECORD 00191

Temp Date Time 210L

VOID: RFI 12 10/29/24 13:49

Subject Hame

Subject I.D.

Operator Wame, I.D.

Location

MSC



Airgas USA LLC (LAB) 3500 Bernard Street St. Louis, Mo. 63103 Ph: (314) 533-3100 Fax: (314) 533-7328

Certificate of Analysis

Customer Name

Exclusive Supplier Intoximeters, Inc. 2081 Craig Road St. Louis, Mo 63146 Test Date: 24-Apr-2023

Lot # AG311004 Model 108

Exp Date 20-Apr-2025 Cyl. Type 108 Component Ethanol Nitrogen Certified Concentration 0.100 ± 2% BrAC (272 ppm)

Certification Traceable to N.I.S.T. RGM and to CRM Ethanol Standards:

RGM Serial No. Concentration
EB0010581 391.8 ppm
EB0010570 259.8 ppm
EB0010285 209.0 ppm
EB0010561 103.7 ppm
EB0010681 52.22 ppm

RGM Serial No. Concentration
EB0010603 392.5 ppm
EB0010559 258.9 ppm
EB0010562 104.2 ppm
EB0010579 52.94 ppm

CRM Serial No. CC727481 CC727496 Concentration 800.0 ppm 253.0 ppm CRM Serial No. CC727493 CC727498 Concentration 390.0 ppm 150.0 ppm

Analytical Method: NDIR

Digitally signed by:Quality Control Reason:Dry gas standard certification of analysis Location:Airgas USA LtC (Lab) Date:05.05.2023 12:02

Approved for Release:

Rod Marsala

ISO 17025:2017 A2LA accredited. Certificate Number 3082.06 ISO 17034:2016 A2LA accredited. Certificate Number 3082.07



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES

BREATH ALCOHOL PROGRAM



PERMIT TYPE II

RYAN SCHILDKNECHT

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):

INTOX DMT, INTOXILYZER 8000, INTOX EC/IR II, ASIV W/PRINTER

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo.

10/10/2022	Laura & Navy
DATE 10/19/2023	DIRECTOR OF STATE PUBLIC HEALTH LABORATORY
NUMBER 230225	
EXPIRES 10/19/2025	DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES
10 -11 AWA (A 10)	LAB-4 (R6-10)

MO 580-0771 (6-10)



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES BREATH ALCOHOL PROGRAM

INSTRUMENT OPERATOR CARD

The named cardholder is authorized to operate an evidential breath alcohol instrument for the determination of the alcoholic content in breath form of expired air in Missouri.

PACE TO THE PROPERTY OF TH

Operator

SCHILDKNECHT, RYAN

Permit No 230225 Date Issued 10/19/2023

Date Expires 10/19/2025