

MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

INTOX EC/IR II MAINTENANCE REPORT

REPORT #3

Complete this report at the time of	of the regular monthly	z preventive maint	enance check /not	to evaced 25		
Complete this report at the time of the regular monthly preventive maintenance check (not to exceed 35 days). Complete this report whenever the instrument is serviced or repaired and whenever it is placed						
into service. Retain the original and send a copy within 15 days to the Breath Alcohol Program, DHSS.						
INTOX EC/IR II SN						
12673	NAME OF AGENCY		DATE OF INSPECTION			
	KIRKWOOD		09/15/2024			
LOCATION OF INSTRUMENT (STREET AND CITY	?)		TIME OF INSPECTION			
131 W. Madison Kirkwood			11:36 CDT			
CHECKLIST: Place a mark in the box	by each item if four	nd to be satisfact	ory or is operatin	ng within		
established limits. (Write in obse	rved values where det	termined). Unmarl	ced items must be o	corrected		
before using instrument.						
X DIAGNOSTIC RECORD						
X BLANK CHECK		X CO2 CHECK				
X FC 1 TEMP		X FLOW CHECK				
X SRC TEMP						

X DET TEMP		X CRC COMP CHE				
X BT TEMP		X CRC CAL CHEC	K			
X STD 2 TEMP		X PRINT TEST	, , , , , , , , , , , , , , , , , , , ,			
X ETH CHECK						
BREATH ANALYZER ACCURACY STAND	ARDS					
SIMULATOR SOLUTION		X COMPRESSED E	THANOL-GAS MIXTU	RE		
X STANDARD SUPPLIER INTOX	IMETERS	LOT# ag306807		DATE 03/09/20)25	
SIMULATOR TEMP (34°C +0.2°C)	SIM. S	N	SIM. NIST EXP I		***************************************	
			1			
CAT TODAMTON CUIDCIE (CATTER CAT						
X CALIBRATION CHECK - (ONLY ON	E STANDARD IS TO B	E USED PER MAIN	TENANCE REPORT)			
Run three tests using a stan	dard solution. All	l three tests m	ust be within +5%	of the standa	ard value	
Run three tests using a stan and must have a spread of .0	dard solution. All	l three tests m	ust be within +5%	of the standandard solution	ard value n being	
Run three tests using a stan	dard solution. All	l three tests m	ust be within +5%	of the standandard solution	ard value n being	
Run three tests using a stan and must have a spread of .0	dard solution. All 05 or less. Mark	l three tests m the box correspo	ust be within ±5% onding to the sta	of the standandard solution	ard value n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ	dard solution. All 05 or less. Mark	three tests muthe box correspondent	ust be within $\pm 5\%$ onding to the sta	of the standandard solution	ard value n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND	three tests method box corresponded to 0.105% INCLUS:	ust be within ±5% onding to the stance stance ive	of the standandandard solution	ard value n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND	three tests method box corresponded to 0.105% INCLUS:	ust be within ±5% onding to the stance stance ive	of the standandard solution	ard value n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND	three tests muthe box correspondent of the box	ust be within ±5% onding to the stance stance ive	andard solution	ard value n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 137 0.098	three tests muthe box correspondent of the box	ust be within ±5% onding to the state of the	andard solution	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 137 0.098	three tests muthe box correspondent of the box	ust be within ±5% onding to the state of the	andard solution	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 137 0.098	three tests muthe box correspondent of the box	ust be within ±5% onding to the state of the	andard solution	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM SATISFACTORILY AND WITHIN ESTABLISHED I	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.0098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED INSPECTING OFFICER SIGNATURE	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW .0509 0 ERATION OR MODIFICATION IMITS (USE OTHER SIDE IN	three tests method box corresponds of the box	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.0098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED INSPECTING OFFICER SIGNATURE	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TESTS IN THE FOLLOW .0509 0 PERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN THE SIDE	three tests method box corresponds to 0.105% INCLUS. D 0.084% INCLUS. D 0.042% INCLUS. D 0.	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW .0509 0 DERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN	three tests muthe box corresponds to 100.105% INCLUSED 0.084% INCLUSED 0.042% INCLUSED 0.042% INCLUSED 100.14 0 THAT WAS MADE TO REFERENCESSARY).	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TESTS IN THE FOLLOW .0509 0 PERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN THE SIDE	three tests method box corresponds to 0.105% INCLUS. D 0.084% INCLUS. D 0.042% INCLUS. D 0.	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 OF TESTS IN THE FOLLOW IN THE FOLLOW IN THE SIDE IN T	three tests muthe box corresponds to 100.105% INCLUSED 0.084% INCLUSED 0.042% INCLUSED 0.042% INCLUSED 100.14 0 THAT WAS MADE TO REFERENCESSARY).	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW .0509 0 PERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN ATION DATE 14/2025 TO THE:	three tests my the box corresponds to the box corresponds of the box	TEST 3 0.098 TEST 3 0.098 TEST 19 0 STORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19 TO OPERATE	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND	three tests muthe box correspondent of the box	ust be within ±5% pnding to the state stat	andard solution	ard value n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 137 0.098	three tests muthe box correspondent of the box	ust be within ±5% onding to the state of the	andard solution	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 137 0.098	three tests muthe box correspondent of the box	ust be within ±5% onding to the state of the	andard solution	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.038% AND TEST 2 0.098 of TESTS IN THE FOLLOW	three tests methe box corresponding the local corresponding to the local co	ust be within ±5% onding to the state of the	andard solution B g/210L FENANCE REPORT	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.038% AND TEST 2 0.098 of TESTS IN THE FOLLOW.	three tests methe box correspondent of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM SATISFACTORILY AND WITHIN ESTABLISHED I	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM SATISFACTORILY AND WITHIN ESTABLISHED I	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW	three tests method box corresponds of the box	ust be within ±5% onding to the state of the	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.0098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED INSPECTING OFFICER SIGNATURE	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW .0509 0 ERATION OR MODIFICATION IMITS (USE OTHER SIDE IN	three tests method box corresponds of the box	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.0098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED INSPECTING OFFICER SIGNATURE	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW .0509 0 ERATION OR MODIFICATION IMITS (USE OTHER SIDE IN	three tests method box corresponds of the box	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.0098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED INSPECTING OFFICER SIGNATURE	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW .0509 0 ERATION OR MODIFICATION IMITS (USE OTHER SIDE IN	three tests method box corresponds of the box	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.0098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED INSPECTING OFFICER SIGNATURE	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TESTS IN THE FOLLOW .0509 0 PERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN THE SIDE	three tests method box corresponds of the box	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.0098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED INSPECTING OFFICER SIGNATURE	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TESTS IN THE FOLLOW .0509 0 PERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN THE SIDE	three tests method box corresponds to 0.105% INCLUS. D 0.084% INCLUS. D 0.042% INCLUS. D 0.	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.0098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED INSPECTING OFFICER SIGNATURE	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TESTS IN THE FOLLOW .0509 0 PERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN THE SIDE	three tests method box corresponds to 0.105% INCLUS. D 0.084% INCLUS. D 0.042% INCLUS. D 0.	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TESTS IN THE FOLLOW .0509 0 PERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN THE SIDE	three tests method box corresponds to 0.105% INCLUS. D 0.084% INCLUS. D 0.042% INCLUS. D 0.	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW .0509 0 DERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN	three tests method box corresponds to 0.105% INCLUS. D 0.084% INCLUS. D 0.042% INCLUS. D 0.	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW .0509 0 DERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN	three tests method box corresponds to 0.105% INCLUS. D 0.084% INCLUS. D 0.042% INCLUS. D 0.	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW .0509 0 DERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN	three tests muthe box corresponds to 100.105% INCLUSED 0.084% INCLUSED 0.042% INCLUSED 0.042% INCLUSED 100.14 0 THAT WAS MADE TO REFERENCESSARY).	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW .0509 0 DERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN	three tests muthe box corresponds to 100.105% INCLUSED 0.084% INCLUSED 0.042% INCLUSED 0.042% INCLUSED 100.14 0 THAT WAS MADE TO REFERENCESSARY).	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW .0509 0 DERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN	three tests muthe box corresponds to 100.105% INCLUSED 0.084% INCLUSED 0.042% INCLUSED 0.042% INCLUSED 100.14 0 THAT WAS MADE TO REFERENCESSARY).	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW .0509 0 DERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN	three tests muthe box corresponds to 100.105% INCLUSED 0.084% INCLUSED 0.042% INCLUSED 0.042% INCLUSED 100.14 0 THAT WAS MADE TO REFERENCESSARY).	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM SATISFACTORILY AND WITHIN ESTABLISHED INSPECTING OFFICER SIGNATURE TYPE II PERMIT NUMBER EXPIR 230253 EXPIR 230253	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 OF TESTS IN THE FOLLOW IN THE FOLLOW IN THE SIDE IN T	three tests muthe box corresponds to 100.105% INCLUSED 0.084% INCLUSED 0.042% INCLUSED 0.042% INCLUSED 100.14 0 THAT WAS MADE TO REFERENCESSARY).	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM SATISFACTORILY AND WITHIN ESTABLISHED INSPECTING OFFICER SIGNATURE TYPE II PERMIT NUMBER EXPIR 230253 EXPIR 230253	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 OF TESTS IN THE FOLLOW IN THE FOLLOW IN THE SIDE IN T	three tests muthe box corresponds to 100.105% INCLUSED 0.084% INCLUSED 0.042% INCLUSED 0.042% INCLUSED 100.14 0 THAT WAS MADE TO REFERENCESSARY).	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM SATISFACTORILY AND WITHIN ESTABLISHED INSPECTING OFFICER SIGNATURE TYPE II PERMIT NUMBER EXPIR 230253 EXPIR 230253	dard solution. All 05 or less. Mark of BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 OF TESTS IN THE FOLLOW IN THE FOLLOW IN THE SIDE IN T	three tests muthe box corresponds to 100.105% INCLUSED 0.084% INCLUSED 0.042% INCLUSED 0.042% INCLUSED 100.14 0 THAT WAS MADE TO REFERENCESSARY).	ust be within ±5% onding to the state ive ive ive TEST 3 0.098 CE THE LAST MAINT .1519 0 ESTORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW .0509 0 PERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN ATION DATE 14/2025 TO THE:	three tests my the box corresponds to the box corresponds of the box	TEST 3 0.098 TEST 3 0.098 TEST 19 0 STORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19 TO OPERATE	n being	
Run three tests using a stan and must have a spread of .0 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.000 1.00	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW .0509 0 PERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN ATION DATE 14/2025 TO THE:	three tests my the box corresponds to the box corresponds of the box	TEST 3 0.098 TEST 3 0.098 TEST 19 0 STORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19 TO OPERATE	n being	
Run three tests using a stan and must have a spread of .0 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.098 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALM SATISFACTORILY AND WITHIN ESTABLISHED INSPECTING OFFICER SIGNATURE TYPE II PERMIT NUMBER EXPIR 230253 EXPIR 230253	dard solution. All 05 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.098 TESTS IN THE FOLLOW .0509 0 PERATION OR MODIFICATION LIMITS (USE OTHER SIDE IN ATION DATE 14/2025 TO THE:	three tests my the box corresponds to the box corresponds of the box	TEST 3 0.098 TEST 3 0.098 TEST 19 0 STORE THE INSTRUMENT	andard solution 3 g/210L FENANCE REPORT OVER .19 TO OPERATE	n being	



Airgas USA LLC (LAB)

3500 Bernard Street St. Louis, Mo. 63103 Ph: (314) 533-3100 Fax: (314) 533-7328

Certificate of Analysis

Customer Name Exclusive Supplier Intoximeters, Inc. 2081 Craig Road St. Louis, Mo 63146 Test Date: 13-Mar-2023

Lot # AG306807 **Model** 108

Exp DateCyl. TypeComponentCertified Concentration9-Mar-2025108Ethanol0.100 ± 2% BrAC (272 ppm)

Nitrogen

Certification Traceable to N.I.S.T. RGM and to CRM Ethanol Standards:

RGM Serial No.	Concentration	RGM Serial No.	Concentration
EB0010581	391.8 ppm	EB0010603	392.5 ppm
EB0010570	259.8 ppm	EB0010559	258.9 ppm
EB0010285	209.0 ppm	EB0010562	104.2 ppm
EB0010561	103.7 ppm	EB0010579	52.94 ppm
EB0010681	52.22 ppm		

 CRM Serial No.
 Concentration
 CRM Serial No.
 Concentration

 CC727481
 800.0 ppm
 CC727493
 390.0 ppm

 CC727496
 253.0 ppm
 CC727498
 150.0 ppm

Analytical Method: NDIR

ISO 17025:2017 A2LA accredited. Certificate Number 3082.06

ISO 17034:2016 A2LA accredited. Certificate Number 3082.07



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES
BREATH ALCOHOL PROGRAM



PERMIT TYPE II

THOMAS W. O'BRIEN

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):

INTOX EC/IR II

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo.

577.020 through 577.041, RSMo and 306.111 through 306.119 RSMi	Mike Massur
DATE11/14/2023	
	DIRECTOR OF STATE PUBLIC HEALTH LABORATORY
NUMBER 230253	
EXPIRES 11/14/2025	Davla J. Nichelson
	DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES

MO 580-0771 (6-10)

LAB-4 (R6-10)



The named cardholder is authorized to operate an evidential breath alcohol instrument for the determination of the alcoholic content in breath form of expired air in Missouri.

Operator O'BRIEN, THOMAS

Permit No 230253

