

MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

	MAINTENANCE REPORT	1	REPORT #3	
Complete this report at the time of the regular monthly preventive maintenance check (not to exceed 35				
days). Complete this report whenever the instrument is serviced or repaired and whenever it is placed				
into service. Retain the original a	nd send a copy within 15 da		, DHSS.	
INTOX EC/IR II SN	NAME OF AGENCY	DATE OF INSPECTION		
12685	SPRINGFIELD POLICE DEP	T 07/06/2024		
LOCATION OF INSTRUMENT (STREET AND CITY)		TIME OF INSPECTION		
2026 W BATTLEFIELD SPRINGFIELD,	MO	15:13 CDT		
CHECKLIST: Place a mark in the box	by each item if found to be	e satisfactory or is operating wit	thin	
established limits. (Write in obser	ved values where determined	d). Unmarked items must be corre	cted	
before using instrument.		5 * 5×3h	****	
X DIAGNOSTIC RECORD				
X BLANK CHECK	X CO2	CHECK		
X FC 1 TEMP		W CHECK		
X SRC TEMP		CHECK		
		COMP CHECK		
X DET TEMP				
X BT TEMP		CAL CHECK		
X STD 2 TEMP	X PRI	NT TEST		
X ETH CHECK				
BREATH ANALYZER ACCURACY STANDA	RDS			
SIMULATOR SOLUTION	TX COM	PRESSED ETHANOL-GAS MIXTURE		
			3 03/13/2026	
		ISIM. NIST EXP DATE		
SIMULATOR TEMP (34°C ±0.2°C)	SIM. SN	SIM. NIST EXP DATE		
	AMANDA DE AMANDA			
X CALIBRATION CHECK - (ONLY ON	S STANDARD IS TO BE USED	PER MAINTENANCE REPORT)		
			the standard value	
Run three tests using a stand	dard solution. All three	<pre>PER MAINTENANCE REPORT) e tests must be within ±5% of x corresponding to the standax</pre>		
Run three tests using a stand	dard solution. All three	e tests must be within ±5% of		
Run three tests using a stand and must have a spread of .00	dard solution. All three	e tests must be within ±5% of x corresponding to the standar		
Run three tests using a stand and must have a spread of .00 used.	dard solution. All three 05 or less. Mark the book	e tests must be within ±5% of x corresponding to the standar		
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ	dard solution. All three 05 or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08	e tests must be within <u>+</u> 5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE		
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ X 0.08% STANDARD - MUST READ	dard solution. All three 05 or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08	e tests must be within <u>+</u> 5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE		
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ X 0.08% STANDARD - MUST READ	dard solution. All three 05 or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE	rd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2	rd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2	rd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2 ANGES SINCE THE LAST MAINTENAME.	rd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04 TEST 2 0.079 g/210L TESTS IN THE FOLLOWING R.	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2 ANGES SINCE THE LAST MAINTENAM	cd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH TEST 1 004 119	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04 TEST 2 0.079 g/210L TESTS IN THE FOLLOWING RESTS IN THE MODIFICATION THAT WAS BETWEEN OR MODIFICATION THAT WAS BETWEEN OR MODIFICATION THAT WAS BETWEEN 0.0509 0 .10	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2 ANGES SINCE THE LAST MAINTENAMED TO RESTORE THE INSTRUMENT TO ONE STANDE THE INSTRUMENT THE INST	cd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH THE STANDARD - MUST READ REFUSALS 1 004 119 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04 TEST 2 0.079 g/210L TESTS IN THE FOLLOWING RESTS IN THE MODIFICATION THAT WAS BETWEEN OR MODIFICATION THAT WAS BETWEEN OR MODIFICATION THAT WAS BETWEEN 0.0509 0 .10	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2 ANGES SINCE THE LAST MAINTENAMED TO RESTORE THE INSTRUMENT TO ONE STANDE THE INSTRUMENT THE INST	cd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH THE STANDARD - MUST READ REFUSALS 1 004 119 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04 TEST 2 0.079 g/210L TESTS IN THE FOLLOWING RESTS IN THE MODIFICATION THAT WAS BETWEEN OR MODIFICATION THAT WAS BETWEEN OR MODIFICATION THAT WAS BETWEEN 0.0509 0 .10	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2 ANGES SINCE THE LAST MAINTENAMED TO RESTORE THE INSTRUMENT TO ONE STANDE THE INSTRUMENT THE INST	cd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH THE STANDARD - MUST READ REFUSALS 1 004 119 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04 TEST 2 0.079 g/210L TESTS IN THE FOLLOWING RESTS IN THE MODIFICATION THAT WAS BETWEEN OR MODIFICATION THAT WAS BETWEEN OR MODIFICATION THAT WAS BETWEEN 0.0509 0 .10	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2 ANGES SINCE THE LAST MAINTENAMED TO RESTORE THE INSTRUMENT TO ONE STANDE THE INSTRUMENT THE INST	cd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH THE STANDARD - MUST READ REFUSALS 1 004 119 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04 TEST 2 0.079 g/210L TESTS IN THE FOLLOWING RESTS IN THE MODIFICATION THAT WAS BETWEEN OR MODIFICATION THAT WAS BETWEEN OR MODIFICATION THAT WAS BETWEEN 0.0509 0 .10	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2 ANGES SINCE THE LAST MAINTENAMED TO RESTORE THE INSTRUMENT TO ONE STANDE THE INSTRUMENT THE INST	cd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH TEST 1 004 119 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED L	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04 TEST 2 0.079 g/210L TESTS IN THE FOLLOWING RESTS IN THE MODIFICATION THAT WAS BETWEEN OR MODIFICATION THAT WAS BETWEEN OR MODIFICATION THAT WAS BETWEEN 0.0509 0 .10	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2 ANGES SINCE THE LAST MAINTENAMED TO RESTORE THE INSTRUMENT TO ONE STANDE THE INSTRUMENT THE INST	cd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH TEST 1 004 119 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LINSPECTING OFFICER	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04 TEST 2 0.079 g/210L FESTS IN THE FOLLOWING R. .0509 0 .10 ERRATION OR MODIFICATION THAT WAS IMITS (USE OTHER SIDE IF NECESS	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2 ANGES SINCE THE LAST MAINTENAM 14 0 .1519 0 OVINGS MADE TO RESTORE THE INSTRUMENT TO ORDARY).	cd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH TEST 1 004 119 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED L INSPECTING OFFICER SIGNATURE	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04 TEST 2 0.079 g/210L FESTS IN THE FOLLOWING R. .0509 0 .10 ERRATION OR MODIFICATION THAT WAS IMITS (USE OTHER SIDE IF NECESS	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2 ANGES SINCE THE LAST MAINTENAM 14 0 .1519 0 OVINGS MADE TO RESTORE THE INSTRUMENT TO OUT TO SARY).	cd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH : REFUSALS 1 004 119 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED L INSPECTING OFFICER SIGNATURE 3	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04 TEST 2 0.079 g/210L FESTS IN THE FOLLOWING R. .0509 0 .10 ERRATION OR MODIFICATION THAT WAS IMITS (USE OTHER SIDE IF NECESS	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2 ANGES SINCE THE LAST MAINTENAM 14 0 .1519 0 OVINGS MADE TO RESTORE THE INSTRUMENT TO ORDARY).	cd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ X 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH TEST 1 004 119 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED L INSPECTING OFFICER SIGNATURE TYPE II PERMIT NUMBER EXPIRE	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04 TEST 2 0.079 g/210L TESTS IN THE FOLLOWING R. .0509 0 .10 ERATION OR MODIFICATION THAT WAS IMITS (USE OTHER SIDE IF NECESS	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2 ANGES SINCE THE LAST MAINTENAM 14 0 .1519 0 OVINGS MADE TO RESTORE THE INSTRUMENT TO OFFICE THE INSTRUMENT	cd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ X 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH TEST 1 004 119 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED L INSPECTING OFFICER SIGNATURE TYPE II PERMIT NUMBER EXPIRE	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04 TEST 2 0.079 g/210L FESTS IN THE FOLLOWING R. .0509 0 .10 ERRATION OR MODIFICATION THAT WAS IMITS (USE OTHER SIDE IF NECESSES) PRINT: KAUFNATION DATE TELEPHO	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2 ANGES SINCE THE LAST MAINTENAM 14 0 .1519 0 OVINGS MADE TO RESTORE THE INSTRUMENT TO ORDARY).	cd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ X 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH TEST 1 004 119 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED L INSPECTING OFFICER SIGNATURE TYPE II PERMIT NUMBER EXPIRE	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04 TEST 2 0.079 g/210L FESTS IN THE FOLLOWING R. .0509 0 .10 ERATION OR MODIFICATION THAT WAS IMITS (USE OTHER SIDE IF NECESSES) PRINT R. KAUFN ATION DATE TELEPHORY (417	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2 ANGES SINCE THE LAST MAINTENAM 14 0 .1519 0 OVINGS MADE TO RESTORE THE INSTRUMENT TO OFFICE THE INSTRUMENT	cd solution being	
Run three tests using a stand and must have a spread of .00 used. 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH TEST 1 004 119 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED L INSPECTING OFFICER SIGNATURE 1040 TYPE II PERMIT NUMBER EXPIR 240140 06/2	dard solution. All three of or less. Mark the box BETWEEN 0.095% AND 0.10 BETWEEN 0.076% AND 0.08 BETWEEN 0.038% AND 0.04 TEST 2 0.079 g/210L FESTS IN THE FOLLOWING R. .0509 0 .10 ERRATION OR MODIFICATION THAT WAS IMITS (USE OTHER SIDE IF NECESSED) PRINT: KAUFN ATTON DATE TELEPHORY 21/2026 (417	e tests must be within ±5% of x corresponding to the standar 5% INCLUSIVE 4% INCLUSIVE 2% INCLUSIVE TEST 3 0.079 g/2 ANGES SINCE THE LAST MAINTENAM 14 0 .1519 0 OVINS MADE TO RESTORE THE INSTRUMENT TO ORDARY). FULL NAME MAN, BENJAMIN ONE NUMBER) 864-1810	cd solution being	



Airgas USA LLC (LAB) 3500 Bernard Street St. Louis, Mo. 63103 Ph: (314) 533-3100 Fax: (314) 533-7328

Certificate of Analysis

Customer Name Exclusive Supplier Intoximeters, Inc. 2081 Craig Road St. Louis, Mo 63146

Test Date: 13-Mar-2024

Lot # AG407302 Model 108

Exp Date 13-Mar-2026 Cyl. Type 108 Component Ethanol **Certified Concentration**

0.080 ± 0.002 BrAC (218 ppm)

Nitrogen

Certification Traceable to N.I.S.T. RGM and to CRM Ethanol Standards:

RGM Serial No.	Concentration	RGM Serial No.	Concentration
EB0010581	391.8 ppm	EB0010603	392.5 ppm
EB0010570	259.8 ppm	EB0010559	258.9 ppm
EB0010285	209.0 ppm	EB0010562	104.2 ppm
EB0010561	103.7 ppm	EB0010579	52.94 ppm
EB0010681	52.22 ppm		· · · · · ·

 CRM Serial No.
 Concentration
 CRM Serial No.
 Concentration

 CC727481
 799.4 ppm
 CC727493
 389.8 ppm

 CC727496
 253.4 ppm
 CC727498
 150.2 ppm

Analytical Method: NDIR

Digitally signed by:Quality Control Reason:Dry gas standard certification of analysis Location:Airgas USA LLC (Lab) Date:03.15.2024 08:01

Approved for Release:

Yusef Woods

ISO 17025:2017 A2LA accredited. Certificate Number 3082.06 ISO 17034:2016 A2LA accredited. Certificate Number 3082.07





STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES
BREATH ALCOHOL PROGRAM



PERMIT TYPE II

BENJAMIN R. KAUFMAN


is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):

INTOX EC/IR II

for the determination of the alcoholic content of blood	d from a sample of expired air. Permit issued under the provisions of sections
577.020 through 577.041, RSMo and 306.111 throu	gh 306.119 RSMo.
•	
DATE6/21/2024	Mile Masson
	DIRECTOR OF STATE PUBLIC HEALTH LABORATORY
NUMBER 240140	
	Daves J. Nichelson
EXPIRES 6/21/2026	
	DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES

MO 580-0771 (6-10)

LAB-4 (R6-10)



The named cardholder is authorized to operate an evidential breath alcohol instrument for the determination of the alcoholic content in breath form of expired ai in Missouri.

Operator KAUFMAN, BENJAMIN Permit No 240140

Date Issued 6/21/2024 Date Expires 6/21/2026

