

#### MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

| INTOX EC/IR II   | MAINTENANCE F   | LEPURI   |  | REPORT #3                                    |
|--|---|--|--|--|
| Complete this report at the time of the regular monthly preventive maintenance check (not to exceed 35   |   |  |  |  |
| days). Complete this report wheneve  | r the instrument i  | services or repai  | red and whenever it  | is placed                                    |
| into service. Retain the original a  |   |  |  | ram, DHSS.                                   |
| INTOX EC/IR II SN  | NAME OF AGENCY SPRINGFIELD POLI   | 7  | DATE OF INSPECTION   |  |
| 12685  | SPRINGFIELD POLI  | CE DEEL  | 08/06/2024   |  |
| LOCATION OF INSTRUMENT (STREET AND CITY)   |   |  | TIME OF INSPECTION   |  |
| 2026 W BATTLEFIELD SPRINGFIELD,  |   |  | 13:52 CDT  |  |
| CHECKLIST: Place a mark in the box   | by each item if four  | d to e satisfact   | ory or is operating  |  |
| established limits. (Write in obser  | ved values where det  | erming). Unmark  | ced items must be co   | orrected                                     |
| before using instrument.   |   | al   |  |  |
| X DIAGNOSTIC RECORD  |   | X C HECK   |  |  |
| X BLANK CHECK  |   | X COL CHECK  |  |  |
| X FC 1 TEMP  |   | X FINN CHECK   |  |  |
| X SRC TEMP   |   | X FC HECK  |  |  |
| X DET TEMP   |   |  |  |  |
| X BT TEMP  |   | A AL GURG  |  |  |
|  |   | TEST   |  |  |
| X STD 2 TEMP   |   |  |  |  |
| X ETH CHECK  |   | <b>ज</b> ह   |  |  |
| BREATH ANALYZER ACCURACY STANDA  |   |  |  |  |
| SIMULATOR SOLUTION   |   | # MA 407302  | THANOL-GAS MIXTUR  | E  |
| X STANDARD SUPPLIER INTOX  | IMETERS   | # MAC 407302   | EXP.   | DATE 03/13/2026                              |
| SIMULATOR TEMP (34°C +0.2°C)   | SIM. S  |  | SIM. NIST EXP D  | ATE  |
| SIMOLATOR TENT (54 C 15.2 C)   | D411. U   |  |  |  |
| l .  | I   |  | 1  |  |
|  |   |  |  |  |
| X CALIBRATION CHECK - (ONLY ONE  | S STANDARD IS TO B  | E USED PER MAIN  | PENANCE REPORT)  |  |
| X CALIBRATION CHECK - (ONLY ONE Run three tests using a stand  |   |  |  | of the standard value                        |
| <del>  </del>  | ard solution. Al  | l three tests m  | ust be within ±5%  |  |
| Run three tests using a stand  | ard solution. Al  | l three tests m  | ust be within ±5%  |  |
| Run three tests using a stand and must have a spread of .00  | dard solution. Al<br>05 or less. Mark   | l three tests mu<br>the box correspo   | ust be within $\pm 5\%$ onding to the star                                 |  |
| Run three tests using a stand<br>and must have a spread of .00<br>used.  | dard solution. Al<br>05 or less. Mark<br>BETWEEN 0.095% AN  | three tests muthe box corresponding 0.105% INCLUS  | ust be within $\pm 5\%$ onding to the star                                 |  |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ  | dard solution. Al<br>05 or less. Mark<br>BETWEEN 0.095% AN<br>BETWEEN 0.076% AN   | l three tests muthe box corresponding 0.105% INCLUS:   | ust be within <u>+</u> 5%<br>onding to the stan<br>IVE<br>IVE              |  |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ X 0.08% STANDARD - MUST READ   | dard solution. Al<br>05 or less. Mark<br>BETWEEN 0.095% AN<br>BETWEEN 0.076% AN   | l three tests muthe box corresponding 0.105% INCLUS:   | ust be within <u>+</u> 5%<br>onding to the stan<br>IVE<br>IVE<br>IVE       | ndard solution being                         |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ X 0.08% STANDARD - MUST READ   | dard solution. Al<br>05 or less. Mark<br>BETWEEN 0.095% AN<br>BETWEEN 0.076% AN<br>BETWEEN 0.038% AN  | l three tests muthe box corresponding 0.105% INCLUS:   | ust be within <u>+</u> 5%<br>onding to the stan<br>IVE<br>IVE              | ndard solution being                         |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L  | dard solution. Al<br>05 or less. Mark<br>BETWEEN 0.095% AN<br>BETWEEN 0.076% AN<br>BETWEEN 0.038% AN  | three tests muthe box correspond 0.105% INCLUS: D 0.084% INCLUS: D 0.042% INCLUS:  | ust be within ±5% onding to the star                                       | ndard solution being                         |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ  0.08% STANDARD - MUST READ  0.04% STANDARD - MUST READ  | dard solution. Al<br>05 or less. Mark<br>BETWEEN 0.095% AN<br>BETWEEN 0.076% AN<br>BETWEEN 0.038% AN  | three tests muthe box correspond 0.105% INCLUS: D 0.084% INCLUS: D 0.042% INCLUS:  | ust be within ±5% onding to the star                                       | ndard solution being                         |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L  | dard solution. Al<br>05 or less. Mark<br>BETWEEN 0.095% AN<br>BETWEEN 0.076% AN<br>BETWEEN 0.038% AN  | three tests muthe box correspond 0.105% INCLUS: D 0.084% INCLUS: D 0.042% INCLUS:  | ust be within ±5% onding to the star                                       | ndard solution being                         |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH 1  | dard solution. Al D5 or less. Mark  BETWEEN 0.095% AN BETWEEN 0.076% AN BETWEEN 0.038% AN TEST 2 0.079  TESTS IN THE FOLLO  | three tests muthe box correspond 0.105% INCLUS: D 0.084% INCLUS: D 0.042% INCLUS: g/210L WING RANGES SING  | onding to the startive  IVE  IVE  TEST 3 0.079  CE THE LAST MAINT          | g/210L ENANCE REPORT:  OVER .19 0            |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L  INDICATE THE NUMBER OF BREATH 1   | dard solution. Al D5 or less. Mark  BETWEEN 0.095% AN BETWEEN 0.076% AN BETWEEN 0.038% AN TEST 2 0.079  TEST 2 0.079  TESTS IN THE FOLLO  .0509 0  ERATION OR MODIFICATION  | three tests methe box correspond 0.105% INCLUS: D 0.084% INCLUS: D 0.042% INCLUS: g/210L WING RANGES SING .1014 1 THAT WAS MADE TO RE  | onding to the startive  IVE  IVE  TEST 3 0.079  CE THE LAST MAINT          | g/210L ENANCE REPORT:  OVER .19 0            |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH 1 REFUSALS 0 004 35 LIST ANY NEW PARTS AND DESCRIBE ANY ALTO   | dard solution. Al D5 or less. Mark  BETWEEN 0.095% AN BETWEEN 0.076% AN BETWEEN 0.038% AN TEST 2 0.079  TEST 2 0.079  TESTS IN THE FOLLO  .0509 0  ERATION OR MODIFICATION  | three tests methe box correspond 0.105% INCLUS: D 0.084% INCLUS: D 0.042% INCLUS: g/210L WING RANGES SING .1014 1 THAT WAS MADE TO RE  | onding to the startive  IVE  IVE  TEST 3 0.079  CE THE LAST MAINT          | g/210L ENANCE REPORT:  OVER .19 0            |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH 1 REFUSALS 0 004 35 LIST ANY NEW PARTS AND DESCRIBE ANY ALTO   | dard solution. Al D5 or less. Mark  BETWEEN 0.095% AN BETWEEN 0.076% AN BETWEEN 0.038% AN TEST 2 0.079  TEST 2 0.079  TESTS IN THE FOLLO  .0509 0  ERATION OR MODIFICATION  | three tests methe box correspond 0.105% INCLUS: D 0.084% INCLUS: D 0.042% INCLUS: g/210L WING RANGES SING .1014 1 THAT WAS MADE TO RE  | onding to the startive  IVE  IVE  TEST 3 0.079  CE THE LAST MAINT          | g/210L ENANCE REPORT:  OVER .19 0            |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH 1 REFUSALS 0 004 35 LIST ANY NEW PARTS AND DESCRIBE ANY ALTO   | dard solution. Al D5 or less. Mark  BETWEEN 0.095% AN BETWEEN 0.076% AN BETWEEN 0.038% AN TEST 2 0.079  TEST 2 0.079  TESTS IN THE FOLLO  .0509 0  ERATION OR MODIFICATION  | three tests methe box correspond 0.105% INCLUS: D 0.084% INCLUS: D 0.042% INCLUS: g/210L WING RANGES SING .1014 1 THAT WAS MADE TO RE  | onding to the startive  IVE  IVE  TEST 3 0.079  CE THE LAST MAINT          | g/210L ENANCE REPORT:  OVER .19 0            |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH 1 REFUSALS 0 004 35 LIST ANY NEW PARTS AND DESCRIBE ANY ALTO   | dard solution. Al D5 or less. Mark  BETWEEN 0.095% AN BETWEEN 0.076% AN BETWEEN 0.038% AN TEST 2 0.079  TEST 2 0.079  TESTS IN THE FOLLO  .0509 0  ERATION OR MODIFICATION  | three tests methe box correspond 0.105% INCLUS: D 0.084% INCLUS: D 0.042% INCLUS: g/210L WING RANGES SING .1014 1 THAT WAS MADE TO RE  | onding to the startive  IVE  IVE  TEST 3 0.079  CE THE LAST MAINT          | g/210L ENANCE REPORT:  OVER .19 0            |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH TREFUSALS 0 004 35 LIST ANY NEW PARTS AND DESCRIBE ANY ALTISALISFACTORILY AND WITHIN ESTABLISHED LESTARD   | dard solution. Al D5 or less. Mark  BETWEEN 0.095% AN BETWEEN 0.076% AN BETWEEN 0.038% AN TEST 2 0.079  TEST 2 0.079  TESTS IN THE FOLLO  .0509 0  ERATION OR MODIFICATION  | three tests methe box correspond 0.105% INCLUS: D 0.084% INCLUS: D 0.042% INCLUS: g/210L WING RANGES SING .1014 1 THAT WAS MADE TO RE  | onding to the startive  IVE  IVE  TEST 3 0.079  CE THE LAST MAINT          | g/210L ENANCE REPORT:  OVER .19 0            |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L INDICATE THE NUMBER OF BREATH TO STANDARD  | dard solution. Al D5 or less. Mark  BETWEEN 0.095% AN BETWEEN 0.076% AN BETWEEN 0.038% AN TEST 2 0.079  TEST 2 0.079  TESTS IN THE FOLLO  .0509 0  ERATION OR MODIFICATION  | three tests muthe box corresponds of the local | onding to the startive  IVE  IVE  TEST 3 0.079  CE THE LAST MAINT          | g/210L ENANCE REPORT:  OVER .19 0            |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ  TEST 1 0.080 g/210L  INDICATE THE NUMBER OF BREATH 1  REFUSALS 0 004 35  LIST ANY NEW PARTS AND DESCRIBE ANY ALTO SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTO SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTO SATISFACTORILY AND WITHIN ESTABLISHED LIST AND WITHIN ESTABLISHED LIST AND SATISFACTORILY AND SATISFACTORILY AND WITHIN ESTABLISHED LIST AND SATISFACTORILY AND SATISF   | dard solution. Al 05 or less. Mark BETWEEN 0.095% AN BETWEEN 0.076% AN BETWEEN 0.038% AN TEST 2 0.079 TESTS IN THE FOLLO  .0509 0 ERATION OR MODIFICATION IMITS (USE OTHER SIDE I   | three tests muthe box corresponds of the local | TEST 3 0.079  TEST 3 0.079  TEST 19 0  ESTORE THE INSTRUMENT               | g/210L ENANCE REPORT:  OVER .19 0            |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 10.04% STANDARD - MUST READ 10.05% STANDARD - MUST | dard solution. Al 15 or less. Mark  BETWEEN 0.095% AN BETWEEN 0.076% AN BETWEEN 0.038% AN TEST 2 0.079  TEST 2 0.079  TESTS IN THE FOLLO  .0509 0  ERATION OR MODIFICATION IMITS (USE OTHER SIDE IMITS)   | three tests methe box corresponds of the local | TEST 3 0.079  TEST 3 0.079  TEST 19 0  ESTORE THE INSTRUMENT               | g/210L ENANCE REPORT:  OVER .19 0            |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L  INDICATE THE NUMBER OF BREATH 1  REFUSALS 0 004 35  LIST ANY NEW PARTS AND DESCRIBE ANY ALTISATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISATISFACTORILY AND WITHIN ESTABLISHED LIST AND WITHIN ESTABLISH AND WITHIN   | dard solution. Al 05 or less. Mark  BETWEEN 0.095% AN BETWEEN 0.076% AN BETWEEN 0.038% AN  TEST 2 0.079  TESTS IN THE FOLLO  .0509 0  ERATION OR MODIFICATION IMITS (USE OTHER SIDE I   | three tests matche box corresponds of the local corresponds of the loca | TEST 3 0.079  TEST 3 0.079  TEST 19 0  ESTORE THE INSTRUMENT               | g/210L ENANCE REPORT:  OVER .19 0            |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L  INDICATE THE NUMBER OF BREATH 1  REFUSALS 0 004 35  LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND WITHIN ESTABLISH A   | dard solution. Al D5 or less. Mark  BETWEEN 0.095% AN BETWEEN 0.076% AN BETWEEN 0.038% AN TEST 2 0.079  TEST 2 0.079  TESTS IN THE FOLLO  CONTROL OF MODIFICATION IMITS (USE OTHER SIDE IMITS (USE OTHER SIDE IMITS) (USE OTHER SIDE IMITS)  ATION DATE 21/2026 | three tests methe box corresponds of the local | TEST 3 0.079  TEST 3 0.079  TEST 19 0  ESTORE THE INSTRUMENT               | g/210L ENANCE REPORT:  OVER .19 0            |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L  INDICATE THE NUMBER OF BREATH 1  REFUSALS 0 004 35  LIST ANY NEW PARTS AND DESCRIBE ANY ALTISATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALTISATISFACTORILY AND WITHIN ESTABLISHED LIST AND WITHIN ESTABLISH AND WITHIN   | dard solution. Al D5 or less. Mark  BETWEEN 0.095% AN BETWEEN 0.076% AN BETWEEN 0.038% AN TEST 2 0.079  TEST 2 0.079  TESTS IN THE FOLLO  CONTROL OF MODIFICATION IMITS (USE OTHER SIDE IMITS (USE OTHER SIDE IMITS) (USE OTHER SIDE IMITS)  ATION DATE 21/2026 | three tests matche box corresponds of the local corresponds of the loca | TEST 3 0.079  TEST 3 0.079  TEST 19 0  ESTORE THE INSTRUMENT               | g/210L ENANCE REPORT:  OVER .19 0            |
| Run three tests using a stand and must have a spread of .00 used.  0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.080 g/210L  INDICATE THE NUMBER OF BREATH 1  REFUSALS 0 004 35  LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LIST AND WITHIN ESTABLISH A   | dard solution. Al 15 or less. Mark  BETWEEN 0.095% AN BETWEEN 0.076% AN BETWEEN 0.038% AN TEST 2 0.079  TEST 2 0.079  TESTS IN THE FOLLO  .0509 0  ERATION OR MODIFICATION IMITS (USE OTHER SIDE IMITS (USE OTHER SIDE IMITS)  ATTON DATE 1/2026                | three tests methe box corresponds of the local | TEST 3 0.079  TEST 3 0.079  TEST 3 0.079  TEST 19 0  ESTORE THE INSTRUMENT | g/210L ENANCE REPORT:  OVER .19 0 TO OPERATE |



Airgas USA LLC (LAB) 3500 Bernard Street St. Louis, Mo. 63103 Ph: (314) 533-3100 Fax: (314) 533-7328

## **Certificate of Analysis**

Customer Name

Exclusive Supplier Intoximeters, Inc. 2081 Craig Road St. Louis, Mo 63146 Test Date: 13-Mar-2024

**Lot #** AG407302 **Model** 108

Exp Date 13-Mar-2026 Cyl. Type 108 **Component** Ethanol

Nitrogen

Certified Concentration

0.080 ± 0.002 BrAC (218 ppm)

Certification Traceable to N.I.S.T. RGM and to CRM Ethanol Standards:

| <b>RGM Serial No.</b> | Concentration | RGM Serial No. | Concentration |
|-----------------------|---------------|----------------|---------------|
| EB0010581             | 391.8 ppm     | EB0010603      | 392.5 ppm     |
| EB0010570             | 259.8 ppm     | EB0010559      | 258.9 ppm     |
| EB0010285             | 209.0 ppm     | EB0010562      | 104.2 ppm     |
| EB0010561             | 103.7 ppm     | EB0010579      | 52.94 ppm     |
| FB0010681             | 52 22 nnm     |                |               |

| CRM Serial No.       | Concentration          | CRM Serial No.       | Concentration |
|----------------------|------------------------|----------------------|---------------|
| CC727481<br>CC727496 | 799.4 ppm<br>253.4 ppm | CC727493<br>CC727498 | 389.8 ppm     |
| 00121430             | 255.4 ppm              | CC121430             | 150.2 ppm     |

Analytical Method: NDIR

Digitally signed by:Quality Control Reason:Dry gas standard certification of analysis Location:Airgas USA LLC (Lab) Date:03.15.2024 08:01

Approved for Release:

Yusef Woods

ISO 17025:2017 A2LA accredited. Certificate Number 3082.06 ISO 17034:2016 A2LA accredited. Certificate Number 3082.07



AG407302



### STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES
BREATH ALCOHOL PROGRAM



# PERMIT TYPE II

## **BENJAMIN R. KAUFMAN**

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):

### **INTOX EC/IR II**

| for the determination of the alcoholic content of blood from a sam |  |
|--|--|
| 577.020 through 577.041, RSMo and 306.111 through 306.119 F        | Mile Masson  |
| DATE6/21/2024  | / like / lassmi                                      |
| DATE   | DIRECTOR OF STATE PUBLIC HEALTH LABORATORY           |
| NUMBER 240140  |  |
| EXPIRES 6/21/2026  | Daves J. McCaller                                    |
| EXFINES WZWZWZW  | DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES |
| MO 580-0771 (6·10)   | LAB-4 (R6-10)  |



The named cardholder is authorized to operate an evidential breath alcohol instrument for the determination of the alcoholic content in breath form of expired air in Missouri.

Operator KAUFMAN, BENJAMIN

Permit No 240140

Date Issued 6/21/2024 Date Expires 6/21/2026

