

MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

	MAINTENANCE :	REPORT		REPORT #3
Complete this report at the time of the regular monthly preventive maintenance check (not to exceed 35				
days). Complete this report whenever the instrument is serviced or repaired and whenever it is placed into service. Retain the original and send a copy within 15 days to the Breath Alcohol Program, DHSS.				
INTOX EC/IR II SN	NAME OF AGENCY	in 15 days to the		
12686	SPRINGFIELD POLI	CE DEPT.	DATE OF INSPECTION 09/04/2024	
LOCATION OF INSTRUMENT (STREET AND CITY)		CE DELI.	TIME OF INSPECTION	
1199 N HASELTINE GC JAIL SPRING			12:57 CDT	
CHECKLIST: Place a mark in the box by each item if for		nd to be satisfact		
established limits. (Write in obser	ved values where de	termined). Unmar	ked items must be corrected	
before using instrument.				
X DIAGNOSTIC RECORD				
X BLANK CHECK		X CO2 CHECK		
X FC 1 TEMP		X FLOW CHECK		
X SRC TEMP		X FCB CHECK		
X DET TEMP		X CRC COMP CHE	X CRC COMP CHECK	
X BT TEMP		X CRC CAL CHEC	K	
X STD 2 TEMP		X PRINT TEST		
X ETH CHECK	<u> </u>			
BREATH ANALYZER ACCURACY STANDA	RDS			
SIMULATOR SOLUTION		COMPRESED F	THANOL-GAS MIXTURE	
	METERS	LOT# AG407302		
SIMULATOR TEMP (34°C +0.2°C)	SIM. S		EXP. DATE 03/13/20	26 ————
	51H. 5	IV	SIM. NIST EXP DATE	
CALIDRATION OF CALIBRATION				
CALIBRATION CHECK - (ONLY ONE			•	
Run three tests using a stand	ard solution. Al	1 three tests my	the second secon	
and much have a covered of one	Con loss March	. Torree ceses me	ist be within +5% of the standa	rd value
and must have a spread of .009 used.	5 or less. Mark	the box correspo	ist be within $\pm 5\%$ of the standa onding to the standard solution	rd value being
and must have a spread of .009 used.	5 or less. Mark	the box correspo	onding to the standard solution	rd value being
and must have a spread of .009 used. 0.10% STANDARD - MUST READ	5 or less. Mark BETWEEN 0.095% AN	the box corresponding of the box corresponding of the box corresponding to the box corresponding	onding to the standard solution	rd value being
and must have a spread of .009 used. 0.10% STANDARD - MUST READ 1 0.08% STANDARD - MUST READ 1	5 or less. Mark BETWEEN 0.095% AN BETWEEN 0.076% AN	the box corresponding of the box corresponding of the box corresponding to the box corresponding	onding to the standard solution IVE IVE	rd value being
and must have a spread of .009 used. 0.10% STANDARD - MUST READ	5 or less. Mark BETWEEN 0.095% AN BETWEEN 0.076% AN	the box corresponding of the box corresponding of the box corresponding to the box corresponding	onding to the standard solution IVE IVE	rd value being
and must have a spread of .009 used. 0.10% STANDARD - MUST READ 1 0.08% STANDARD - MUST READ 1	5 or less. Mark BETWEEN 0.095% AN BETWEEN 0.076% AN	the box corresponding to the box corresponding to the control of the control of the corresponding to the correspon	onding to the standard solution IVE IVE	rd value being
and must have a spread of .000 used. 0.10% STANDARD - MUST READ 1 0.08% STANDARD - MUST READ 1 0.04% STANDARD - MUST READ 1 TEST 1 0.077 g/210L	5 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.077	the box correspond of the corresponding the control of the corresponding to the corresponding	onding to the standard solution IVE IVE IVE TEST 3 0.077 g/210L	rd value being
and must have a spread of .00 used. 0.10% STANDARD - MUST READ 1 0.08% STANDARD - MUST READ 1 0.04% STANDARD - MUST READ 1	5 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.077	the box correspond of the corresponding the control of the corresponding to the corresponding	onding to the standard solution IVE IVE IVE TEST 3 0.077 g/210L	rd value being
and must have a spread of .00 used. 0.10% STANDARD - MUST READ 10.08% STANDARD - MUST READ 10.04% STANDARD - MUST READ 10.04% STANDARD - MUST READ 10.077 g/210L INDICATE THE NUMBER OF BREATH TO REFUSALS 0 004 0	5 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.077 ESTS IN THE FOLLOW	the box correspondence of the box correspond	TEST 3 0.077 g/210L TEST 3 0.077 g/210L THE LAST MAINTENANCE REPORT:	rd value being
and must have a spread of .000 used. 0.10% STANDARD - MUST READ 1 0.08% STANDARD - MUST READ 1 0.04% STANDARD - MUST READ 1 TEST 1 0.077 g/210L INDICATE THE NUMBER OF BREATH TO REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER	5 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND TEST 2 0.077 ESTS IN THE FOLLOW .0509 1 RATION OR MODIFICATION	the box correspond D 0.105% INCLUSI D 0.084% INCLUSI D 0.042% INCLUSI g/210L WING RANGES SINC .1014 3	TEST 3 0.077 g/210L TEST 3 0.077 g/210L THE LAST MAINTENANCE REPORT:	being
and must have a spread of .00 used. 0.10% STANDARD - MUST READ 10.08% STANDARD - MUST READ 10.04% STANDARD - MUST READ 10.04% STANDARD - MUST READ 10.077 g/210L INDICATE THE NUMBER OF BREATH TO REFUSALS 0 004 0	5 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND TEST 2 0.077 ESTS IN THE FOLLOW .0509 1 RATION OR MODIFICATION	the box correspond D 0.105% INCLUSI D 0.084% INCLUSI D 0.042% INCLUSI g/210L WING RANGES SINC .1014 3	TEST 3 0.077 g/210L TEST 3 0.077 g/210L THE LAST MAINTENANCE REPORT:	being
and must have a spread of .000 used. 0.10% STANDARD - MUST READ 1 0.08% STANDARD - MUST READ 1 0.04% STANDARD - MUST READ 1 TEST 1 0.077 g/210L INDICATE THE NUMBER OF BREATH TO REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER	5 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND TEST 2 0.077 ESTS IN THE FOLLOW .0509 1 RATION OR MODIFICATION	the box correspond D 0.105% INCLUSI D 0.084% INCLUSI D 0.042% INCLUSI g/210L WING RANGES SINC .1014 3	TEST 3 0.077 g/210L TEST 3 0.077 g/210L THE LAST MAINTENANCE REPORT:	being
and must have a spread of .000 used. 0.10% STANDARD - MUST READ 1 0.08% STANDARD - MUST READ 1 0.04% STANDARD - MUST READ 1 TEST 1 0.077 g/210L INDICATE THE NUMBER OF BREATH TO REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER	5 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND TEST 2 0.077 ESTS IN THE FOLLOW .0509 1 RATION OR MODIFICATION	the box correspond D 0.105% INCLUSI D 0.084% INCLUSI D 0.042% INCLUSI g/210L WING RANGES SINC .1014 3	TEST 3 0.077 g/210L TEST 3 0.077 g/210L THE LAST MAINTENANCE REPORT:	being
and must have a spread of .000 used. 0.10% STANDARD - MUST READ 1 0.08% STANDARD - MUST READ 1 0.04% STANDARD - MUST READ 1 TEST 1 0.077 g/210L INDICATE THE NUMBER OF BREATH TO REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER	5 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND TEST 2 0.077 ESTS IN THE FOLLOW .0509 1	the box correspond D 0.105% INCLUSI D 0.084% INCLUSI D 0.042% INCLUSI g/210L WING RANGES SINC .1014 3	TEST 3 0.077 g/210L TEST 3 0.077 g/210L THE LAST MAINTENANCE REPORT:	being
and must have a spread of .00 used. 0.10% STANDARD - MUST READ 10.08% STANDARD - MUST READ 10.04% STANDARD OF BREATH TO REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER SATISFACTORILY AND WITHIN ESTABLISHED LIN	5 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND TEST 2 0.077 ESTS IN THE FOLLOW .0509 1	the box correspond D 0.105% INCLUSI D 0.084% INCLUSI D 0.042% INCLUSI g/210L WING RANGES SINC .1014 3	TEST 3 0.077 g/210L TEST 3 0.077 g/210L THE LAST MAINTENANCE REPORT:	being
and must have a spread of .00 used. 0.10% STANDARD - MUST READ 1 0.08% STANDARD - MUST READ 1 0.04% STANDARD - MUST READ 1 TEST 1 0.077 g/210L INDICATE THE NUMBER OF BREATH TO REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER SATISFACTORILY AND WITHIN ESTABLISHED LIN	5 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND TEST 2 0.077 ESTS IN THE FOLLOW .0509 1	the box correspond of	TEST 3 0.077 g/210L TEST 3 0.077 g/210L THE LAST MAINTENANCE REPORT:	being
and must have a spread of .00 used. 0.10% STANDARD - MUST READ 1 0.08% STANDARD - MUST READ 1 0.04% STANDARD - MUST READ 1 TEST 1 0.077 g/210L INDICATE THE NUMBER OF BREATH TO REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER SATISFACTORILY AND WITHIN ESTABLISHED LIN INSPECTING OFFICER SIGNATURE	5 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND TEST 2 0.077 ESTS IN THE FOLLOW .0509 1	the box correspond of	TEST 3 0.077 g/210L	being
and must have a spread of .000 used. 0.10% STANDARD - MUST READ 1 0.08% STANDARD - MUST READ 1 0.04% STANDARD - MUST READ 1 TEST 1 0.077 g/210L INDICATE THE NUMBER OF BREATH TO REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER SATISFACTORILY AND WITHIN ESTABLISHED LIN INSPECTING OFFICER SIGNATURE	5 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND TEST 2 0.077 BSTS IN THE FOLLOW .0509 1 RATION OR MODIFICATION MITS (USE OTHER SIDE IN	D 0.105% INCLUSI D 0.084% INCLUSI D 0.042% INCLUSI G/210L WING RANGES SINC .1014 3 THAT WAS MADE TO RE F NECESSARY). PRINT FULL NAME KAUFMAN, BENJ	TEST 3 0.077 g/210L	being
and must have a spread of .000 used. 0.10% STANDARD - MUST READ 1 0.08% STANDARD - MUST READ 1 0.04% STANDARD - MUST READ 1 TEST 1 0.077 g/210L INDICATE THE NUMBER OF BREATH TO REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER SATISFACTORILY AND WITHIN ESTABLISHED LIN INSPECTING OFFICER SIGNATURE TYPE II PERMIT NUMBER EXPIRATE	5 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND TEST 2 0.077 ESTS IN THE FOLLOW .0509 1	the box correspond of	TEST 3 0.077 g/210L TEST 3 0.077 g/210L TEST 1 0.077 g/210L TEST 1 0.077 g/210L TEST 3 0.077 g/210L TEST 3 0.077 g/210L TEST 3 0.077 g/210L	being
and must have a spread of .000 used. 0.10% STANDARD - MUST READ 10.08% STANDARD - MUST READ 10.04% STANDARD OF BREATH TO REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER SATISFACTORILY AND WITHIN ESTABLISHED LINUSPECTING OFFICER SIGNATURE INSPECTING OFFICER SIGNATURE 1846 TYPE II PERMIT NUMBER EXPIRAT 240140 06/21	5 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.077 ESTS IN THE FOLLOW .0509 1 RATION OR MODIFICATION MITS (USE OTHER SIDE IN	D 0.105% INCLUSI D 0.084% INCLUSI D 0.084% INCLUSI D 0.042% INCLUSI g/210L WING RANGES SINC .1014 3 THAT WAS MADE TO RE F NECESSARY). PRINT FOLL NAME KAUFMAN, BENJ TELEPHONE NUMBER	TEST 3 0.077 g/210L TEST 3 0.077 g/210L TEST 1 0.077 g/210L TEST 1 0.077 g/210L TEST 3 0.077 g/210L TEST 3 0.077 g/210L TEST 3 0.077 g/210L	being
and must have a spread of .000 used. 0.10% STANDARD - MUST READ 10.08% STANDARD - MUST READ 10.04% STANDARD OF BREATH TO REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER SATISFACTORILY AND WITHIN ESTABLISHED LINUSPECTING OFFICER SIGNATURE INSPECTING OFFICER SIGNATURE 240140 06/21 RETURN COMPLETED REPORT TO	5 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.077 ESTS IN THE FOLLOW .0509 1 RATION OR MODIFICATION MITS (USE OTHER SIDE IN	the box correspond of	TEST 3 0.077 g/210L TEST 3 0.077 g/210L TEST 19 4 OVER .19 STORE THE INSTRUMENT TO OPERATE	being
and must have a spread of .000 used. 0.10% STANDARD - MUST READ 10.08% STANDARD - MUST READ 10.04% STANDARD OF BREATH TO REFUSALS 0 004 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER SATISFACTORILY AND WITHIN ESTABLISHED LINUSPECTING OFFICER SIGNATURE INSPECTING OFFICER SIGNATURE 1846 TYPE II PERMIT NUMBER EXPIRAT 240140 06/21	5 or less. Mark BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 0.077 ESTS IN THE FOLLOW .0509 1 RATION OR MODIFICATION MITS (USE OTHER SIDE IN	the box correspond of	TEST 3 0.077 g/210L TEST 3 0.077 g/210L TEST 19 4 OVER .19 STORE THE INSTRUMENT TO OPERATE	being



Airgas USA LLC (LAB) 3500 Bernard Street St. Louis, Mo. 63103 Ph: (314) 533-3100 Fax: (314) 533-7328

Certificate of Analysis

Customer Name Exclusive Supplier Intoximeters, Inc. 2081 Craig Road St. Louis, Mo 63146

Test Date: 13-Mar-2024

Lot # AG407302 Model 108

Exp Date 13-Mar-2026 Cyl. Type 108 **Component** Ethanol

Certified Concentration

0.080 ± 0.002 BrAC (218 ppm)

Nitrogen

Certification Traceable to N.I.S.T. RGM and to CRM Ethanol Standards:

RGM Serial No.	Concentration	RGM Serial No.	Concentration
EB0010581	391.8 ppm	EB0010603	392.5 ppm
EB0010570	259.8 ppm	EB0010559	258.9 ppm
EB0010285	209.0 ppm	EB0010562	104.2 ppm
EB0010561	103.7 ppm	EB0010579	52.94 ppm
EB0010681	52 22 nnm		

CRM Serial No.	Concentration	CRM Serial No.	Concentration
CC727481	799.4 ppm	CC727493	389.8 ppm
CC727496	253.4 ppm	CC727498	150.2 ppm

Analytical Method: NDIR

Digitally signed by Quality Control Reason:Dry gas standard certification of analysis Location:Airgas USA LLC (Lab) Date:03:15.2024 08:01

Approved for Release:

Yusef Woods

ISO 17025:2017 A2LA accredited. Certificate Number 3082.06 ISO 17034:2016 A2LA accredited. Certificate Number 3082.07



22-0785-00 AG407302



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES **BREATH ALCOHOL PROGRAM**



PERMIT TYPE II

BENJAMIN R. KAUFMAN

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):


INTOX EC/IR II

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo.

DATE6/21/2024	Mile Massur
	DIRECTOR OF STATE PUBLIC HEALTH LABORATORY
NUMBER 240140	
EXPIRES 6/21/2026	Daves I. nichelson
	DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES

MO 580-0771 (6-10)

LAB-4 (R6-10)



The named cardholder is authorized to operate an evidential breath alcohol instrument for the determination of the alcoholic content in breath form of expired air in Missouri.

KAUFMAN, BENJAMIN Permit No

Date Issued 6/21/2024

Date Expires 6/21/2026

