

### MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

| INTOX EC/IR II MAINTENANCE   |   |  | REPORT #3                                      |  |  |
|--|---|--|--|--|--|
| Complete this report at the time of the regular month  | hly preventive maint  | enance check (not  | to exceed 35                                   |  |  |
| days). Complete this report whenever the instrument is serviced or repaired and whenever it is placed  |   |  |  |  |  |
| into service. Retain the original and send a copy with   | thin 15 days to the   |  | gram, DHSS.                                    |  |  |
| INTOX EC/IR II SN NAME OF AGENCY   | n.r. nn   | DATE OF INSPECTION   |  |  |  |
| 12696 TOWN AND COUNT   | RY PD   | 09/12/2024   |  |  |  |
| LOCATION OF INSTRUMENT (STREET AND CITY)   |   | TIME OF INSPECTION   |  |  |  |
| 1011 Municipal Ctr. Dr. Town and Country   | 1 1 1 1 1 6 1   | 01:39 CDT  | ~ithin   |  |  |
| CHECKLIST: Place a mark in the box by each item if for   |   |  |  |  |  |
| established limits. (Write in observed values where before using instrument.   | determined). Onmais   | ted Items mast be c  | Offected                                       |  |  |
| X DIAGNOSTIC RECORD  |   |  |  |  |  |
|  | X CO2 CHECK   |  |  |  |  |
| X BLANK CHECK  |   |  |  |  |  |
| X FC 1 TEMP  | X FLOW CHECK  |  |  |  |  |
| X SRC TEMP   | X FCB CHECK   |  |  |  |  |
| X DET TEMP   | X CRC COMP CHE  |  |  |  |  |
| X BT TEMP  | X CRC CAL CHEC  | C  |  |  |  |
| X STD 2 TEMP   | X PRINT TEST  |  |  |  |  |
| X ETH CHECK  |   |  |  |  |  |
| BREATH ANALYZER ACCURACY STANDARDS   |   |  |  |  |  |
| SIMULATOR SOLUTION   | X COMPRESSED E  | THANOL-GAS MIXTUR  | RE   |  |  |
| X STANDARD SUPPLIER INTOXIMETERS, INC  | LOT# AG329702   |  | DATE 10/24/2025                                |  |  |
|  | K (ADDR-TANGETER) TO SERVICE TO CONTROL OF ACCOUNTS   | SIM. NIST EXP D  |  |  |  |
| SIMULATOR TEMP (34°C ±0.2°C) SIM.  | 21/   | SIM. NISI EAF L  | AIB  |  |  |
|  |   |  |  |  |  |
| X CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT)   |   |  |  |  |  |
| A CONTROL OF THE PROPERTY OF T |   | I DITHICH MALONE,  |  |  |  |
| Run three tests using a standard solution.   | All three tests m   | ust be within +5%  | of the standard value                          |  |  |
| Run three tests using a standard solution. A and must have a spread of .005 or less. Mark  | All three tests m   | ust be within +5%  | of the standard value indard solution being    |  |  |
| Run three tests using a standard solution. and must have a spread of .005 or less. Markused.   | All three tests m<br>k the box correspo   | ust be within <u>+</u> 5%<br>onding to the sta   | of the standard value<br>indard solution being |  |  |
| Run three tests using a standard solution. A and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095%  | All three tests m<br>k the box corresponding of the corresponding the corresponding to the corre | ust be within <u>+</u> 5%<br>onding to the sta<br>IVE  | of the standard value<br>indard solution being |  |  |
| Run three tests using a standard solution. A and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% A 0.08% STANDARD - MUST READ BETWEEN 0.076% A  | All three tests m<br>k the box corresponding<br>AND 0.105% INCLUS<br>AND 0.084% INCLUS  | ust be within <u>+</u> 5%<br>onding to the sta<br>IVE<br>IVE   | of the standard value<br>indard solution being |  |  |
| Run three tests using a standard solution. A and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095%  | All three tests m<br>k the box corresponding<br>AND 0.105% INCLUS<br>AND 0.084% INCLUS  | ust be within <u>+</u> 5%<br>onding to the sta<br>IVE<br>IVE   | of the standard value<br>ndard solution being  |  |  |
| Run three tests using a standard solution. and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% 0.08% STANDARD - MUST READ BETWEEN 0.076% 0.04% STANDARD - MUST READ BETWEEN 0.038%  | All three tests m<br>k the box corresponding<br>AND 0.105% INCLUS<br>AND 0.084% INCLUS<br>AND 0.042% INCLUS   | ust be within <u>+</u> 5% onding to the sta  IVE  IVE  IVE   | ndard solution being                           |  |  |
| Run three tests using a standard solution.  and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% 0.08% STANDARD - MUST READ BETWEEN 0.076% 0.04% STANDARD - MUST READ BETWEEN 0.038% TEST 1 0.100 g/210L  TEST 1 0.100 g/210L  TEST 2 0.100  | All three tests m<br>k the box correspond<br>AND 0.105% INCLUS<br>AND 0.084% INCLUS<br>AND 0.042% INCLUS<br>0 g/210L  | ust be within ±5% onding to the state of the | ndard solution being                           |  |  |
| Run three tests using a standard solution. and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% 0.08% STANDARD - MUST READ BETWEEN 0.076% 0.04% STANDARD - MUST READ BETWEEN 0.038%  | All three tests m<br>k the box correspond<br>AND 0.105% INCLUS<br>AND 0.084% INCLUS<br>AND 0.042% INCLUS<br>0 g/210L  | ust be within ±5% onding to the state of the | ndard solution being                           |  |  |
| Run three tests using a standard solution. A and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% A 0.08% STANDARD - MUST READ BETWEEN 0.076% A 0.04% STANDARD - MUST READ BETWEEN 0.038% A TEST 1 0.100 g/210L  TEST 1 0.100 g/210L  TEST 2 0.100 INDICATE THE NUMBER OF BREATH TESTS IN THE FOLE   | All three tests m<br>k the box correspondent<br>AND 0.105% INCLUS<br>AND 0.084% INCLUS<br>AND 0.042% INCLUS<br>0 g/210L<br>LOWING RANGES SING   | ust be within ±5% pnding to the state of the | ndard solution being g/210L ENANCE REPORT:     |  |  |
| Run three tests using a standard solution. A and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% A 0.08% STANDARD - MUST READ BETWEEN 0.076% A 0.04% STANDARD - MUST READ BETWEEN 0.038% A TEST 1 0.100 g/210L TEST 2 0.100 INDICATE THE NUMBER OF BREATH TESTS IN THE FOLEMARD TEST IN T | All three tests m<br>k the box correspondence of the correspondence o | ust be within ±5% pnding to the state of the | og/210L PENANCE REPORT:  OVER .19 0            |  |  |
| Run three tests using a standard solution.  and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% A 0.08% STANDARD - MUST READ BETWEEN 0.076% A 0.04% STANDARD - MUST READ BETWEEN 0.038% A TEST 1 0.100 g/210L  TEST 1 0.100 g/210L  TEST 2 0.100  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLEMARD A DESCRIBE ANY ALTERATION OR MODIFICATE   | All three tests m k the box correspond AND 0.105% INCLUS AND 0.084% INCLUS AND 0.042% INCLUS 0 g/210L LOWING RANGES SING .1014 1 ION THAT WAS MADE TO R   | ust be within ±5% pnding to the state of the | og/210L PENANCE REPORT:  OVER .19 0            |  |  |
| Run three tests using a standard solution. A and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% A 0.08% STANDARD - MUST READ BETWEEN 0.076% A 0.04% STANDARD - MUST READ BETWEEN 0.038% A TEST 1 0.100 g/210L TEST 2 0.100 INDICATE THE NUMBER OF BREATH TESTS IN THE FOLEMARD TEST IN T | All three tests m k the box correspond AND 0.105% INCLUS AND 0.084% INCLUS AND 0.042% INCLUS 0 g/210L LOWING RANGES SING .1014 1 ION THAT WAS MADE TO R   | ust be within ±5% pnding to the state of the | og/210L PENANCE REPORT:  OVER .19 0            |  |  |
| Run three tests using a standard solution.  and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% A 0.08% STANDARD - MUST READ BETWEEN 0.076% A 0.04% STANDARD - MUST READ BETWEEN 0.038% A TEST 1 0.100 g/210L  TEST 1 0.100 g/210L  TEST 2 0.100  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLEMARD A DESCRIBE ANY ALTERATION OR MODIFICATE   | All three tests m k the box correspond AND 0.105% INCLUS AND 0.084% INCLUS AND 0.042% INCLUS 0 g/210L LOWING RANGES SING .1014 1 ION THAT WAS MADE TO R   | ust be within ±5% pnding to the state of the | og/210L PENANCE REPORT:  OVER .19 0            |  |  |
| Run three tests using a standard solution.  and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% A 0.08% STANDARD - MUST READ BETWEEN 0.076% A 0.04% STANDARD - MUST READ BETWEEN 0.038% A TEST 1 0.100 g/210L  TEST 1 0.100 g/210L  TEST 2 0.100  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLEMARD A DESCRIBE ANY ALTERATION OR MODIFICATE   | All three tests m k the box correspond AND 0.105% INCLUS AND 0.084% INCLUS AND 0.042% INCLUS 0 g/210L LOWING RANGES SING .1014 1 ION THAT WAS MADE TO R   | ust be within ±5% pnding to the state of the | og/210L PENANCE REPORT:  OVER .19 0            |  |  |
| Run three tests using a standard solution.  and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% A 0.08% STANDARD - MUST READ BETWEEN 0.076% A 0.04% STANDARD - MUST READ BETWEEN 0.038% A TEST 1 0.100 g/210L  TEST 1 0.100 g/210L  TEST 2 0.100  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLEMARD A DESCRIBE ANY ALTERATION OR MODIFICATE   | All three tests m k the box correspond AND 0.105% INCLUS AND 0.084% INCLUS AND 0.042% INCLUS 0 g/210L LOWING RANGES SING .1014 1 ION THAT WAS MADE TO R   | ust be within ±5% pnding to the state of the | og/210L PENANCE REPORT:  OVER .19 0            |  |  |
| Run three tests using a standard solution.  and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% A 0.08% STANDARD - MUST READ BETWEEN 0.076% A 0.04% STANDARD - MUST READ BETWEEN 0.038% A TEST 1 0.100 g/210L  TEST 1 0.100 g/210L  TEST 2 0.100  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLEMARD A DESCRIBE ANY ALTERATION OR MODIFICATE   | All three tests m k the box correspond AND 0.105% INCLUS AND 0.084% INCLUS AND 0.042% INCLUS 0 g/210L LOWING RANGES SING .1014 1 ION THAT WAS MADE TO R   | ust be within ±5% pnding to the state of the | og/210L PENANCE REPORT:  OVER .19 0            |  |  |
| Run three tests using a standard solution.  and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% A 0.08% STANDARD - MUST READ BETWEEN 0.076% A 0.04% STANDARD - MUST READ BETWEEN 0.038% A TEST 1 0.100 g/210L  TEST 1 0.100 g/210L  TEST 2 0.100  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLEMARD A DESCRIBE ANY ALTERATION OR MODIFICATE   | All three tests moved the box corresponds to the box corresponds and 0.105% INCLUS and 0.042% INCLUS 0 g/210L  LOWING RANGES SING 1.1014 1  ION THAT WAS MADE TO REE IF NECESSARY).   | ust be within ±5% pnding to the state of the | og/210L PENANCE REPORT:  OVER .19 0            |  |  |
| Run three tests using a standard solution.  and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% A 0.08% STANDARD - MUST READ BETWEEN 0.076% A 0.04% STANDARD - MUST READ BETWEEN 0.038% A TEST 1 0.100 g/210L  TEST 1 0.100 g/210L  TEST 2 0.100  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLEMARY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATE SATISFACTORILY AND WITHIN ESTABLISHED LIMITS (USE OTHER SIDE  | All three tests moved the box corresponds to the box corresponds to the box corresponds and 0.105% inclus and 0.042% inclus of g/210L  LOWING RANGES SING 1.1014 1  ION THAT WAS MADE TO REE IF NECESSARY).   | ust be within ±5% pnding to the state of the | og/210L PENANCE REPORT:  OVER .19 0            |  |  |
| Run three tests using a standard solution.  and must have a spread of .005 or less. Markused.     0.10% STANDARD - MUST READ BETWEEN 0.095%  | All three tests moved the box corresponds to the box corresponds to the box corresponds and 0.105% inclus and 0.042% inclus o g/210L  LOWING RANGES SING 1014 1  ION THAT WAS MADE TO REE IF NECESSARY).  | ust be within ±5% pnding to the state of the | og/210L PENANCE REPORT:  OVER .19 0            |  |  |
| Run three tests using a standard solution.  and must have a spread of .005 or less. Markused.  | All three tests my k the box corresponds to the corresponding to the cor    | Ist be within ±5% pnding to the state of the | og/210L PENANCE REPORT:  OVER .19 0            |  |  |
| Run three tests using a standard solution.  and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% A 0.08% STANDARD - MUST READ BETWEEN 0.076% A 0.04% STANDARD - MUST READ BETWEEN 0.038% A TEST 1 0.100 g/210L  TEST 1 0.100 g/210L  TEST 2 0.100  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLE  REFUSALS 2 004 0 .0509 1  LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATE SATISFACTORILY AND WITHIN ESTABLISHED LIMITS (USE OTHER SIDE SIGNATURE)  TYPE II PERMIT NUMBER  TYPE II PERMIT NUMBER  EXPIRATION DATE  10/23/2025  | All three tests moved the box corresponds to the box corresponds to the box corresponds and 0.105% inclus and 0.042% inclus o g/210L  LOWING RANGES SING 1014 1  ION THAT WAS MADE TO REE IF NECESSARY).  | Ist be within ±5% pnding to the state of the | og/210L PENANCE REPORT:  OVER .19 0            |  |  |
| Run three tests using a standard solution.  and must have a spread of .005 or less. Markused.     0.10% STANDARD - MUST READ BETWEEN 0.095%  | All three tests my k the box corresponds to the corresponding to the cor    | ist be within ±5% pnding to the state ive ive ive ive ive its 3 \$\sigma 0.100\$  TEST 3 \$\sigma 0.100\$  TEST 19 2  ESTORE THE INSTRUMENT  | og/210L PENANCE REPORT:  OVER .19 0 TO OPERATE |  |  |
| Run three tests using a standard solution.  and must have a spread of .005 or less. Markused.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% A 0.08% STANDARD - MUST READ BETWEEN 0.076% A 0.04% STANDARD - MUST READ BETWEEN 0.038% A TEST 1 0.100 g/210L  TEST 1 0.100 g/210L  TEST 2 0.100  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLE  REFUSALS 2 004 0 .0509 1  LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATE SATISFACTORILY AND WITHIN ESTABLISHED LIMITS (USE OTHER SIDE SIGNATURE)  TYPE II PERMIT NUMBER  TYPE II PERMIT NUMBER  EXPIRATION DATE  10/23/2025  | All three tests my k the box corresponds to the corresponding to the cor    | ist be within ±5% pnding to the state ive ive ive ive ive its 3 \$\sigma 0.100\$  TEST 3 \$\sigma 0.100\$  TEST 19 2  ESTORE THE INSTRUMENT  | og/210L PENANCE REPORT:  OVER .19 0 TO OPERATE |  |  |



Airgas USA LLC (LAB) 3500 Bernard Street St. Louis, Mo. 63103 Ph: (314) 533-3100 Fax: (314) 533-7328

# **Certificate of Analysis**

Customer Name
Exclusive Supplier
Intoximeters, Inc.
2081 Craig Road
St. Louis, Mo 63146

Test Date: 25-Oct-2023

390.0 ppm

150.0 ppm

### Lot # AG329702 Model 108

Exp Date 24-Oct-2025 Cyl. Type 108 Component

**Certified Concentration** 

Ethanol

Nitrogen

0.100 ± 2% BrAC (272 ppm)

### Certification Traceable to N.I.S.T. RGM and to CRM Ethanol Standards:

800.0 ppm

253.0 ppm

| RGM Serial No.        | Concentration | RGM Serial No. | Concentration |
|-----------------------|---------------|----------------|---------------|
| EB0010581             | 391.8 ppm     | EB0010603      | 392.5 ppm     |
| EB0010570             | 259.8 ppm     | EB0010559      | 258.9 ppm     |
| EB0010285             | 209.0 ppm     | EB0010562      | 104.2 ppm     |
| EB0010561             | 103.7 ppm     | EB0010579      | 52.94 ppm     |
| EB0010681             | 52.22 ppm     |                |               |
|                       |               | 961            |               |
| <b>CRM Serial No.</b> | Concentration | CRM Serial No. | Concentration |

Analytical Method: NDIR

CC727481

CC727496

Digitally signed by:Quality Control Reason:Dry gas standard certification of analysis Location:Airgas USA LLC (Lab) Date:10.26.2023 18:41

Approved for Release:

Yusef Woods

CC727493

CC727498

ISO 17025:2017 A2LA accredited. Certificate Number 3082.06 ISO 17034:2016 A2LA accredited. Certificate Number 3082.07



MO 580-0771 (6-10)

### STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES **BREATH ALCOHOL PROGRAM** 



# PERMIT TYPE II

# STEVEN M. DOLL

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs; and operate the following breath analyzer(s):

## INTOX EC/IR II

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo. MA

| DATE10/23/2023     | Mike Massim                                |
|--------------------|--|
| DAIE               | DIRECTOR OF STATE PUBLIC HEALTH LABORATORY |
| NUMBER 230227      | Danla J. Nichelson                         |
| EXPIRES 10/23/2025 | toma s. I percesso                         |

DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES

LAB-4 (R6-10)



### STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES BREATH ALCOHOL PROGRAM

### INSTRUMENT OPERATOR CARD

The named cardholder is authorized to operate an evidential breath alcohol instrument for the determination of the alcoholic content in breath form of expired air in Missouri.

DOLL, STEVEN Permit No 230227

Date Issued 10/23/2023

Date Expires 10/23/2025

