RECEIVED

MISSOURI DEPARTMENT OF HEALTH AND SENI By Tracy Crews at 8:26 am, Aug 14, 2024

MISSOURI DEPARTMENT OF HEALTH AND STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

INTOX EC/IR II MAINTENANCE REPORT

REPORT #3

INTOX EC/IR II MAINTENANCE REPORT we maintenance check (not to exceed 35			
Complete this report at the time of the regular monthly preventive maintenance check (not to exceed 35 days). Complete this report whenever the instrument is serviced or repaired and whenever it is placed			
days). Complete this report whenever the instrument is serviced of repaired and whenever it is placed into service. Retain the original and send a copy within 15 days to the Breath Alcohol Program, DHSS.			
	and send a copy within 15 days to th	DATE OF INSPECTION	
INTOX EC/IR II SN	Olivette Police Dept.	08/13/2024	
12708		TIME OF INSPECTION	
LOCATION OF INSTRUMENT (STREET AND CITY)		10:42 CDT	
1140 Dielman Rd Olivette			
CHECKLIST: Place a mark in the box by each item if found to be satisfactory or is operating within established limits. (Write in observed values where determined). Unmarked items must be corrected			
before using instrument.			
X DIAGNOSTIC RECORD			
	X CO2 CHECK		
A DELINITION			
X 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2			
X SRC TEMP X FCB CHECK			
X DET TEMP X CRC COMP CHECK			
X BT TEMP X CRC CAL CHECK			
X STD 2 TEMP	X PRINT TEST		
X ETH CHECK			
BREATH ANALYZER ACCURACY STANDARDS			
SIMULATOR SOLUTION X COMPRESSED ETHANOL-GAS MIXTURE			
	IMETERS LOT# AG305902		
SIMULATOR TEMP (34°C ±0.2°C)		SIM. NIST EXP DATE	
SIMULATOR TEMP (34°C +0.2°C)			
The second secon	X CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT)		
X CALIBRATION CHECK - (ONLY ON	E STANDARD IS TO BE USED PER MAI	NTENANCE REPORT)	
Dun three tests using a stand	dard solution. All three tests	must be within +5% of the standard value	
Run three tests using a stand and must have a spread of .00	dard solution. All three tests	NTENANCE REPORT) must be within $\pm 5\%$ of the standard value ponding to the standard solution being	
Run three tests using a stand and must have a spread of .00 used.	dard solution. All three tests 05 or less. Mark the box corres	must be within $\pm 5\%$ of the standard value ponding to the standard solution being	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ	dard solution. All three tests 05 or less. Mark the box corres BETWEEN 0.095% AND 0.105% INCLU	must be within ±5% of the standard value ponding to the standard solution being SIVE	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ	dard solution. All three tests 05 or less. Mark the box corres BETWEEN 0.095% AND 0.105% INCLUBETWEEN 0.076% AND 0.084% INCLU	must be within ±5% of the standard value ponding to the standard solution being SIVE	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ	dard solution. All three tests 05 or less. Mark the box corres BETWEEN 0.095% AND 0.105% INCLU	must be within ±5% of the standard value ponding to the standard solution being SIVE	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ	dard solution. All three tests of or less. Mark the box corres BETWEEN 0.095% AND 0.105% INCLUBETWEEN 0.076% AND 0.084% INCLUBETWEEN 0.038% AND 0.042% INCLU	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L	dard solution. All three tests of or less. Mark the box correst BETWEEN 0.095% AND 0.105% INCLUBETWEEN 0.076% AND 0.084% INCLUBETWEEN 0.038% AND 0.042% INCLUBETS 2 0.100 g/210L	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE TEST 3 0.099 g/210L	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L	dard solution. All three tests of or less. Mark the box correst BETWEEN 0.095% AND 0.105% INCLUBETWEEN 0.076% AND 0.084% INCLUBETWEEN 0.038% AND 0.042% INCLUBETS 2 0.100 g/210L	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH 7	dard solution. All three tests of or less. Mark the box correst BETWEEN 0.095% AND 0.105% INCLUBETWEEN 0.076% AND 0.084% INCLUBETWEEN 0.038% AND 0.042% INCLUBETS IN THE FOLLOWING RANGES SI	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE TEST 3 0.099 g/210L NCE THE LAST MAINTENANCE REPORT:	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST 1 0.100 g/210L	dard solution. All three tests of or less. Mark the box correst BETWEEN 0.095% AND 0.105% INCLUBETWEEN 0.076% AND 0.084% INCLUBETWEEN 0.038% AND 0.042% INCLUBETS IN THE FOLLOWING RANGES SI	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE TEST 3 0.099 g/210L NCE THE LAST MAINTENANCE REPORT: .1519 0 OVER .19 0	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEFUSALS 0 004 1	dard solution. All three tests of or less. Mark the box corres BETWEEN 0.095% AND 0.105% INCLU BETWEEN 0.076% AND 0.084% INCLU BETWEEN 0.038% AND 0.042% INCLU TEST 2 0.100 g/210L TESTS IN THE FOLLOWING RANGES SI .0509 0 .1014 0 ERATION OR MODIFICATION THAT WAS MADE TO	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE TEST 3 0.099 g/210L NCE THE LAST MAINTENANCE REPORT: .1519 0 OVER .19 0	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST 1 0.100 g/210L	dard solution. All three tests of or less. Mark the box corres BETWEEN 0.095% AND 0.105% INCLU BETWEEN 0.076% AND 0.084% INCLU BETWEEN 0.038% AND 0.042% INCLU TEST 2 0.100 g/210L TESTS IN THE FOLLOWING RANGES SI .0509 0 .1014 0 ERATION OR MODIFICATION THAT WAS MADE TO	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE TEST 3 0.099 g/210L NCE THE LAST MAINTENANCE REPORT: .1519 0 OVER .19 0	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST 1 0.100 g/210L REFUSALS 0 004 1 LIST ANY NEW FARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED L	dard solution. All three tests of or less. Mark the box corres BETWEEN 0.095% AND 0.105% INCLU BETWEEN 0.076% AND 0.084% INCLU BETWEEN 0.038% AND 0.042% INCLU TEST 2 0.100 g/210L TESTS IN THE FOLLOWING RANGES SI .0509 0 .1014 0 ERATION OR MODIFICATION THAT WAS MADE TO	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE TEST 3 0.099 g/210L NCE THE LAST MAINTENANCE REPORT: .1519 0 OVER .19 0	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST 1 0.100 g/210L	dard solution. All three tests of or less. Mark the box corres BETWEEN 0.095% AND 0.105% INCLU BETWEEN 0.076% AND 0.084% INCLU BETWEEN 0.038% AND 0.042% INCLU TEST 2 0.100 g/210L TESTS IN THE FOLLOWING RANGES SI .0509 0 .1014 0 ERATION OR MODIFICATION THAT WAS MADE TO	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE TEST 3 0.099 g/210L NCE THE LAST MAINTENANCE REPORT: .1519 0 OVER .19 0	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST 1 0.100 g/210L REFUSALS 0 004 1 LIST ANY NEW FARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED L	dard solution. All three tests of or less. Mark the box corres BETWEEN 0.095% AND 0.105% INCLU BETWEEN 0.076% AND 0.084% INCLU BETWEEN 0.038% AND 0.042% INCLU TEST 2 0.100 g/210L TESTS IN THE FOLLOWING RANGES SI .0509 0 .1014 0 ERATION OR MODIFICATION THAT WAS MADE TO	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE TEST 3 0.099 g/210L NCE THE LAST MAINTENANCE REPORT: .1519 0 OVER .19 0	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH THE STANDARD STAND	dard solution. All three tests of or less. Mark the box corres BETWEEN 0.095% AND 0.105% INCLU BETWEEN 0.076% AND 0.084% INCLU BETWEEN 0.038% AND 0.042% INCLU TEST 2 0.100 g/210L TESTS IN THE FOLLOWING RANGES SI .0509 0 .1014 0 ERATION OR MODIFICATION THAT WAS MADE TO	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE TEST 3 0.099 g/210L NCE THE LAST MAINTENANCE REPORT: .1519 0 OVER .19 0	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST 1 0.100 g/210L REFUSALS 0 004 1 LIST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LAUgust Maintenance	dard solution. All three tests of or less. Mark the box correst BETWEEN 0.095% AND 0.105% INCLUBETWEEN 0.076% AND 0.084% INCLUBETWEEN 0.038% AND 0.042% INCLUBETS IN THE FOLLOWING RANGES SINGLOUSE OF THE STOLE OF T	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE TEST 3 0.099 g/210L NCE THE LAST MAINTENANCE REPORT: .1519 0 OVER .19 0	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH THE STANDARD STAND	dard solution. All three tests of or less. Mark the box corres BETWEEN 0.095% AND 0.105% INCLU BETWEEN 0.076% AND 0.084% INCLU BETWEEN 0.038% AND 0.042% INCLU TEST 2 0.100 g/210L TESTS IN THE FOLLOWING RANGES SI .0509 0 .1014 0 ERATION OR MODIFICATION THAT WAS MADE TO	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE TEST 3 0.099 g/210L NCE THE LAST MAINTENANCE REPORT: .1519 0 OVER .19 0 RESTORE THE INSTRUMENT TO OPERATE	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LAUgust Maintenance INSPECTING OFFICER SIGNATURE	dard solution. All three tests of less. Mark the box correst per less per less. Mark the box correst per less per les p	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE TEST 3 0.099 g/210L NCE THE LAST MAINTENANCE REPORT: .1519 0 OVER .19 0 RESTORE THE INSTRUMENT TO OPERATE	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH THE SATISFACTORILY AND WITHIN ESTABLISHED LAUGUST MAINTENANCE INSPECTING OFFICER SIGNATURE TYPE II PERMIT NUMBER EXPIRE	dard solution. All three tests of or less. Mark the box correst BETWEEN 0.095% AND 0.105% INCLUBETWEEN 0.076% AND 0.084% INCLUBETWEEN 0.038% AND 0.042% INCLUBETS IN THE FOLLOWING RANGES SIONSTAND OF THE STREET OF	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE TEST 3 0.099 g/210L NCE THE LAST MAINTENANCE REPORT: .1519 0 OVER .19 0 RESTORE THE INSTRUMENT TO OPERATE	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LAUGUST Maintenance INSPECTING OFFICER SIGNATURE TYPE II PERMIT NUMBER EXPIR 240011 01/11	dard solution. All three tests of or less. Mark the box correst between 0.095% AND 0.105% INCLUBETWEEN 0.076% AND 0.084% INCLUBETWEEN 0.038% AND 0.042% INCLUBETS IN THE FOLLOWING RANGES SINGS IN THE FOLLOWING RANGES SINGS (USE OTHER SIDE IF NECESSARY). PRINT FULL NAME MCBRIDE, DAI TELEPHONE NUMBER 12/2026 (314) 645-30	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE TEST 3 0.099 g/210L NCE THE LAST MAINTENANCE REPORT: .1519 0 OVER .19 0 RESTORE THE INSTRUMENT TO OPERATE	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LAUGUST Maintenance INSPECTING OFFICER SIGNATURE TYPE IT FERMIT NUMBER EXPIRIT 240011 01/11 RETURN COMPLETED REPORT T	dard solution. All three tests of or less. Mark the box correst between 0.095% AND 0.105% INCLUBETWEEN 0.076% AND 0.084% INCLUBETWEEN 0.038% AND 0.042% INCLUBETS IN THE FOLLOWING RANGES SINGS IN THE SIDE IF NECESSARY).	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE TEST 3 0.099 g/210L NCE THE LAST MAINTENANCE REPORT: .1519 0 OVER .19 0 RESTORE THE INSTRUMENT TO OPERATE	
Run three tests using a stand and must have a spread of .00 used. X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 0.100 g/210L INDICATE THE NUMBER OF BREATH TEST ANY NEW PARTS AND DESCRIBE ANY ALT SATISFACTORILY AND WITHIN ESTABLISHED LAUGUST Maintenance INSPECTING OFFICER SIGNATURE TYPE IT FERMIT NUMBER EXPIRIT 240011 01/11 RETURN COMPLETED REPORT T	dard solution. All three tests of or less. Mark the box correst between 0.095% AND 0.105% INCLUBETWEEN 0.076% AND 0.084% INCLUBETWEEN 0.038% AND 0.042% INCLUBETS IN THE FOLLOWING RANGES SINGS IN THE FOLLOWING RANGES SINGS (USE OTHER SIDE IF NECESSARY). PRINT FULL NAME MCBRIDE, DAI TELEPHONE NUMBER 12/2026 (314) 645-30	must be within ±5% of the standard value ponding to the standard solution being SIVE SIVE TEST 3 0.099 g/210L NCE THE LAST MAINTENANCE REPORT: .1519 0 OVER .19 0 RESTORE THE INSTRUMENT TO OPERATE	



Airgas USA LLC (LAB) 3500 Bernard Street St Louis, Mo. 63103 Ph: (314) 633-3100 Fax: (314) 533-7328

Certificate of Analysis

Customer Name Exclusive Supplier Intoximeters, Inc. 2081 Cralg Road St. Louis, Mo 63146

Test Date: 28-Feb-2023

Lot # AG305902 Model 108

Exp Date 28-Feb-2025 Cyl. Type 108

Component Ethanol

Nitrogen

Certified Concentration 0.100 ± 2% BrAC (272 ppm)

Certification Traceable to N.I.S.T. RGM and to CRM Ethanol Standards:

RGM Serial No. Concentration EB0010581 EB0010570 EB0010285 EB0010561 EB0010681

391.8 ppm 259.8 ppm 209.0 ppm 103.7 ppm 52.22 ppm

EB0010603 EB0010559 EB0010562 EB0010579

RGM Serial No.

Concentration 392.5 ppm 258.9 ppm 104.2 ppm 52.94 ppm

CRM Serial No. CC727481 CC727496

Concentration 800.0 ppm 253.0 ppm

CRM Serial No. CC727493 CC727498

Concentration 390.0 ppm 150.0 ppm

Analytical Method: NDIR

Olgitally signed by:Quality Control Reason:Dry gas standard certification of analysis Location:Argas USA (L.O (Lab) Date:03.01.2023 1728

Approved for Release:

ISO 17025;2017 A2LA accredited. Certificate Number 3082.06 ISO 17034:2016 A2LA accredited. Certificate Number 3082.07



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES
BREATH ALGOHOL PROGRAM



PERMIT TYPE II

DANIEL McBRIDE

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and recand operate the following breath analyzer(s):

MØ 580-0771 (6-10)

EXPIRES 1/12/2026

DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES

LAB-4 (B



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES BREATH ALCOHOL PROGRAM

INSTRUMENT OPERATOR CARD

The named cardholder is authorized to operate on evidential breath sloohol Instrument for the determination of the elcoholic content in breath form of expired all In Missouri.

Operator McBRIDE, DANIEL

Permit No 240011

Date Issued 1/12/2024 Date Expires 1/12/2026

