

MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

INTOX EC/IR II MAI	NTENANCE R	EPORT			REPORT #3
Complete this report at the time of the					
days). Complete this report whenever the					
into service. Retain the original and send a copy within 15 days to the Breath Alcohol Program,				ogram, DHSS.	
INTOX EC/IR II SN NAME OF AGENCY		DATE OF INSPECTION			
12841 GREENE COUNTY SO		10/04/2024			
LOCATION OF INSTRUMENT (STREET AND CITY)			TIME OF INSPECTION		
5100 W. DIVISION ST SPRINGFIELD			08:43 CDT		
CHECKLIST: Place a mark in the box by ea					
established limits. (Write in observed vote before using instrument.	alues where det	ermined). Unmari	tea items must be t	corrected	
X DIAGNOSTIC RECORD				400	
X BLANK CHECK	a	ХСО2 СНЕСК			
X FC 1 TEMP		X FLOW CHECK			
		X FCB CHECK		9703 20	
X DET TEMP	X DET TEMP X CRC		RC COMP CHECK		
X BT TEMP	*	X CRC CAL CHEC	X CRC CAL CHECK		
X STD 2 TEMP		X PRINT TEST	\$ \$0.		
X ETH CHECK		90 20%		2000 % 50 6	
BREATH ANALYZER ACCURACY STANDARDS		· · · · · · · · · · · · · · · · · · ·			
SIMULATOR SOLUTION		COMPRESSED E	THANOL-GAS MIXTU	त्रप्र	
X STANDARD SUPPLIER INTOXIMETER	DC 1	LOT# AG331103	EXP. DATE 11/07/2025		125
Invest	- C	4010900 TO 100 TO 1	00/17/2000/1909/10/07 1		
SIMULATOR TEMP (34°C ±0.2°C)	SIM. SI	N	SIM. NIST EXP	DATE	
				2000	
X CALIBRATION CHECK - (ONLY ONE STAN	NDARD IS TO B	E USED PER MAIN	TENANCE REPORT)		
				% of the standa	ard value
X CALIBRATION CHECK - (ONLY ONE STAN Run three tests using a standard s and must have a spread of .005 or	solution. Al	l three tests m	ust be within ±5		
Run three tests using a standard s	solution. Al	l three tests m	ust be within ±5		
Run three tests using a standard s and must have a spread of .005 or	solution. Al. less. Mark (l three tests much box corresponding	ust be within ± 5 onding to the st		
Run three tests using a standard s and must have a spread of .005 or used.	solution. Al. less. Mark (EEN 0.095% AN	three tests muche box corresponded on the correspondence of the co	ust be within ±5 onding to the sta		
Run three tests using a standard s and must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWE	solution. All less. Mark t EEN 0.095% ANI EEN 0.076% ANI	three tests much box corresponded to 0.105% INCLUS 0.084% INCLUS	ust be within <u>+</u> 5 onding to the sta IVE IVE		
Run three tests using a standard sand must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWEE 0.08% STANDARD - MUST READ BETWEE 0.04% STANDARD - MUST READ BETWEE DESCRIPTION OF THE PROPERTY	solution. All less. Mark t EEN 0.095% ANI EEN 0.076% ANI	three tests muche box corresponded on the low corresponded on the lower state of the lowe	ust be within ±5 onding to the st IVE IVE IVE	andard solution	
Run three tests using a standard sand must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWEE 0.08% STANDARD - MUST READ BETWEE 0.04% STANDARD - MUST READ BETWEE DESCRIPTION OF THE PROPERTY	solution. All less. Mark t EEN 0.095% ANI EEN 0.076% ANI	three tests muche box corresponded on the low corresponded on the lower state of the lowe	ust be within <u>+</u> 5 onding to the sta IVE IVE	andard solution	
Run three tests using a standard sand must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWEE 0.08% STANDARD - MUST READ BETWEE 0.04% STANDARD - MUST READ BETWEE DESCRIPTION OF THE PROPERTY	solution. All less. Mark of the mark of th	three tests muche box corresponded on the low corresponded on the lower state of the lowe	ust be within ±5 onding to the state of the	andard solution	n being
Run three tests using a standard s and must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWEE 0.08% STANDARD - MUST READ BETWEE 0.04% STANDARD - MUST READ BETWEE TEST 1 0.101 g/210L TEST	solution. All less. Mark of the mark of th	three tests muche box corresponded on the low corresponded on the lower state of the lowe	ust be within ±5 onding to the state of the	andard solution	n being
Run three tests using a standard sand must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWEE 0.08% STANDARD - MUST READ BETWEE 0.04% STANDARD - MUST READ BETWEE TEST 1 0.101 g/210L TEST 1 10.101 g/210L TEST 1 0.101 g/210L TEST 1	solution. All less. Mark the sen 0.095% AND SEEN 0.038% AND The second of the second o	three tests muche box correspond 0.105% INCLUS 0.084% INCLUS 0.042% INCL	ust be within ±5 onding to the state of the	andard solution 1 g/210L TENANCE REPORT:	n being
Run three tests using a standard sand must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWEE 0.08% STANDARD - MUST READ BETWEE 0.04% STANDARD - MUST READ BETWEE TIME THE NUMBER OF BREATH TESTS REFUSALS 0 004 5 .05 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION	solution. All less. Mark the sen 0.095% AND EEN 0.076% AND The sen 0.101 of the sen 0.001 o	three tests muche box corresponds 0.105% INCLUS 0.084% INCLUS 0.042% INC	ust be within ±5 onding to the state of the	andard solution 1 g/210L TENANCE REPORT:	n being
Run three tests using a standard sand must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWEE 0.08% STANDARD - MUST READ BETWEE 0.04% STANDARD - MUST READ BETWEE TEST 1 0.101 g/210L TEST 1 10.101 g/210L TEST 1 0.101 g/210L TEST 1	solution. All less. Mark the sen 0.095% AND EEN 0.076% AND The sen 0.101 of the sen 0.001 o	three tests muche box corresponds 0.105% INCLUS 0.084% INCLUS 0.042% INC	ust be within ±5 onding to the state of the	andard solution 1 g/210L TENANCE REPORT:	n being
Run three tests using a standard sand must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWEE 0.08% STANDARD - MUST READ BETWEE 0.04% STANDARD - MUST READ BETWEE TIME THE NUMBER OF BREATH TESTS REFUSALS 0 004 5 .05 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION	solution. All less. Mark the sen 0.095% AND EEN 0.076% AND The sen 0.101 of the sen 0.001 o	three tests muche box corresponds 0.105% INCLUS 0.084% INCLUS 0.042% INC	ust be within ±5 onding to the state of the	andard solution 1 g/210L TENANCE REPORT:	n being
Run three tests using a standard sand must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWEE 0.08% STANDARD - MUST READ BETWEE 0.04% STANDARD - MUST READ BETWEE TIME THE NUMBER OF BREATH TESTS REFUSALS 0 004 5 .05 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION	solution. All less. Mark the sen 0.095% AND EEN 0.076% AND The sen 0.101 of the sen 0.001 o	three tests muche box corresponds 0.105% INCLUS 0.084% INCLUS 0.042% INC	ust be within ±5 onding to the state of the	andard solution 1 g/210L TENANCE REPORT:	n being
Run three tests using a standard sand must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWEE 0.08% STANDARD - MUST READ BETWEE 0.04% STANDARD - MUST READ BETWEE TIME THE NUMBER OF BREATH TESTS REFUSALS 0 004 5 .05 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION	solution. All less. Mark the sen 0.095% AND EEN 0.076% AND The sen 0.101 of the sen 0.001 o	three tests muche box corresponds 0.105% INCLUS 0.084% INCLUS 0.042% INC	ust be within ±5 onding to the state of the	andard solution 1 g/210L TENANCE REPORT:	n being
Run three tests using a standard sand must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWEE 0.08% STANDARD - MUST READ BETWEE 0.04% STANDARD - MUST READ BETWEE TIME THE NUMBER OF BREATH TESTS REFUSALS 0 004 5 .05 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION	solution. All less. Mark the sen 0.095% AND EEN 0.076% AND The sen 0.101 of the sen 0.001 o	three tests muche box corresponds 0.105% INCLUS 0.084% INCLUS 0.042% INC	ust be within ±5 onding to the state of the	andard solution 1 g/210L TENANCE REPORT:	n being
Run three tests using a standard sand must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWEE 0.08% STANDARD - MUST READ BETWEE 0.04% STANDARD - MUST READ BETWEE TIME THE NUMBER OF BREATH TESTS REFUSALS 0 004 5 .05 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION	solution. All less. Mark the sen 0.095% AND EEN 0.076% AND The sen 0.101 of the sen 0.001 o	three tests muche box corresponds 0.105% INCLUS 0.084% INCLUS 0.042% INC	ust be within ±5 onding to the state of the	andard solution 1 g/210L TENANCE REPORT:	n being
Run three tests using a standard and must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWING O.08% STANDARD - MUST READ BETWING O.04% STANDARD OF BREATH TESTS REFUSALS 0 004 5 .05 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION SATISFACTORILY AND WITHIN ESTABLISHED LIMITS OF ORDER OF THE ORDER OF T	solution. All less. Mark the sen 0.095% AND EEN 0.076% AND The sen 0.101 of the sen 0.001 o	three tests muche box corresponds 0.105% INCLUS 0.084% INCLUS 0.042% INC	ust be within ±5 onding to the state of the	andard solution 1 g/210L TENANCE REPORT:	n being
Run three tests using a standard sand must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWING O.08% STANDARD - MUST READ BETWING O.04% STANDARD - MUST READ BETWING TEST 1 0.101 g/210L TEST TIMBLE THE NUMBER OF BREATH TESTS REFUSALS 0 004 5 .05 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION SATISFACTORILY AND WITHIN ESTABLISHED LIMITS OF TIMBLE	solution. All less. Mark to le	three tests muche box corresponds of the local corresponding to the local c	ust be within ±5 onding to the state of the	andard solution 1 g/210L TENANCE REPORT:	n being
Run three tests using a standard and must have a spread of .005 or used. 0.10% STANDARD - MUST READ BETWING O.04% STANDARD - MUST READ BETWING O.04% STANDARD - MUST READ BETWING TEST 1 0.101 g/210L TEST 1 0.101 g/210L TEST INDICATE THE NUMBER OF BREATH TESTS REFUSALS	solution. All less. Mark to le	three tests muche box corresponds of the local	ust be within ±5 onding to the state of the	andard solution 1 g/210L TENANCE REPORT:	n being
Run three tests using a standard sand must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWING O.08% STANDARD - MUST READ BETWING O.04% STANDARD - MUST READ BETWING TEST 1 0.101 g/210L TEST TIMBLE THE NUMBER OF BREATH TESTS REFUSALS 0 004 5 .05 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION SATISFACTORILY AND WITHIN ESTABLISHED LIMITS OF TIMBLE	solution. All less. Mark to le	three tests muche box corresponds of the local corresponding to the local c	ust be within ±5 onding to the state of the	andard solution 1 g/210L TENANCE REPORT:	n being
Run three tests using a standard and must have a spread of .005 or used. 0.10% STANDARD - MUST READ BETWING O.04% STANDARD - MUST READ BETWING O.04% STANDARD - MUST READ BETWING TEST 1 0.101 g/210L TEST 1 0.101 g/210L TEST INDICATE THE NUMBER OF BREATH TESTS REFUSALS	solution. All less. Mark to le	three tests muche box corresponds of the local	ust be within ±5 onding to the state of the	andard solution 1 g/210L TENANCE REPORT:	n being
Run three tests using a standard and must have a spread of .005 or used. X 0.10% STANDARD - MUST READ BETWEE 0.08% STANDARD - MUST READ BETWEE 0.04% STANDARD - MUST READ BETWEE 10.101 g/210L TEST 1 0.101 g/210L TEST INDICATE THE NUMBER OF BREATH TESTS REFUSALS 0 004 5 .05 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION SATISFACTORILY AND WITHIN ESTABLISHED LIMITS OF STANDARD EXPERTION DESCRIBE 104/02/20	solution. All less. Mark the less. Mark the less. Mark the less of	three tests muche box corresponds of the local	ust be within ±5 onding to the state of the	andard solution 1 g/210L TENANCE REPORT: OVER .19 TO OPERATE	n being



Airgas USA LLC (LAB) 3500 Bernard Street St. Louis, Mo. 63103 Ph: (314) 533-3100 Fax: (314) 533-7328

Certificate of Analysis

Customer Name Exclusive Supplier Intoximeters, Inc. 2081 Craig Road St. Louis, Mo 63146 Test Date: 8-Nov-2023

Lot # AG331103 Model 108

Exp Date 7-Nov-2025 Cyl. Type 108

Component

Certified Concentration

Ethanol

Nitrogen

0.100 ± 2% BrAC (272 ppm)

Certification Traceable to N.I.S.T. RGM and to CRM Ethanol Standards:

RGM Serial No. Concentration EB0010581 391.8 ppm EB0010570 259.8 ppm 209.0 ppm EB0010285 EB0010561 103.7 ppm 52.22 ppm EB0010681

RGM Serial No. EB0010603 EB0010559 EB0010562 EB0010579

392.5 ppm 258.9 ppm 104.2 ppm 52.94 ppm

Concentration

CRM Serial No. CC727481

Concentration 799.4 ppm 253.4 ppm

CRM Serial No. CC727493

CC727498

Concentration 389.8 ppm 150,2 ppm

Analytical Method: NDIR

CC727496

Digitally signed by:Quality Control Reason:Dry gas standard certification of analysis Location:Airgas USA LLC (Lab) Date:11.09.2023 19:42

Approved for Release:

Yusef Woods

ISO 17025:2017 A2LA accredited. Certificate Number 3082.06 ISO 17034:2016 A2LA accredited. Certificate Number 3082.07



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES **BREATH ALCOHOL PROGRAM**



PERMIT TYPE II

COLTON PENDERGRASS

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):

ALCO-SENSOR IV WITH PRINTER, INTOX EC/IR II

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections

577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo. Mike Massur 4/2/2024 DATE _ DIRECTOR OF STATE PUBLIC HEALTH LABORATORY NUMBER 240081 Daves J. Nichelson EXPIRES 4/2/2026_____ DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES LAB-4 (R6-10) MO 580-0771 (6-10)

STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES BREATH ALCOHOL PROGRAM

INSTRUMENT OPERATOR CARD

The named cardholder is authorized to operate an evidential breath alcohol instrument for the determination of the alcoholic content in breath form of expired air

Operator PENDERGRASS, COLTON

240081 Permit No Date Issued 4/2/2024 Date Expires 4/2/2026

