

MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

## RECEIVED

By Tracy Crews at 10:08 am, Jan 03, 2025

INTOX EC/IR II MAINTENANCE REPORT

REPORT #3

days). Complete this report whenever the instrument is serviced or repaired and whenever it is placed into service. Retain the original and send a copy within 15 days to the Breath Alcohol Program, DHSS.  INTOX EC/IR II SN NAME OF AGENCY DATE OF INSPECTION  13044 Jefferson County Sheriff 12/31/2024  LOCATION OF INSTRUMENT (STREET AND CITY)  955 Windsor Harbor Rd IMPERIAL, MO. 16:09 CST  CHECKLIST: Place a mark in the box by each item if found to be satisfactory or is operating within established limits. (Write in observed values where determined). Unmarked items must be corrected before using instrument.						
INTOX EC/IR II SN  13044  LOCATION OF INSTRUMENT (STREET AND CITY)  955 Windsor Harbor Rd IMPERIAL, MO.  CHECKLIST: Place a mark in the box by each item if found to be satisfactory or is operating within established limits. (Write in observed values where determined). Unmarked items must be corrected before using instrument.						
Jefferson County Sheriff  12/31/2024  LOCATION OF INSTRUMENT (STREET AND CITY)  955 Windsor Harbor Rd IMPERIAL, MO.  CHECKLIST: Place a mark in the box by each item if found to be satisfactory or is operating within established limits. (Write in observed values where determined). Unmarked items must be corrected before using instrument.						
LOCATION OF INSTRUMENT (STREET AND CITY)  955 Windsor Harbor Rd IMPERIAL, MO.  CHECKLIST: Place a mark in the box by each item if found to be satisfactory or is operating within established limits. (Write in observed values where determined). Unmarked items must be corrected before using instrument.						
955 Windsor Harbor Rd IMPERIAL, MO.  16:09 CST  CHECKLIST: Place a mark in the box by each item if found to be satisfactory or is operating within established limits. (Write in observed values where determined). Unmarked items must be corrected before using instrument.						
CHECKLIST: Place a mark in the box by each item if found to be satisfactory or is operating within established limits. (Write in observed values where determined). Unmarked items must be corrected before using instrument.						
established limits. (Write in observed values where determined). Unmarked items must be corrected before using instrument.						
established limits. (Write in observed values where determined). Unmarked items must be corrected before using instrument.						
before using instrument.						
X DIAGNOSTIC RECORD						
X BLANK CHECK X CO2 CHECK						
X FC 1 TEMP X FLOW CHECK						
X SRC TEMP X FCB CHECK						
X DET TEMP X CRC COMP CHECK						
X STD 2 TEMP X PRINT TEST						
X ETH CHECK						
BREATH ANALYZER ACCURACY STANDARDS						
SIMULATOR SOLUTION X COMPRESSED ETHANOL-GAS MIXTURE						
X STANDARD SUPPLIER Intoximeters LOT# AG305902 EXP. DATE 02/28/2025						
SIMULATOR TEMP (34°C ±0.2°C) SIM. SN SIM. NIST EXP DATE						
SIM. NIST EXP DATE						
X CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT)						
Run three tests using a standard solution. All three tests must be within +5% of the standard value						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  TEST 1 0.100 g/210L  TEST 2 0.100 g/210L  TEST 3 0.100 g/210L						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  TEST 1 0.100 g/210L  TEST 2 0.100 g/210L  TEST 3 0.100 g/210L						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.  2 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  TEST 1 0.100 g/210L  TEST 2 0.100 g/210L  TEST 3 0.100 g/210L  TOUCATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  REFUSALS 0 004 0 .0509 0 .1014 0 .1519 0 OVER .19 0						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.    0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.  2 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  TEST 1 0.100 g/210L  TEST 2 0.100 g/210L  TEST 3 0.100 g/210L  TOUCATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  REFUSALS 0 004 0 .0509 0 .1014 0 .1519 0 OVER .19 0						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.    0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.    0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.    0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.    0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.    0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  TEST 1 0.100 g/210L TEST 2 0.100 g/210L TEST 3 0.100 g/210L  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  REFUSALS 0 004 0 .0509 0 .1014 0 .1519 0 OVER .19 0  LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN ESTABLISHED LIMITS (USE OTHER SIDE IF NECESSARY).						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.  2 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  TEST 1 0.100 g/210L TEST 2 0.100 g/210L TEST 3 0.100 g/210L  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  REFUSALS 0 004 0 .0509 0 .1014 0 .1519 0 OVER .19 0  LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN ESTABLISHED LIMITS (USE OTHER SIDE IF NECESSARY).  INSPECTING OFFICER SIGNATURE S						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.  2 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  TEST 1 0.100 g/210L  TEST 2 0.100 g/210L  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  REFUSALS 0 004 0 .0509 0 .1014 0 .1519 0 OVER .19 0  LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN ESTABLISHED LIMITS (USE OTHER SIDE IF NECESSARY).  TYPE II PERMITYNUMBER PRINT FULL NAME REED, ZACHARY  TYPE II PERMITYNUMBER EXPERATION DATE TELEPHONE NUMBER						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.  X 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0.038% AND 0.084% INCLUSIVE  TEST 1 0.100 g/210L  TEST 2 0.100 g/210L  TEST 2 0.100 g/210L  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  REFUSALS 0 004 0 .0509 0 .1014 0 .1519 0 OVER .19 0  LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN ESTABLISHED LIMITS (USE OTHER SIDE IF NECESSARY).  INSPECTING OFFICER SIGNATURE  SIGNATURE  PRINT FULL NAME  REED, ZACHARY						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.  20.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  TEST 1 0.100 g/210L TEST 2 0.100 g/210L TEST 3 0.100 g/210L  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  REFUSALS 0 004 0 .0509 0 .1014 0 .1519 0 OVER .19 0  LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN ESTABLISHED LIMITS (USE OTHER SIDE IF NECESSARY).  INSPECTING OFFICER  SIGNATURE  SIGNATURE  TYPE II PERMIT NUMBER EXPIRATION DATE TELEPHONE NUMBER (636 ) 797-5000						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.  20.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  TEST 1 0.100 g/210L  TEST 2 0.100 g/210L  TEST 3 0.100 g/210L  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  REFUSALS 0 004 0 .0509 0 .1014 0 .1519 0 OVER .19 0  LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN ESTABLISHED LIMITS (USE OTHER SIDE IF NECESSARY).  INSPECTING OFFICER  SIGNATURE  TYPE II PERMITYNUMBER  REED, ZACHARY  TYPE II PERMITYNUMBER  REED, ZACHARY  TELEPHONE NUMBER  (636) 797-5000  RETURN COMPLETED REPORT TO THE:						
and must have a spread of .005 or less. Mark the box corresponding to the standard solution being used.  20.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  TEST 1 0.100 g/210L TEST 2 0.100 g/210L TEST 3 0.100 g/210L  INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  REFUSALS 0 004 0 .0509 0 .1014 0 .1519 0 OVER .19 0  LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN ESTABLISHED LIMITS (USE OTHER SIDE IF NECESSARY).  INSPECTING OFFICER  SIGNATURE  SIGNATURE  TYPE II PERMITTNUMBER EXPIRATION DATE TELEPHONE NUMBER (636 ) 797-5000						