

MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

#### INTOX DMT MAINTENANCE REPORT

**RECEIVED** By Tracy Crews at 8:18 am, Jul 23, 2024

**REPORT #1** 

Retain the original and send a copy within 15 of INTOX DMT SN NAME OF AGENCY	(		DATE OF INSPEC		
500257 St. James	Police Dept		07/18/202 TIME OF INSPEC		
200 N. Bourbeuse Street, St. James, M	O 65559		19:31:44		
CHECKLIST: Place a mark in the box by each values where determined). Unmarked items m	h item if found to b just be corrected b	e satisfactory or is o before using instrum	pperating within established ent.	limits. (Write in observed	
DIAGNOSTIC RECORD					
DATE AND TIME 07/18/2024 19:31:4	6		TOR		
PROGRAM		S FILTER 1			
SAMPLE CHAMBER 48.7°C		S FILTER	R 2		
BREATH TUBE 43.9°C			X FILTER 3		
DUMP			NAL STANDARD	e e e e e e e e e e e e e e e e e e e	
BREATH ANALYZER ACCURACY STAND	ARDS				
SIMULATOR STANDARD			RESSED ETHANOL-GAS	MIXTURE	
	Sec. Sec.			ATE 05 47 0005	
STANDARD SUPPLIER GUTH		LOT # 23180	EXP. D/	ATE 05/17/2025	
<ul> <li>SIMULATOR TEMP (34°C ± 0.2°C) <u>34.0</u></li> <li>CALIBRATION CHECK - (ONLY ONE S Run three tests using a standard. All three of .005 or less. Mark the box correspondi</li> <li>0.10% STANDARD - MUST REA</li> <li>0.08% STANDARD - MUST REA</li> </ul>	0 TANDARD IS TO tests must be with ng to the standard D BETWEEN 0.00 D BETWEEN 0.00	SIM. SN <u>MP2927</u> O BE USED PER M hin ±5% of the stand I being used. 95% AND 0.105% 76% AND 0.084%	SIM. NIST EXF MAINTENANCE REPORT) dard value and must have a NCLUSIVE NCLUSIVE	DATE 10/05/2024	
<ul> <li>SIMULATOR TEMP (34°C ± 0.2°C) <u>34.0</u></li> <li>CALIBRATION CHECK - (ONLY ONE S Run three tests using a standard. All three of .005 or less. Mark the box correspondi</li> <li>0.10% STANDARD - MUST REA</li> <li>0.08% STANDARD - MUST REA</li> <li>0.04% STANDARD - MUST REA</li> </ul>	0 TANDARD IS TC tests must be with ng to the standard D BETWEEN 0.0 D BETWEEN 0.0 D BETWEEN 0.0	SIM. SN <u>MP2927</u> D BE USED PER M hin ±5% of the stan I being used. 95% AND 0.105% 76% AND 0.084% 38% AND 0.042%	SIM. NIST EXF MAINTENANCE REPORT) dard value and must have a NCLUSIVE NCLUSIVE NCLUSIVE	DATE <u>10/05/2024</u> spread	
<ul> <li>SIMULATOR TEMP (34°C ± 0.2°C) 34.1</li> <li>CALIBRATION CHECK - (ONLY ONE S Run three tests using a standard. All three of .005 or less. Mark the box correspondi</li> <li>0.10% STANDARD - MUST REA</li> <li>0.08% STANDARD - MUST REA</li> <li>0.04% STANDARD - MUST REA</li> <li>TEST 1: 0.099</li> </ul>	0 TANDARD IS TO tests must be with ng to the standard D BETWEEN 0.00 D BETWEEN 0.00	SIM. SN <u>MP2927</u> D BE USED PER M hin ±5% of the stan I being used. 95% AND 0.105% 76% AND 0.084% 38% AND 0.042%	SIM. NIST EXF MAINTENANCE REPORT) dard value and must have a NCLUSIVE NCLUSIVE	DATE <u>10/05/2024</u> spread	
<ul> <li>SIMULATOR TEMP (34°C ± 0.2°C) 34.1</li> <li>CALIBRATION CHECK - (ONLY ONE S Run three tests using a standard. All three of .005 or less. Mark the box correspondi</li> <li>0.10% STANDARD - MUST REA</li> <li>0.08% STANDARD - MUST REA</li> <li>0.04% STANDARD - MUST REA</li> <li>TEST 1: 0.099</li> <li>PERFORM R.F.I. TEST</li> </ul>	0 TANDARD IS TO tests must be with ng to the standard D BETWEEN 0.0 D BETWEEN 0.0 D BETWEEN 0.0 TEST 2: 0.099	SIM. SN <u>MP2927</u> D BE USED PER M hin ±5% of the stand I being used. 95% AND 0.105% 76% AND 0.084% 38% AND 0.042%	SIM. NIST EXF MAINTENANCE REPORT) dard value and must have a NCLUSIVE NCLUSIVE NCLUSIVE TEST 3: 0.0	DATE <u>10/05/2024</u> spread	
<ul> <li>SIMULATOR TEMP (34°C ± 0.2°C) 34.0</li> <li>CALIBRATION CHECK - (ONLY ONE S Run three tests using a standard. All three of .005 or less. Mark the box correspondi</li> <li>0.10% STANDARD - MUST REA</li> <li>0.08% STANDARD - MUST REA</li> <li>0.04% STANDARD - MUST REA</li> <li>0.04% STANDARD - MUST REA</li> <li>TEST 1: 0.099</li> <li>PERFORM R.F.I. TEST</li> <li>INDICATE THE NUMBER OF BREATH TE</li> </ul>	0 TANDARD IS TO tests must be with ng to the standard D BETWEEN 0.0 D BETWEEN 0.0 D BETWEEN 0.0 TEST 2: 0.099 STS IN THE FOL	SIM. SN <u>MP2927</u> D BE USED PER M hin ±5% of the stand l being used. 95% AND 0.105% 76% AND 0.084% 38% AND 0.042%	SIM. NIST EXF MAINTENANCE REPORT) dard value and must have a NCLUSIVE NCLUSIVE NCLUSIVE TEST 3: 0.0 S SINCE THE LAST MAIN	DATE <u>10/05/2024</u> spread	
<ul> <li>SIMULATOR TEMP (34°C ± 0.2°C) 34.0</li> <li>CALIBRATION CHECK - (ONLY ONE S Run three tests using a standard. All three of .005 or less. Mark the box correspondi</li> <li>0.10% STANDARD - MUST REA</li> <li>0.08% STANDARD - MUST REA</li> <li>0.04% STANDARD - MUST REA</li> <li>0.04% STANDARD - MUST REA</li> <li>TEST 1: 0.099</li> <li>PERFORM R.F.I. TEST</li> <li>INDICATE THE NUMBER OF BREATH TE REFUSALS: 0</li> <li>004: 0</li> <li>LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR M</li> </ul>	D TANDARD IS TC tests must be with ng to the standard D BETWEEN 0.02 D BETWEEN 0.02 D BETWEEN 0.02 TEST 2: 0.099 STS IN THE FOL .0509: 0	SIM. SN <u>MP2927</u> D BE USED PER M hin ±5% of the stand I being used. 95% AND 0.105% 76% AND 0.084% 38% AND 0.042% 0 LOWING RANGE .1014: 0	SIM. NIST EXF MAINTENANCE REPORT) dard value and must have a NCLUSIVE NCLUSIVE TEST 3: 0.0 S SINCE THE LAST MAIN	DATE <u>10/05/2024</u> spread 999 NTENANCE REPORT: OVER .19: 0	
<ul> <li>☑ SIMULATOR TEMP (34°C ± 0.2°C) <u>34.4</u></li> <li>☑ CALIBRATION CHECK - (ONLY ONE S Run three tests using a standard. All three of .005 or less. Mark the box correspondi</li> <li>☑ 0.10% STANDARD - MUST REA</li> <li>☐ 0.08% STANDARD - MUST REA</li> <li>☐ 0.04% STANDARD - MUST REA</li> <li>☐</li></ul>	0 CartanDARD IS TO e tests must be with ng to the standard D BETWEEN 0.02 D BETWEEN 0.02 D BETWEEN 0.02 D BETWEEN 0.02 D BETWEEN 0.02 D BETWEEN 0.02 STS IN THE FOL .0509: 0	SIM. SN <u>MP2927</u> D BE USED PER M hin ±5% of the stand being used. 95% AND 0.105% 76% AND 0.084% 38% AND 0.042% 0 .LOWING RANGE .1014: ( 5 MADE TO RESTORE THE	SIM. NIST EXF MAINTENANCE REPORT) dard value and must have a NCLUSIVE NCLUSIVE TEST 3: 0.0 S SINCE THE LAST MAIN 1.1519: 0	DATE <u>10/05/2024</u> spread 999 NTENANCE REPORT: OVER .19: 0	
of .005 or less. Mark the box correspondi 0.10% STANDARD - MUST REA 0.08% STANDARD - MUST REA 0.04% STANDARD - MUST REA TEST 1: 0.099 PERFORM R.F.I. TEST INDICATE THE NUMBER OF BREATH TE REFUSALS: 0 004: 0 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR M	0 CartanDARD IS TO e tests must be with ng to the standard D BETWEEN 0.02 D BETWEEN 0.02 D BETWEEN 0.02 D BETWEEN 0.02 D BETWEEN 0.02 D BETWEEN 0.02 STS IN THE FOL .0509: 0	SIM. SN <u>MP2927</u> D BE USED PER M hin ±5% of the stand l being used. 95% AND 0.105% 76% AND 0.084% 38% AND 0.042% 0 LOWING RANGE .1014: C S MADE TO RESTORE THE PRINT FULL CHRIS	SIM. NIST EXF	DATE <u>10/05/2024</u> spread 999 NTENANCE REPORT: OVER .19: 0	



Missouri Department of Health and Senior Services

P.O. Box 570, Jefferson City, MO 65102- 7 Ph ne: 73-7 1-64 FAX: 73-7 1-6 1 RELAY MISS URI f r H a i g a d Sp ch Imp d 1-8 -73 -29 V CE 1-8 -73 -2466



Paula Nickelson Acting Director Michael L. Parson Governo

## SIMULATOR CERTIFICATION REPORT

#### SIMULATOR INFORMATION

Simulator Serial Number: MP2927 Manufacturer: Guth

Model Number: 12V500

Agency:

ST JAMES PD

Agency Address: 200 N BOURBEUSE ST, ST JAMES, MO 65559

1/23/2023

#### NIST THERMOMETER INFORMATION

Serial Number: 17KMM00689

Uncertainty: 0.02

Bias:

**Date of Certification:** 

Date of Expiration: 1/23/2024

0.00

#### **ENVIRONMENTAL CONDITIONS**

The environmental conditions during testing are within the tolerances of DHSS BAP method 3.

#### VERIFICATION RESULTS

Simulator Average 34.01 NIST Average 34.00 Combined Uncertainty .03

The combined uncertainty is calculated with a k=2 value.

#### ADJUSTMENT RESULTS

No adjustment was needed.

Date of testing:10/5/2023Certification Expiration:10/5/2024Simulator testing technician:R. SCHILDKNECHT

Notes on Condition: none

Deviation(s) from method: none

DHSS BAP Scientist Approving: Certification No:

MP2927 1052023

**BRIANNA MEDRANO** 

nian Mehra X

DHSS BAP Scientist Approving

Simulator Calibration Ce tification Issued by Lab Manager, DHSS BAP R s Da : 06/25/2022 B eath Alcohol P g am 1903 N t w d Driv , Suit 4 pla Bluff, MO 3901 DHSS BAP D cum t 3.6A R vis 2 g 1 f 1



#### CERTIFICATE OF ANALYSIS

Certified Alcohol Reference Solution for Simulator

Random Samples of Lot Number 23180 of Alcohol Reference Solution for Simulator were analyzed by gas chromatography on May 18, 2023, using a Perkin Elmer Gas Chromatograph Autosystem XL S/N: 610N9030209, and found to contain 0.1220% (w/vol) ethyl alcohol. The expiration date for this lot number is May 17, 2025 at 11:59 PM.

When used in a calibrated Simulator, operating at  $34^{\circ}C$  +/- .2°C, this solution will give a breath alcohol analysis instrument reading of 0.100 g/210L +/- 3%.

The alcohol and water used in this solution were free of test interfering substances.

Kaulen

Ted L. Pauley, President GUTH LABORATORIES, INC.

NIST Traceability:

Testing was conducted using Cerilliant Reference Standard lot number FN11172002 whose values are traceable to NIST.

All balances are calibrated annually by an outside agency using NIST traceable weights. Calibration verification is done prior to each use utilizing NIST traceable weights.



STATE OF MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES BREATH ALCOHOL PROGRAM



# **PERMIT** TYPE II CHRISTOPHER PIGG

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):

### **INTOX DMT**

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo.

DATE 2/28/2024

NUMBER 240059

EXPIRES 2/28/2026

MO 580-0771 (6-10)

DIRECTOR OF STATE PUBLIC HEALTH LABORATORY

Danes I. Nickelson

DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES

LAB-4 (R6-10)

