RECEIVED

By Tracy Crews at 10:56 am, Jan 13, 2025



MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

INTOX DMT MAINTENANCE REPORT

REPORT #1

	F AGENCY Louis County Into	ake		01/10			
ocation of instrument (street and city) 100 S. Central, Clayton MO				TIME OF IN:			
CHECKLIST: Place a mark in the box ralues where determined). Unmarked	by each item if fo	und to be satisfactory	y or is operating w	ithin establis	ned limits.	(Write in observed	
DIAGNOSTIC RECORD	items must be co	rected before dailing in	not differit.				
DATE AND TIME 01/10/2025	13:35:05		DETECTOR				
☑ PROGRAM		□ □	FILTER 1				
☑ SAMPLE CHAMBER 48.7°	С	□ □	FILTER 2				
☑ BREATH TUBE 48.1°C			FILTER 3				
☑ PUMP			INTERNAL STAN	DARD			
BREATH ANALYZER ACCURACY	STANDARDS	ED 1					
SIMULATOR STANDARD		□ COMPRESSED ET		THANOL-G	AS MIXT	URE	
			LOT# 24110		EXP. DATE 03/05/2026		
STANDARD SUPPLIER GUTH		LOT#_24	110		. DATE	03/03/2020	
SIMULATOR TEMP (34°C ± 0.2° CALIBRATION CHECK - (ONL' Run three tests using a standard of .005 or less. Mark the box cor 0.10% STANDARD - MU	C) 34.0 ONE STANDAR All three tests mu responding to the IST READ BETW	SIM. SN SI RD IS TO BE USED st be within ±5% of th standard being used. EEN 0.095% AND 0. EEN 0.076% AND 0.	PER MAINTENA ne standard value	SIM. NIST ANCE REPO and must ha	EXP DAT	TE 05/23/2025	
SIMULATOR TEMP (34°C ± 0.2° CALIBRATION CHECK - (ONL' Run three tests using a standard of .005 or less. Mark the box cor □ 0.10% STANDARD - ML □ 0.08% STANDARD - ML	C) 34.0 ONE STANDAR All three tests must responding to the UST READ BETW UST READ BETW UST READ BETW	SIM. SN SI RD IS TO BE USED st be within ±5% of th standard being used. EEN 0.095% AND 0. EEN 0.076% AND 0.	PER MAINTENA ne standard value	SIM. NIST ANCE REPO and must ha	EXP DAT DRT) ve a sprea	TE 05/23/2025	
SIMULATOR TEMP (34°C ± 0.2° CALIBRATION CHECK - (ONL' Run three tests using a standard of .005 or less. Mark the box cor 0.10% STANDARD - ML 0.08% STANDARD - ML 0.04% STANDARD - ML	C) 34.0 ONE STANDAR All three tests must responding to the UST READ BETW UST READ BETW UST READ BETW	SIM. SN SI RD IS TO BE USED st be within ±5% of the standard being used. EEN 0.095% AND 0. EEN 0.076% AND 0. EEN 0.038% AND 0.	PER MAINTENA ne standard value	SIM. NIST ANCE REPO and must ha	EXP DAT DRT) ve a sprea	TE 05/23/2025	
SIMULATOR TEMP (34°C ± 0.2° CALIBRATION CHECK - (ONL' Run three tests using a standard of .005 or less. Mark the box cor 0.10% STANDARD - MU 0.08% STANDARD - MU 0.04% STANDARD - MU 1.004% STANDARD	C) 34.0 Y ONE STANDAF All three tests mu responding to the IST READ BETW UST READ BETW UST READ BETW TEST	SIM. SN SI RD IS TO BE USED st be within ±5% of the standard being used. EEN 0.095% AND 0. EEN 0.076% AND 0. EEN 0.038% AND 0. 2: 0.100	D2671 PER MAINTENA ne standard value105% INCLUSIVE .084% INCLUSIVE	SIM. NIST ANCE REPO and must ha E E TEST 3	EXP DAT ORT) ve a sprea	TE 05/23/2025	
SIMULATOR TEMP (34°C ± 0.2° CALIBRATION CHECK - (ONL' Run three tests using a standard of .005 or less. Mark the box cor 0.10% STANDARD - MU 0.08% STANDARD - MU 0.04% STANDARD - MU 0.04% STANDARD - MU DEST 1: 0.100 PERFORM R.F.I. TEST	C) 34.0 Y ONE STANDAF All three tests mu responding to the IST READ BETW UST READ BETW UST READ BETW TEST	SIM. SN SI RD IS TO BE USED st be within ±5% of the standard being used. EEN 0.095% AND 0. EEN 0.076% AND 0. EEN 0.038% AND 0. 2: 0.100	D2671 PER MAINTENA ne standard value105% INCLUSIVE .084% INCLUSIVE	SIM. NIST ANCE REPO and must ha E E TEST 3	EXP DAT ORT) ve a sprea : 0.100	TE 05/23/2025	
SIMULATOR TEMP (34°C ± 0.2° CALIBRATION CHECK - (ONL' Run three tests using a standard of .005 or less. Mark the box cor 0.10% STANDARD - MU 0.08% STANDARD - MU 0.04% STANDARD - MU 0.04% STANDARD - MU EST 1: 0.100 PERFORM R.F.I. TEST NDICATE THE NUMBER OF BRE REFUSALS: 0 004: 20 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER	C) 34.0 ONE STANDAF All three tests mu responding to the IST READ BETW IST READ BETW IST READ BETW ATH TESTS IN 1 .050	SIM. SN SI RD IS TO BE USED st be within ±5% of the standard being used. EEN 0.095% AND 0. EEN 0.076% AND 0. 2: 0.100 THE FOLLOWING R 9: 1	PER MAINTENA ne standard value 	SIM. NIST ANCE REPO and must ha E E TEST 3 THE LAST	EXP DAT ORT) ve a sprea : 0.100 MAINTEN	NANCE REPORT: OVER .19: 0	
SIMULATOR TEMP (34°C ± 0.2° CALIBRATION CHECK - (ONL' Run three tests using a standard of .005 or less. Mark the box cor 0.10% STANDARD - MU 0.08% STANDARD - MU 0.08% STANDARD - MU 0.04% STANDARD - MU DEST 1: 0.100 PERFORM R.F.I. TEST NDICATE THE NUMBER OF BREE REFUSALS: 0 004: 20 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER ESTABLISHED LIMITS (USE OTHER SIDE IF NECES	C) 34.0 ONE STANDAF All three tests mu responding to the IST READ BETW IST READ BETW IST READ BETW ATH TESTS IN 1 .050	SIM. SN SI RD IS TO BE USED st be within ±5% of the standard being used. EEN 0.095% AND 0. EEN 0.076% AND 0. 2: 0.100 THE FOLLOWING R 9: 1	PER MAINTENA ne standard value 	SIM. NIST ANCE REPO and must ha E E TEST 3 THE LAST	EXP DAT ORT) ve a sprea : 0.100 MAINTEN	NANCE REPORT: OVER .19: 0	
SIMULATOR TEMP (34°C ± 0.2° CALIBRATION CHECK - (ONL' Run three tests using a standard of .005 or less. Mark the box cor 0.10% STANDARD - MU 0.08% STANDARD - MU 0.08% STANDARD - MU 0.04% STANDARD - MU DEST 1: 0.100 PERFORM R.F.I. TEST NDICATE THE NUMBER OF BREE REFUSALS: 0 004: 20 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER ESTABLISHED LIMITS (USE OTHER SIDE IF NECES	C) 34.0 ONE STANDAF All three tests mu responding to the IST READ BETW IST READ BETW IST READ BETW ATH TESTS IN 1 .050	SIM. SN SI RD IS TO BE USED st be within ±5% of the standard being used. EEN 0.095% AND 0. EEN 0.076% AND 0. 2: 0.100 THE FOLLOWING R 9: 1	PER MAINTENA ne standard value 	SIM. NIST ANCE REPO and must ha E E TEST 3 THE LAST	EXP DAT ORT) ve a sprea : 0.100 MAINTEN	NANCE REPORT: OVER .19: 0	
SIMULATOR TEMP (34°C ± 0.2° CALIBRATION CHECK - (ONL' Run three tests using a standard of .005 or less. Mark the box cor 0.10% STANDARD - MU 0.08% STANDARD - MU 0.08% STANDARD - MU 0.04% STANDARD - MU EST 1: 0.100 PERFORM R.F.I. TEST NDICATE THE NUMBER OF BRE REFUSALS: 0 004: 20 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER ESTABLISHED LIMITS (USE OTHER SIDE IF NECES	C) 34.0 ONE STANDAF All three tests mu responding to the IST READ BETW IST READ BETW IST READ BETW ATH TESTS IN 1 .050	SIM. SN SI RD IS TO BE USED st be within ±5% of the standard being used. EEN 0.095% AND 0. EEN 0.076% AND 0. 2: 0.100 THE FOLLOWING R 9: 1	PER MAINTENA ne standard value 	SIM. NIST ANCE REPO and must ha E E TEST 3 THE LAST	EXP DAT ORT) ve a sprea : 0.100 MAINTEN	NANCE REPORT: OVER .19: 0	
SIMULATOR TEMP (34°C ± 0.2° CALIBRATION CHECK - (ONL' Run three tests using a standard of .005 or less. Mark the box cor 0.10% STANDARD - MU 0.08% STANDARD - MU 0.08% STANDARD - MU 0.04% STANDARD - MU EST 1: 0.100 PERFORM R.F.I. TEST NDICATE THE NUMBER OF BRE REFUSALS: 0 004: 20 LIST ANY NEW PARTS AND DESCRIBE ANY ALTER ESTABLISHED LIMITS (USE OTHER SIDE IF NECES	C) 34.0 ONE STANDAF All three tests mu responding to the IST READ BETW IST READ BETW IST READ BETW ATH TESTS IN 1 .050	SIM. SN SI RD IS TO BE USED st be within ±5% of the standard being used. EEN 0.095% AND 0. EEN 0.076% AND 0. 2: 0.100 THE FOLLOWING R 9: 1	PER MAINTENA ne standard value 	SIM. NIST ANCE REPO and must ha E E TEST 3 THE LAST	EXP DAT ORT) ve a sprea : 0.100 MAINTEN	NANCE REPORT: OVER .19: 0	
SIMULATOR TEMP (34°C ± 0.2° CALIBRATION CHECK - (ONL' Run three tests using a standard of .005 or less. Mark the box cor 0.10% STANDARD - MU 0.08% STANDARD - MU 0.08% STANDARD - MU 0.04% STANDARD - MU EST 1: 0.100 PERFORM R.F.I. TEST NDICATE THE NUMBER OF BREE REFUSALS: 0 004: 20 IST ANY NEW PARTS AND DESCRIBE ANY ALTER ESTABLISHED LIMITS (USE OTHER SIDE IF NECES	C) 34.0 ONE STANDAF All three tests mu responding to the IST READ BETW IST READ BETW IST READ BETW ATH TESTS IN 1 .050	SIM. SN SI RD IS TO BE USED st be within ±5% of the standard being used. EEN 0.095% AND 0. EEN 0.076% AND 0. 2: 0.100 THE FOLLOWING R 9: 1	PER MAINTENA ne standard value 	SIM. NIST ANCE REPO and must ha E E TEST 3 THE LAST	EXP DAT ORT) ve a sprea : 0.100 MAINTEN	NANCE REPORT: OVER .19: 0	
SIMULATOR TEMP (34°C ± 0.2° CALIBRATION CHECK - (ONL' Run three tests using a standard of .005 or less. Mark the box cor 0.10% STANDARD - MU 0.08% STANDARD - MU 0.04% STANDARD - MU 0.04% STANDARD - MU 1.000 STANDARD - MU 1.00	C) 34.0 ONE STANDAF All three tests mu responding to the IST READ BETW IST READ BETW IST READ BETW ATH TESTS IN 1 .050	SIM. SN SI RD IS TO BE USED st be within ±5% of the standard being used. EEN 0.095% AND 0. EEN 0.076% AND 0. 2: 0.100 THE FOLLOWING R 9: 1	PER MAINTENA ne standard value 	SIM. NIST ANCE REPO and must ha E E TEST 3 THE LAST	EXP DAT ORT) ve a sprea : 0.100 MAINTEN	NANCE REPORT: OVER .19: 0	
SIMULATOR TEMP (34°C ± 0.2° CALIBRATION CHECK - (ONL' Run three tests using a standard of .005 or less. Mark the box cor	C) 34.0 ONE STANDAF All three tests mu responding to the IST READ BETW IST READ BETW IST READ BETW ATH TESTS IN 1 .050	SIM. SN SI RD IS TO BE USED st be within ±5% of the standard being used. EEN 0.095% AND 0. EEN 0.076% AND 0. EEN 0.038% AND 0. THE FOLLOWING R 9: 1 .1	PER MAINTENA ne standard value 	SIM. NIST ANCE REPO and must ha E E TEST 3 THE LAST	EXP DAT ORT) ve a sprea : 0.100 MAINTEN	NANCE REPORT: OVER .19: 0	
of .005 or less. Mark the box cor 0.10% STANDARD - MU 0.08% STANDARD - MU 0.04% STANDARD - MU TEST 1: 0.100 PERFORM R.F.I. TEST INDICATE THE NUMBER OF BRE	C) 34.0 ONE STANDAF All three tests mu responding to the IST READ BETW IST READ BETW IST READ BETW ATH TESTS IN 1 .050	SIM. SN SI RD IS TO BE USED st be within ±5% of the standard being used. EEN 0.095% AND 0. EEN 0.076% AND 0. EEN 0.038% AND 0. 22: 0.100 THE FOLLOWING R 9: 1 .1	PER MAINTENA ne standard value 	SIM. NIST ANCE REPORT AND E REPORT AND E REPORT E E E TEST 3 THE LAST .1519 TO OPERATE SA	EXP DAT ORT) ve a sprea : 0.100 MAINTEN	NANCE REPORT: OVER .19: 0	



CERTIFICATE OF ANALYSIS

Certified Alcohol Reference Solution for Simulator

Random Samples of Lot Number 24110 of
Alcohol Reference Solution for Simulator were analyzed by
gas chromatography on March 6, 2024, using a Perkin Elmer Gas
Chromatograph Autosystem XL S/N: 610N9030209, and found to contain
0.1215% (w/vol) ethyl alcohol. The expiration date for this lot
number is March 5, 2026 at 11:59 PM.

When used in a calibrated Simulator, operating at 34°C +/- .2°C, this solution will give a breath alcohol analysis instrument reading of 0.100 g/210L +/- 3%.

The alcohol and water used in this solution were free of test interfering substances.

Ted L. Pauley, President GUTH LABORATORIES, INC.

NIST Traceability:

Testing was conducted using Cerilliant Reference Standard lot number FN03072301 whose values are traceable to NIST.

All balances are calibrated annually by an outside agency using NIST traceable weights. Calibration verification is done prior to each use utilizing NIST traceable weights.



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES
BREATH ALCOHOL PROGRAM



4 4817

PERMIT TYPE II

CHARLES A. WARDIN

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):

INTOX DMT

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo.

NUMBER 240251

EXPIRES 12/11/2026

12000

DIRECTOR STATE PUBLIC HEALTH LABORATORY

DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES

LAB-4 (R6-10)

MO 580-0771 (6-10)



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES BREATH ALCOHOL PROGRAM

INSTRUMENT OPERATOR CARD

The named cardholder is authorized to operate an evidential breath alcohol instrument for the determination of the alcoholic content in breath form of expired air in Missouri.

Operator WARDIN, CHARLES

Permit No 240251

Date Issued 12/11/2024 Date Expires 12/11/2026

