## RECEIVED

By Tracy Crews at 10:09 am, Mar 06, 2025



MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

## INTOX DMT MAINTENANCE REPORT

REPORT #1

Complete this report at the time of the regular mo Complete this report whenever the instrument is a Retain the original and send a copy within 15 day	serviced or repaired and when	ver it is placed into service.	v ∴	
NAME OF AGENCY 500111 NAME OF AGENCY Missouri State Highway Patrol			DATE OF INSPECTION 03/05/2025	
LOCATION OF INSTRUMENT (STREET AND CITY) 211 South New Madrid, Benton, Missouri			TIME OF INSPECTION 12:43:13	
CHECKLIST: Place a mark in the box by each item if found to be satisfactory or is operating within established limits. (Write in observed values where determined). Unmarked items must be corrected before using instrument.				
☑ DIAGNOSTIC RECORD				
DATE AND TIME <u>03/05/2025 12:43:15</u> ☑ DETECTOR				
☑ PROGRAM  ☑ FILTER 1				
☑ SAMPLE CHAMBER 48.8°C ☑ FILTER 2				
☑ BREATH TUBE 48.1°C  ☑ FILTER 3				
☑ PUMP ☑ INTERNAL STANDARD				
BREATH ANALYZER ACCURACY STANDARDS				
☐ SIMULATOR STANDARD ☐ COMPRESSED ETHANOL-GAS MIXTURE				
☑ STANDARD SUPPLIER INTOXIMETER	LOT#_AG32	0501 EXP. [	DATE <u>07/24/2025</u>	
SIMULATOR TEMP (34°C ± 0.2°C)	SIM. SN	SIM. NIST EX	(P DATE	
<ul> <li>         □ CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT)         Run three tests using a standard. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Mark the box corresponding to the standard being used.         □ 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE         □ 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.044% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.044% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.044% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWEEN 0.044% INCLUSIVE         □ 0.04% STANDARD - MUST READ BETWE</li></ul>				
TEST 1: 0.099	TEST 2: 0.098		TEST 3: 0.099	
☑ PERFORM R.F.I. TEST				
INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:				
REFUSALS: 0 004: 0	.0509: 1	4: 0 .1519: 2	OVER .19: 0	
LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MOD ESTABLISHED LIMITS (USE OTHER SIDE IF NECESSARY)	I DIFICATION THAT WAS MADE TO RESTOR	THE INSTRUMENT TO OPERATE SATISF	ACTORILY AND WITHIN	
ADVANCED TIME FORWARD 2 MINUTES				
INSPECTING OFFICER				
SIGNATURE /54. do/	ADAM R SHIPLEY			
TYPE II PERMIT NUMBER 230275	EXPIRATION DATE 11/28/2025	TELEPHONE NUMBER 573-840-9500		
RETURN COMPLETED REPORT TO THE  Breath Alcohol Program, Missouri Department of Health and Senior Services by mail, fax, or email				