

By Tracy Crews at 11:29 am, Mar 12, 2025



MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

REPORT #1

complete this report at the time of the complete this report whenever the instruction the original and send a copy with the complete this report whenever the instruction the original and send a copy with the complete this report at the time of the complete this report whenever the instruction the complete this report whenever the complete	thin 15 days to the Bre	atti Alconori Togran	ii, Di 166.	DATE OF INSPECTION 03/05/2025	
500132 Missouri State Highway Patrol				TIME OF INSPECTION	
OCATION OF INSTRUMENT (STREET AND CITY) Potosi PD #1 Police Plaza, Potos	si			18:13:37	(M/site in observed
CHECKLIST: Place a mark in the box ralues where determined). Unmarked	by each item if found items must be correct	to be satisfactory or ed before using inst	is operating wrument.	vithin established limits.	(VVIILE III ODSEIVEG
DIAGNOSTIC RECORD					
DATE AND TIME 03/05/2025	18:13:41	<b>⊠</b> DE	TECTOR		
☑ PROGRAM			TER 1		
☑ SAMPLE CHAMBER 48.8°	С		TER 2	11.5	
☑ BREATH TUBE 44.9°C	_		TER 3		
☑ PUMP		⊠ IN1	TERNAL STA	NDARD	
BREATH ANALYZER ACCURACY	STANDARDS			ETHANOL CAS MIVT	IDC
☐ SIMULATOR STANDARD				ETHANOL-GAS MIXT	ASSESSED AND ASSESSED
T ATTIVIDADO CUIDOUED INTO	KIMETERS	LOT # <u>AG40</u>	00203		01/02/2026
XI STANDARD SUPPLIER INTO				LOUIS EVE EVE DA	TC
<ul> <li>SIMULATOR TEMP (34°C ± 0.2°</li> <li>         CALIBRATION CHECK - (ONL Run three tests using a standard of .005 or less. Mark the box co.         <ul> <li>■ 0.10% STANDARD - MI</li> </ul> </li> </ul>	Y ONE STANDARD I All three tests must by tresponding to the star UST READ BETWEE	N 0.095% AND 0.10	5% INCLUSI	<b>VE</b>	
☐ SIMULATOR TEMP (34°C ± 0.2°  ☐ CALIBRATION CHECK - (ONL Run three tests using a standard of .005 or less. Mark the box co ☐ 0.10% STANDARD - MI ☐ 0.08% STANDARD - MI	Y ONE STANDARD I I. All three tests must b rresponding to the star JST READ BETWEEL UST READ BETWEEL	S TO BE USED Ple within ±5% of the ndard being used. N 0.095% AND 0.10	05% INCLUSIN 184% INCLUSIN	IANCE REPORT) e and must have a spre VE	
☐ SIMULATOR TEMP (34°C ± 0.2°  ☐ CALIBRATION CHECK - (ONL Run three tests using a standard of .005 or less. Mark the box co	Y ONE STANDARD I I. All three tests must b rresponding to the star JST READ BETWEEL UST READ BETWEEL	S TO BE USED Ple within ±5% of the address of the second o	05% INCLUSIN 184% INCLUSIN	IANCE REPORT) e and must have a spre VE	
□ SIMULATOR TEMP (34°C ± 0.2° □ CALIBRATION CHECK - (ONL Run three tests using a standard of .005 or less. Mark the box co □ 0.10% STANDARD - MI □ 0.08% STANDARD - MI □ 0.04% STANDARD - MI □ 0.04% STANDARD - MI	Y ONE STANDARD II. All three tests must be tresponding to the star UST READ BETWEED UST READ BETWEED UST READ BETWEED UST READ BETWEED TEST 2:	S TO BE USED Ple within ±5% of the ndard being used. N 0.095% AND 0.10 N 0.076% AND 0.08 N 0.038% AND 0.04	05% INCLUSIN 84% INCLUSIN 42% INCLUSIN	IANCE REPORT) e and must have a spre VE VE VE TEST 3: 0.099	ad
□ SIMULATOR TEMP (34°C ± 0.2° □ CALIBRATION CHECK - (ONL Run three tests using a standard of .005 or less. Mark the box co □ 0.10% STANDARD - MI □ 0.08% STANDARD - MI □ 0.04% STANDARD - MI □ 0.04% STANDARD - MI	Y ONE STANDARD II. All three tests must be tresponding to the star UST READ BETWEED UST READ BETWEED UST READ BETWEED UST READ BETWEED TEST 2:	S TO BE USED Ple within ±5% of the ndard being used. N 0.095% AND 0.10 N 0.076% AND 0.08 N 0.038% AND 0.04	05% INCLUSIN 84% INCLUSIN 42% INCLUSIN	IANCE REPORT) e and must have a spre VE VE VE TEST 3: 0.099	NANCE REPORT:
□ SIMULATOR TEMP (34°C ± 0.2°  □ CALIBRATION CHECK - (ONL Run three tests using a standard of .005 or less. Mark the box co □ 0.10% STANDARD - MI □ 0.08% STANDARD - MI □ 0.04% STANDARD - MI  TEST 1: 0.099 □ PERFORM R.F.I. TEST  INDICATE THE NUMBER OF BRI	Y ONE STANDARD II. All three tests must be tresponding to the star JST READ BETWEEL UST READ BETWEEL UST READ BETWEEL TEST 2:	S TO BE USED Ple within ±5% of the edard being used. N 0.095% AND 0.10 N 0.076% AND 0.08 N 0.038% AND 0.04 0.099	05% INCLUSINGES SINCE	IANCE REPORT) e and must have a spre  VE  VE  TEST 3: 0.099  E THE LAST MAINTE	NANCE REPORT:
□ SIMULATOR TEMP (34°C ± 0.2°  □ CALIBRATION CHECK - (ONL Run three tests using a standard of .005 or less. Mark the box co □ 0.10% STANDARD - MI □ 0.08% STANDARD - MI □ 0.04% STANDARD - MI  TEST 1: 0.099 □ PERFORM R.F.I. TEST  INDICATE THE NUMBER OF BRI  REFUSALS: 0 004: 20	Y ONE STANDARD II. All three tests must be tresponding to the start UST READ BETWEED UST READ BETWEED TEST 2:  EATH TESTS IN THE0509: ( ERATION OR MODIFICATION THE	S TO BE USED Ple within ±5% of the edard being used. N 0.095% AND 0.10 N 0.076% AND 0.08 N 0.038% AND 0.04 0.099	05% INCLUSINGES SINCE	IANCE REPORT) e and must have a spre  VE  VE  TEST 3: 0.099  E THE LAST MAINTE	NANCE REPORT:
□ CALIBRATION CHECK - (ONL Run three tests using a standard of .005 or less. Mark the box co     □ 0.10% STANDARD - MI     □ 0.08% STANDARD - MI     □ 0.04% STANDARD - MI     □ 0.04% STANDARD - MI     □ 0.04% STANDARD - MI     □ 1.0099      □ PERFORM R.F.I. TEST  INDICATE THE NUMBER OF BRI	Y ONE STANDARD II. All three tests must be tresponding to the start UST READ BETWEED UST READ BETWEED TEST 2:  EATH TESTS IN THE0509: ( ERATION OR MODIFICATION THE	S TO BE USED Ple within ±5% of the edard being used. N 0.095% AND 0.10 N 0.076% AND 0.08 N 0.038% AND 0.04 0.099	05% INCLUSINGES SINCE	IANCE REPORT) e and must have a spre  VE  VE  TEST 3: 0.099  E THE LAST MAINTE	NANCE REPORT:
□ SIMULATOR TEMP (34°C ± 0.2°  □ CALIBRATION CHECK - (ONL Run three tests using a standard of .005 or less. Mark the box co □ 0.10% STANDARD - MI □ 0.08% STANDARD - MI □ 0.04% STANDARD - MI  TEST 1: 0.099 □ PERFORM R.F.I. TEST  INDICATE THE NUMBER OF BRI  REFUSALS: 0 004: 20	Y ONE STANDARD II. All three tests must be tresponding to the start UST READ BETWEED UST READ BETWEED TEST 2:  EATH TESTS IN THE0509: ( ERATION OR MODIFICATION THE	S TO BE USED Ple within ±5% of the edard being used. N 0.095% AND 0.10 N 0.076% AND 0.08 N 0.038% AND 0.04 0.099	05% INCLUSINGES SINCE	IANCE REPORT) e and must have a spre  VE  VE  TEST 3: 0.099  E THE LAST MAINTE	NANCE REPORT:
□ SIMULATOR TEMP (34°C ± 0.2°  □ CALIBRATION CHECK - (ONL Run three tests using a standard of .005 or less. Mark the box co □ 0.10% STANDARD - MI □ 0.08% STANDARD - MI □ 0.04% STANDARD - MI  TEST 1: 0.099 □ PERFORM R.F.I. TEST  INDICATE THE NUMBER OF BRI  REFUSALS: 0 004: 20	Y ONE STANDARD II. All three tests must be tresponding to the start UST READ BETWEED UST READ BETWEED TEST 2:  EATH TESTS IN THE0509: ( ERATION OR MODIFICATION THE	S TO BE USED Ple within ±5% of the edard being used. N 0.095% AND 0.10 N 0.076% AND 0.08 N 0.038% AND 0.04 0.099	05% INCLUSINGES SINCE	IANCE REPORT) e and must have a spre  VE  VE  TEST 3: 0.099  E THE LAST MAINTE	NANCE REPORT:
□ SIMULATOR TEMP (34°C ± 0.2°  □ CALIBRATION CHECK - (ONL Run three tests using a standard of .005 or less. Mark the box co □ 0.10% STANDARD - MI □ 0.08% STANDARD - MI □ 0.04% STANDARD - MI  TEST 1: 0.099 □ PERFORM R.F.I. TEST  INDICATE THE NUMBER OF BRI  REFUSALS: 0 004: 20	Y ONE STANDARD II. All three tests must be tresponding to the start UST READ BETWEED UST READ BETWEED TEST 2:  EATH TESTS IN THE0509: ( ERATION OR MODIFICATION THE	S TO BE USED Ple within ±5% of the edard being used. N 0.095% AND 0.10 N 0.076% AND 0.08 N 0.038% AND 0.04 0.099	05% INCLUSINGES SINCE	IANCE REPORT) e and must have a spre  VE  VE  TEST 3: 0.099  E THE LAST MAINTE	NANCE REPORT:
□ SIMULATOR TEMP (34°C ± 0.2°  □ CALIBRATION CHECK - (ONL Run three tests using a standard of .005 or less. Mark the box co □ 0.10% STANDARD - MI □ 0.08% STANDARD - MI □ 0.04% STANDARD - MI  TEST 1: 0.099 □ PERFORM R.F.I. TEST  INDICATE THE NUMBER OF BRI  REFUSALS: 0 004: 20	Y ONE STANDARD II. All three tests must be tresponding to the start UST READ BETWEED UST READ BETWEED TEST 2:  EATH TESTS IN THE0509: ( ERATION OR MODIFICATION THE	S TO BE USED Ple within ±5% of the edard being used. N 0.095% AND 0.10 N 0.076% AND 0.08 N 0.038% AND 0.04 0.099	05% INCLUSINGES SINCE	IANCE REPORT) e and must have a spre  VE  VE  TEST 3: 0.099  E THE LAST MAINTE	NANCE REPORT:
□ SIMULATOR TEMP (34°C ± 0.2°  □ CALIBRATION CHECK - (ONL Run three tests using a standard of .005 or less. Mark the box co □ 0.10% STANDARD - MI □ 0.08% STANDARD - MI □ 0.04% STANDARD - MI  TEST 1: 0.099 □ PERFORM R.F.I. TEST  INDICATE THE NUMBER OF BRI  REFUSALS: 0	Y ONE STANDARD II. All three tests must be tresponding to the start UST READ BETWEED UST READ BETWEED TEST 2:  EATH TESTS IN THE0509: ( ERATION OR MODIFICATION THE	S TO BE USED Ple within ±5% of the edard being used. N 0.095% AND 0.10 N 0.076% AND 0.08 N 0.038% AND 0.04 0.099	05% INCLUSINGES SINCE	IANCE REPORT) e and must have a spre  VE  VE  TEST 3: 0.099  E THE LAST MAINTE	NANCE REPORT:
□ SIMULATOR TEMP (34°C ± 0.2°  □ CALIBRATION CHECK - (ONL Run three tests using a standard of .005 or less. Mark the box co □ 0.10% STANDARD - MI □ 0.08% STANDARD - MI □ 0.04% STANDARD - MI  TEST 1: 0.099 □ PERFORM R.F.I. TEST  INDICATE THE NUMBER OF BRI REFUSALS: 0	Y ONE STANDARD II. All three tests must be tresponding to the start UST READ BETWEED UST READ BETWEED TEST 2:  EATH TESTS IN THE0509: ( ERATION OR MODIFICATION THE	S TO BE USED PI e within ±5% of the indard being used. N 0.095% AND 0.10 N 0.076% AND 0.08 N 0.038% AND 0.04 0.099 E FOLLOWING RA 1 .10- INTERNATIONAL TO RESTOR	35% INCLUSING IN	IANCE REPORT) e and must have a spre  VE  VE  TEST 3: 0.099  E THE LAST MAINTE  .1519: 0  NT TO OPERATE SATISFACTOR	NANCE REPORT:
□ SIMULATOR TEMP (34°C ± 0.2°  □ CALIBRATION CHECK - (ONL Run three tests using a standard of .005 or less. Mark the box co □ 0.10% STANDARD - MI □ 0.08% STANDARD - MI □ 0.04% STANDARD - MI  TEST 1: 0.099 □ PERFORM R.F.I. TEST  INDICATE THE NUMBER OF BRI  REFUSALS: 0	Y ONE STANDARD II. All three tests must be tresponding to the start UST READ BETWEEN UST READ BETWEEN TEST 2:  EATH TESTS IN THE	S TO BE USED PI e within ±5% of the indard being used. N 0.095% AND 0.10 N 0.076% AND 0.08 N 0.038% AND 0.04 0.099 E FOLLOWING RA 1 .10- INTERNATIONAL TO RESTOR	NT FULL NAME THADEUS E I	IANCE REPORT) e and must have a spre  VE  VE  TEST 3: 0.099  E THE LAST MAINTE  .1519: 0  NT TO OPERATE SATISFACTOR	NANCE REPORT: